



公差表/General tolerances(mm)		0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±2
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	300/12	/	300/10
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	250/12	320/12	630/12
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4	4	4
螺丝扭矩/Torque Tightening(N·m/Lb·in)	/	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~2.5/26~12		
可距/Pitch(mm)/线数范围/Poles	5.08/N=02~24P		
剥线长度/Stripping length(mm)	9~10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		
MATERIAL:	SURFACE: /		

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD: LIGL	2020.06.22
CHKD: Mek	2020.06.22
DRAFT: HS	2016.08.30
NAME:	2EDGKDHG-5.08-XXP-1Y-00A(H)
DRAWING NO.:	2EDGKDHG-5.08-C01
TYPE:	CUSTOMER DRAWING
SCALE:	1.5:1 SHEET 1/1

DEGSON	宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD	
APPD: LIGL	2020.06.22
CHKD: Mek	2020.06.22
DRAFT: HS	2016.08.30
NAME:	2EDGKDHG-5.08-XXP-1Y-00A(H)
DRAWING NO.:	2EDGKDHG-5.08-C01
TYPE:	CUSTOMER DRAWING
SCALE:	1.5:1 SHEET 1/1

ITEM	NAME OF PART	MATERIAL	NOTES
1	Housing	PA66	UL94V-0
2	Cover	PA66	UL94V-0
3	Clamp	Copper alloy	Sn Plated
4	Spring	Stainless steel	/
5	Button	PA66	UL94V-0
6	R-Clasp	PA66	UL94V-0
7	L-Clasp	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE