



The certification mark is available on the left or right

精度等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±Z	±Z

5	Screw	Steel	M2/Zn Plated
4	Cage	Copper Alloy	M2/NI Plated
3	Clamp	Copper Alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/8	/	300/8
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	II/2		
污染度/Pollution Degree	450/77		
额定电压/电涌/Rated Voltage(V)/Current(A)	4		
额定冲击电压(kV)/Rate Impulse Voltage(kV)	M2, 0.2/1.77		
拧紧扭矩/ Torque Tightening(N·m/Lbin)	0.5~1.5/28~16		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	5.08/N=02~12P		
间距/Pitch(mm)	6~7		
剥线长度/Stripping length(mm)	-40~+105		
使用温度范围/Operating temperature(°C)	Yes		
符合RoHS要求/Conform to RoHS			

MATERIAL: /

SURFACE: /

DEGSON 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: 15EDGK-5.08-XXP-1Y-00A(H)

MAT NO.:	/
STATUS:	/
Appd: Lanch	2020.03.26
CHKD: YJZ	2020.03.26
DRAFT: HZD	2015.08.20
DRAWING NO.:	15EDGK-5.08-C01
TYPE:	CUSTOMER DRAWING
SCALE:	2:1
REV	T2
SHEET	1/1

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 2:1	SHEET
1					mm			1/1