



Pitch Range In mm		Nominal Dimension Range In mm						
Over	Over	Over	Over	Over	Over	Over	0.1/10	
6	10	10	30	60	100	150		
TO	TO	TO	TO	TO	TO	TO	≤	
6	10	24	30	60	100	150		
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2

PCB LAYOUT

MATERIAL: /
SURFACE: /

MAT NO.: /
STATUS: /

NAME: **DEGSSON** 宁波高松电子有限公司
NINGBO DEGSSON ELECTRICAL CO., LTD

NAME: **DEGSSON** 宁波高松电子有限公司
NINGBO DEGSSON ELECTRICAL CO., LTD

APPD: /
CHKD: /
DRAFT: Gao WG 2019.12.19

DRAWING NO.: DG1716-B-C01
TYPE: CUSTOMER DRAWING
SCALE: 1:1
SHEET 1/1

REV: /
ECN: /
DESCRIPTION: /
DRAFT: /
DATE: /

ITEM	NAME OF PART	MATERIAL	NOTES
5	Cover	PC	UL94 V-2
4	Nut	Steel	Zn Plated
3	Screw	Steel	Zn Plated
2	Pin Header	Copper Alloy	Sn Plated
1	Housing	PBT	UL94 V-0

UL 标准/UL Standard: B C D
额定电压/Rated Voltage(V)/Current(A) 600/80 600/80 600/5
额定扭矩/Torque Tightening(N.m/Lb.in) M6, 7.9/70.00
线径范围/线径/Wire Range(flexible)(AWG) 26~4
间距/Pitch(mm)/线数范围/Poles 17.00/N=04~14P
剥线长度/Stripping length(mm) 17
使用温度范围/Operating temperature(°C) -40~+120
符合RoHS环保要求/Conform to RoHS Yes

D C B A

1 2 3 4 5 6