DEGSON-Global Industrial Connector Manufacturer, Providing Customized Solution To All Partners.





DEGSON

DEGSON PTE. LTD.

Add: 2 Venture Drive#08-07 Vision Exchange Singapore 608526

www.degson.com

Tel: +0065-69808477

E-mail: sale@degson.com

The catalog is for reference purpose only and details are base on company's specifications

DEGSON website

LINKEDIN

ATP 24-E02

DEGSON

Automation

ISO9001 ISO14001 ISO45001 ISO80079-34 ISO/TS22163 IATF16949 RoHS REACH

Brief Introduction

Founded in 1990,DEGSON is well known as a comprehensive industrial solution provider,with UL-CTDP,VDE-TDAP and CNAS approved laboratory.DEGSON has passed ISO9001, ISO14001, ISO45001, IS080079-34,ISO/TS22163and IATF16949 Management System,and is a national high-tech enterprise.

DEGSON is engaged in supplying highly reliable and durable products to serve global customers. The company has a market-leading capability of mould processing, automatic manufacturing and advanced testing. DEGSON has the complete engineering ability to support global customers with the professional customization solution and value-added service.

DEGSON products are widely recognized in China, the USA, Germany, the UK, Italy, Spain, Turkey, Japan, South Korea, Singapore, etc. totally hundred countries and regions. DEGSON supply high quality products and provide professional services globally in the industry sectors likely industrial automation, instrument, electric power, railway, marine and offshore, new energy, E-bike industrial elevator, lighting, security, machinery, etc. The company won the recognition from partners among Fortune 500 and industry leading enterprises.

Based on the core values of “Clients First, Win-win Strategy, Responsibility Integrity, Excellence Pursuit”, DEGSON continuously integrates professional technical resources, R&D innovation, product manufacturing and technology application capabilities. Relying on global sales network, DEGSON aims to supply series of multiple varieties of high-quality products and services. We provide global customers with professional and quick connected application solutions, help customers continue to create value. DEGSON is making contributions to creating a smart and interconnected world.

DEGSON全球生产基地/研发中心
DEGSON Global Production Base and R&D Center

中国工厂
China site

高新区工厂
High-tech zone site

越南工厂
Vietnam site

南京竞争力中心
Nanjing R&D Center

洛阳研发中心
Luoyang R&D Center

DEGSON产品销往全球100多个国家和地区
DEGSON products are very popular more than 100 countries and areas.

DEGSON

UL-CTDP (USA), VDE-TDAP (Germany) and CNAS labs

Strategic cooperation with UL and VDE

① The general manager of UL global energy &technology division visit our company

② Sven Ohrke, President of VDE global services, comes to DEGSON to discuss strategic cooperation

③ VDE Laboratory Accreditation: In July 2010, VDE Issued the "VDE Authorized Laboratory" Certificate to DEGSON′ s laboratory.
UL laboratory accreditation: UL formally issued "UL WTDP" certification to DEGSON in March 2013.
On April, 2016, UL-CTDP.
On December, 2016, VDE-TDAP.
On January, 2017, Pass IRIS system audit.

ISO9001

ISO14001

IATF16949

ISO/TS 22163

UL - CTDP

VDE - TDAP

CNAS certificate

EX certificate

UL Certificates:10,Covering 4000+Products



VDE Certificates:178,Covering 3000+Products

TUV certificate

European invention patent

DEGSON

CONTENTS

DF50 series I/O



Small **Compact** **Convenient**

- The DF50 series I/O system is a new upgrade to the DF20 series
- Comprehensively improve I/O performance and compatibility
- Tool free use, greatly improving convenience
- The bus coupler supports 32 modules without the need for a power module

DF50 Series I/O Modules



Bus coupler

- The bus coupler comes with 8 digital inputs
- Supports multiple industrial Ethernet bus protocols
- The bus coupler support 32 modules

Tool free

- No tools required for module installation and disassembly
- No tools required to install and remove front connectors
- No tools required for wiring and dismantling

I/O module

- The I/O signal is independently powered, no need to add power module
- Digital input compatible with both PNP and NPN signals
- The analog input/output module is compatible with current and voltage, supports multiple ranges and each channel can be independently selected, and supports 2, 3, and 4 wire connection methods

Appearance

- 12mm ultra-thin volume, sharp blade shape
- The module has an identification system
- The module is grounded through the back metal connection DIN-rail
- Distinguish wiring holes with different functions by color





- PUSH-IN, no tools required for wire connection and disassembly

- Pluggable front connector



- Tool free manual operation lever
- The module is grounded through the back metal connection DIN-rail



- Bus coupler can support up to 32 modules



- Module has identification
- The module indicator system contains information such as signals, power, faults …

- Communication between modules through side connecting finger
- Module power supply is connected through side metal clips

Model	Functionality	Coupler Support Module List				
		DF50-C-PN-RT	DF50-C-EC	DF50-C-EN-IP	DF50-C-MD-TCP	DF50-C-CC-FB
Digital Module						
DF50-M-16DI-P/N	16DI,NPN/PNP	✓	✓	✓	✓	✓
DF50-M-16DI-P/N-TS	16DI,NPN/PNP including counting function	✓	✓	✓	✓	✗
DF50-M-32DI-P/N	32DI,NPN/PNP	✓	✓	✓	✓	✓
DF50-M-4DO-R	4DO Relay Output	✓	✓	✓	✓	✓
DF50-M-16DO-N	16DO NPN Output, Short-Circuit Protection	✓	✓	✓	✓	✓
DF50-M-16DO-P	16DO PNP Output, Short-Circuit Protection	✓	✓	✓	✓	✓
DF50-M-4DO-P-2A	4DO PNP Output	✓	✓	✓	✓	✓
DF50-M-32DO-N	32DO NPN Output, Short-Circuit Protection	✓	✓	✓	✓	✓
DF50-M-32DO-P	32DO PNP Output, Short-Circuit Protection	✓	✓	✓	✓	✓
DF50-M-16DI-16DO-N	16DI+16DO NPN	✓	✓	✓	✓	✓
DF50-M-16DI-16DO-P	16DI+16DO PNP	✓	✓	✓	✓	✓
Analog Module						
DF50-M-8AI-U-4	8AI,Voltage,16bit accuracy	✓	✓	✓	✓	✓
DF50-M-8AI-I-5	8AI, current, 16bit accuracy	✓	✓	✓	✓	✓
DF50-M-4AI-UI-6	4AI, voltage/current, 16bit accuracy	✓	✓	✓	✓	✓
DF50-M-4RTD-PT	4-channel RTD thermocouple module	✓	✓	✓	✓	✓
DF50-M-8TC	8-channel TC thermocouple module	✓	✓	✓	✓	✓
DF50-M-8AO-U-4	8AO,Voltage,16bit accuracy	✓	✓	✓	✓	✓
DF50-M-8AO-I-5	8AO,Current,16bit accuracy	✓	✓	✓	✓	✓
DF50-M-4AO-UI-6	4AO, voltage/current, 16bit accuracy	✓	✓	✓	✓	✓
Protocol Converter						
DF50-M-1COM-232/485/422	Serial Modules	✓	✓	✓	✗	✓
DF50-M-4IOL	IO-LINK Master Module	✓	✓	✗	✗	✗
Pulse counting/output						
DF50-M-2CNT-PIL-5	2-channel counting module input (5V)	✓	✓	✓	✓	✓
DF50-M-2CNT-PIL-24	2-channel counter module input (24V)	✓	✓	✓	✓	✓
Auxiliary Modules						
DF50-M-DC-U-0	0V Power Supply Common Terminal	✓	✓	✓	✓	✓
DF50-M-DC-U-24	24V Power Common Terminal	✓	✓	✓	✓	✓

PROFINET Bus coupler

CE RoHS

DF50-C-PN-RT

PROFINET, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two PROFINET interface (RJ45,10/100Mbps).
- With Media Redundancy Protocol.

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected to 24V is NPN, and connected to 0V is PNP

Specification

Product	DF50-C-PN-RT
Communication protocol	PROFINET
Transmission rate	10/100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	PROFINET specification
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Features	RT, conforming to Class C, MRP, automatic addressing/topology detection
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Minimum cycle time	1ms

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>11V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.6mA
Fault diagnosis	2.3mA
Typical input current	2.1mA
Fault diagnosis	2.4mA
Filtering time	0.2ms-40ms configurable
Hardware response time	200us

PROFINET Bus coupler

CE RoHS

Product	DF50-C-PN-RT

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	Max. 1.5A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Internal system rated voltage	5VDC
Internal system rated current	2.5A
Output power supply voltage	24V(20.4VDC~28.8VDC)
Output power supply current	0.75A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
STA	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
L/A0	Green : PORT 1 connected successfully.
	Green blinking : Port 1 has data communication.
L/A1	Green : PORT 2 connected successfully.
	Green blinking : Port 2 has data communication.
Sys 24v	Green:The system power input is normal
Sys 5v	Green: The system power output is normal
Feild 24v	Green:Load power input is normal
Load 24v	Green: The load power output is normal

EtherCAT Bus coupler

CE RoHS

DF50-C-EC

EtherCAT, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two EtherCAT interface (RJ45,100Mbps).

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected to 24V is NPN, and connected to 0V is PNP

Specification

Product	DF50-C-EC
Communication protocol	EtherCAT
Transmission rate	10/100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	EtherCAT specification, DIP switch
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Minimum cycle time	1ms
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Connection type	2 X RJ45, with switch function

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>11V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.6mA
Fault diagnosis	2.3mA
Typical input current	2.1mA
Fault diagnosis	2.4mA
Filtering time	0.2ms-40ms configurable
Hardware response time	200us

EtherCAT Bus coupler

CE RoHS

Product	DF50-C-EC

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	Max. 1.5A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Internal system rated voltage	5VDC
Internal system rated current	2.5A
Output power supply voltage	24V(20.4VDC~28.8VDC)
Output power supply current	0.75A

Mechanical

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
STA	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
L/A0	Green : PORT 1 connected successfully.
	Green blinking : Port 1 has data communication.
L/A1	Green : PORT 2 connected successfully.
	Green blinking : Port 2 has data communication.
Sys 24v	Green:The system power input is normal
Sys 5v	Green: The system power output is normal
Feild 24v	Green:Load power input is normal
Load 24v	Green: The load power output is normal

CC-Link IE Field Basic Bus coupler

CE RoHS

DF50-C-CC-FB

CC-Link IE Field Basic, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two CC-Link IE Field Basic interface (RJ45,100Mbps).

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected to 24V is NPN, and connected to 0V is PNP

Specification

Product	DF50-C-CC-FB	
Communication protocol	CC-Link IE Field Basic	
Transmission rate	10/100Mbps, full duplex	
Transmission distance	100 meters	
Number of logical stations	1~4	
Maximum data volume	RX, RY	4×64 bits
	RWr, RWw	4×32 Words
Number of extensible modules	32	
Address mapping	Yes	
Address setting	CC-Link IE Field Basic specification, DIP switch	
Transmission medium	Class 5 twisted pair cable	
Isolation method	Electrical isolation	
Alarm function	Diagnostic alarm, process alarm	
Connection type	2 X RJ45, with switch function	

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>11V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.6mA
Fault diagnosis	2.3mA
Typical input current	2.1mA
Fault diagnosis	2.4mA
Filtering time	0.2ms-40ms configurable
Hardware response time	200us

CC-Link IE Field Basic Bus coupler

CE RoHS

Product	DF50-C-CC-FB

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	Max. 1.5A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Internal system rated voltage	5VDC
Internal system rated current	2.5A
Output power supply voltage	24V(20.4VDC~28.8VDC)
Output power supply current	0.75A

Mechanical

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
STA	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
L/A0	Green : PORT 1 connected successfully.
	Green blinking : Port 1 has data communication.
L/A1	Green : PORT 2 connected successfully.
	Green blinking : Port 2 has data communication.
FP	Green: Load power input is normal
LP	Green: Load power output is normal
SP	Green:System power input is normal
S5	Green: System power output is normal

Ethernet/IP Bus coupler

CE RoHS

DF50-C-EN-IP

Ethernet/IP, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two Ethernet/IP interface (RJ45,100Mbps).

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected to 24V is NPN, and connected to 0V is PNP

Specification

Product	DF50-C-EN-IP
Communication protocol	Ethernet/IP
Transmission rate	10/100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	Ethernet/IP specification
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Minimum cycle time	1ms
Alarm function	Diagnostic alarm, process alarm
Connection type	2 X RJ45, with switch function

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>11V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.6mA
Fault diagnosis	2.3mA
Typical input current	2.1mA
Fault diagnosis	2.4mA
Filtering time	0.2ms-40ms configurable
Hardware response time	200us

Ethernet/IP Bus coupler

CE RoHS

Product	DF50-C-EN-IP

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	Max. 1.5A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Internal system rated voltage	5VDC
Internal system rated current	2.5A
Output power supply voltage	24V(20.4VDC~28.8VDC)
Output power supply current	0.75A

Mechanical

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
STA	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
L/A0	Green : PORT 1 connected successfully.
	Green blinking : Port 1 has data communication.
L/A1	Green : PORT 2 connected successfully.
	Green blinking : Port 2 has data communication.
FP	Green: Load power input is normal
LP	Green: Load power output is normal
SP	Green:System power input is normal
S5	Green: System power output is normal

ModbusTCP Bus coupler

CE RoHS

DF50-C-MD-TCP

ModbusTCP, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two ModbusTCP interface (RJ45,100Mbps).

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected to 24V is NPN, and connected to 0V is PNP

Specification

Product	DF50-C-MD-TCP
Communication protocol	ModbusTCP
Transmission rate	10/100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	ModbusTCP specification
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Minimum cycle time	1ms
Alarm function	Diagnostic alarm, process alarm
Connection type	2 X RJ45, with switch function

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>11V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.6mA
Fault diagnosis	2.3mA
Typical input current	2.1mA
Fault diagnosis	2.4mA
Filtering time	0.2ms-40ms configurable
Hardware response time	200us

ModbusTCP Bus coupler

CE RoHS

Product	DF50-C-MD-TCP

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	Max. 1.5A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Internal system rated voltage	5VDC
Internal system rated current	2.5A
Output power supply voltage	24V(20.4VDC~28.8VDC)
Output power supply current	0.75A

Mechanical

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
STA	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
L/A0	Green : PORT 1 connected successfully.
	Green blinking : Port 1 has data communication.
L/A1	Green : PORT 2 connected successfully.
	Green blinking : Port 2 has data communication.
FP	Green: Load power input is normal
LP	Green: Load power output is normal
SP	Green:System power input is normal
S5	Green: System power output is normal

Digital input module

CE RoHS

DF50-M-16DI-P/N

Digital input module, 16 ports, PNP, 24VDC

Pin Definition



Wiring Diagram



COM is the common terminal of DI0~DI17, connected to 24V is NPN, and connected to 0V is PNP

Specification

Product	DF50-M-16DI-P/N
Number of channels	16
Data size	2 Byte
Signal type	NPN & PNP
"0" signal voltage	>11V
"1" signal voltage	<5V
Connection type	1-line,Type 1/Type 3 , Refer to IEC 61131-2
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.6mA
Fault diagnosis	2.3mA
Typical input current	2.1mA
Fault diagnosis	2.4mA
Filtering time	0.2ms-40ms configurable,
Hardware response time	200us

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<30mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5…95%RH(non-condensing)

Digital input module

CE RoHS

DF50-M-32DI-P/N



Digital input module, 32-channel input, NPN & PNP,24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-32DI-P/N
Number of channels	32
Signal type	NPN & PNP
"off" signal voltage	Voltage difference <5VDC
"on" signal voltage	Voltage difference > 11VDC
Data size	4 Byte
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Switching frequency (resistive)	100Hz
Switching frequency (lamp)	10Hz
Switching frequency (inductive)	0.2Hz
Response time of protection circuit	< 100μs
Filtering time	0-40ms configurable

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 24mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Digital input counting module

CE RoHS

DF50-M-16DI-P/N-TS

Digital input module, 16 ports+Low speed counting, PNP, 24VDC

Pin Definition



COM is the common terminal of DI0~DI17, connected to 24V is NPN, and connected to 0V is PNP

Wiring Diagram



Specification

Product	DF50-M-16DI-P/N-TS
Number of channels	16
Data size	2 Byte
Signal type	NPN & PNP
"0" signal voltage	>11V
"1" signal voltage	<5V
Connection type	1-line,Type 1/Type 3 , Refer to IEC 61131-2
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.6mA
Fault diagnosis	2.3mA
Typical input current	2.1mA
Fault diagnosis	2.4mA
Filtering time	0.2ms-40ms configurable,
Hardware response time	200us
Count mode	Rising edge counting, falling edge counting, double-sided edge counting, configurable
Counting range	0-4294967296
Maximum counting frequency	500Hz

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<30mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5…95%RH(non-condensing)

Digital output module

CE RoHS

DF50-M-16DO-N

Digital output module, 16 ports, NPN, 24VDC

Pin Definition



Wiring Diagram



NPN

Specification

Product	DF50-M-16DO-N
Number of channels	16
Data size	2 Byte
Signal type	NPN
"0" signal voltage	High-impedance state
"1" signal voltage	0V DC
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Switching Frequency (resistance/lamp load)	<1000Hz
Switching Frequency (Inductive load)	<0.2Hz
Response Time of the Protection Circuit	< 100μs
Output current per channel(MAX)	500 mA
Load type	Inductive (7.2W/point, 24W/module), resistive (0.5A/point, 4A/module), light (5W/point, 18W/module)

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<75mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5…95%RH(non-condensing)

Digital output module

CE RoHS

DF50-M-16DO-P

Digital output module, 16 ports, PNP, 24VDC

Pin Definition



Wiring Diagram



PNP

Specification

Product	DF50-M-16DO-P
Number of channels	16
Data size	2 Byte
Signal type	PNP
"0" signal voltage	High-impedance state
"1" signal voltage	24V DC
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Switching Frequency (resistance/lamp load)	<1000Hz
Switching Frequency (Inductive load)	<0.2Hz
Response Time of the Protection Circuit	< 100μs
Output current per channel(MAX)	500 mA
Load type	Inductive (7.2W/point, 24W/module), resistive (0.5A/point, 4A/module), light (5W/point, 18W/module)

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<75mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5...95%RH(non-condensing)

Digital output module

CE RoHS

DF50-M-32DO-N



Digital output module, 32-channel output, NPN,24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-32DO-N
Number of channels	32
Signal type	NPN
"off" signal voltage	High resistance state
"on" signal voltage	0V DC
Data size	4 Byte
Connection type	1-line
Reverse protection	Yes
Overcurrent protection	Yes
Short circuit protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Switching frequency (resistive)	100Hz
Switching frequency (lamp)	10Hz
Switching frequency (inductive)	0.2Hz
Response time of protection circuit	< 100μs
Maximum output current per channel	500 mA

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 24mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5... 95%RH(non-condensing)

Digital output module

CE RoHS

DF50-M-32DO-P



Digital output module, 32-channel output, PNP,24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-32DO-P
Number of channels	32
Signal type	PNP
"off" signal voltage	High resistance state
"on" signal voltage	24V DC
Data size	4 Byte
Connection type	1-line
Reverse protection	Yes
Overcurrent protection	Yes
Short circuit protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Switching frequency (resistive)	100Hz
Switching frequency (lamp)	10Hz
Switching frequency (inductive)	0.2Hz
Response time of protection circuit	< 100μs
Maximum output current per channel	500 mA

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 24mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Digital input output module

CE RoHS

DF50-M-16DI-16DO-N



Digital input output module,
16-channel input+16-channel output, NPN, 24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-16DI-16DO-N
Number of channels	16-channel input+16-channel output
Signal type	NPN
"off" signal voltage	Voltage difference <5VDC
"on" signal voltage	Voltage difference ＞11VDC
Data size	4 Byte
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Switching frequency (resistive)	100Hz
Switching frequency (lamp)	10Hz
Switching frequency (inductive)	0.2Hz
Response time of protection circuit	< 100μs
Maximum output current per channel	500 mA
Filtering time	0-40ms configurable

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 24mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Digital input output module

CE RoHS

DF50-M-16DI-16DO-P



Digital input output module,
16-channel input+16-channel output, PNP, 24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-16DI-16DO-P
Number of channels	16-channel input+16-channel output
Signal type	PNP
"off" signal voltage	Voltage difference <5VDC
"on" signal voltage	Voltage difference > 11VDC
Data size	4 Byte
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Switching frequency (resistive)	100Hz
Switching frequency (lamp)	10Hz
Switching frequency (inductive)	0.2Hz
Response time of protection circuit	< 100μs
Maximum output current per channel	500 mA
Filtering time	0-40ms configurable

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 24mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Relay output module

CE RoHS

DF50-M-4DOR

Relay output module, 4 channels

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-4DOR
Number of channels	4
Contact type	N.O. Contacts
Maximum output current	Single-channel output maximum current: 5A, module output maximum current: 20A
Maximum switching voltage	250VAC/30VDC
Switching frequency	30Hz
Response time of the protection circuit	< 100μs
Leakage current	Maximum value: 0uA
Output impedance	<200mΩ
Output delay	OFF to ON :Max.100us, ON to OFF :Max.150us
Protective function	Over-temperature shutdown: 125°C typical
Load type	Resistive (5A/point, 20A/module)

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Digital output module

CE RoHS

DF50-M-4DO-P-2A

Digital output module, 4-channel, PNP, 24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-4DO-P-2A
Number of channels	4
Signal type	PNP
"off" signal voltage	High resistance state
"on" signal voltage	24V DC
Data size	1 Byte
Connection type	1-line
Switching frequency (resistive)	100Hz
Switching frequency (lamp)	10Hz
Switching frequency (inductive)	0.2Hz
Response time of protection circuit	< 100μs
Maximum output current per channel	2A
Leakage current	Maximum value: 0.18uA
Hardware response time	100us/100us
Output impedance	<200mΩ
Output delay time	OFF to ON :Max.100us, ON to OFF :Max.150us
Protection function	Over-temperature shutdown: 135°C typical Overcurrent protection: 4A. 2A typical Support short circuit protection
Load type	Inductive (7.2W/point, 24W/module), Resistive (0.5A/point, 4A/module), Lamp (5W/point, 18W/module)

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Digital output module

CE RoHS

DF50-M-4DO-N-2A

Digital output module, 4-channel, NPN, 24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-4DO-N-2A
Number of channels	4
Signal type	NPN
"off" signal voltage	High resistance state
"on" signal voltage	0 DC
Data size	1 Byte
Connection type	1-line
Switching frequency (resistive)	100Hz
Switching frequency (lamp)	10Hz
Switching frequency (inductive)	0.2Hz
Response time of protection circuit	< 100μs
Maximum output current per channel	2A
Leakage current	Maximum value: 0.18uA
Hardware response time	100us/100us
Output impedance	<200mΩ
Output delay time	OFF to ON :Max.100us, ON to OFF :Max.150us
Protection function	Over-temperature shutdown: 135°C typical Overcurrent protection: 4A. 2A typical Support short circuit protection
Load type	Inductive (7.2W/point, 24W/module), Resistive (0.5A/point, 4A/module), Lamp (5W/point, 18W/module)

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Analog input module

CE RoHS

DF50-M-4AI-UI-6

Analog input module, 4 channels, voltage type, current type

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-4AI-UI-6
Number of channels	4
Data size	8 Byte
Voltage test range	±10V、0-10V、2-10V、±5V、0-5V、1-5V
Current test range	0-20mA、4-20mA
Connection type	2/3/4-line
Reverse protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Diagnostic reporting	Yes
Resolution	16 Bit
Signal type	/
Filter parameter configuration	/
Input accuracy	±0.20%
Conversion time	60us/channel
Sampling time	4-channel 250us

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Analog input module

CE RoHS

DF50-M-8AI-U-4

Analog input module, 8 channels, voltage type

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-8AI-U-4
Number of channels	8
Data size	16 Byte
Voltage test range	±10V、0-10V、2-10V、±5V、0-5V、1-5V
Connection type	2-line
Reverse protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Diagnostic reporting	Yes
Resolution	16 Bit
Signal type	Single-ended
Filter parameter configuration	The software filtering time can be configured through the upper computer
Input accuracy	±0.20%
Conversion time	60us/channel
Sampling time	8-channel 500us

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Analog input module

CE RoHS

DF50-M-8AI-I-5

Analog input module, 8 channels, current type

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-8AI-I-5
Number of channels	8
Data size	16 Byte
Current test range	0-20mA、4-20mA
Connection type	2-line
Reverse protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Diagnostic reporting	Yes
Resolution	16 Bit
Signal type	Single-ended
Filter parameter configuration	The software filtering time can be configured through the upper computer
Input accuracy	±0.20%
Conversion time	60us/channel
Sampling time	8-channel 500us

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Analog output module

CE RoHS

DF50-M-4AO-UI-6

Analog output module, 4 channels, voltage type, current type

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-4AO-UI-6
Number of channels	4
Data size	8 Byte
Voltage output range	±10V、0-10V、2-10V、±5V、0-5V、1-5V
Current output range	0-20mA、4-20mA
Signal type	Single-ended
Connection type	2/3/4-line
Overcurrent protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Resolution	16 Bit
Output accuracy	±0.50%
Temperature coefficient	<30 ppm/K
Independent channel configuration	Yes
Conversiontime	60us/channel

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Analog output module

CE RoHS

DF50-M-8AO-U-4

Analog output module, 8 channels, voltage type

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-8AO-U-4
Number of channels	8
Data size	16 Byte
Voltage output range	±10V、0-10V、2-10V、±5V、0-5V、1-5V
Signal type	Single-ended
Connection type	2-line
Overcurrent protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Resolution	16 Bit
Output accuracy	±0.50%
Temperature coefficient	<30 ppm/K
Independent channel configuration	Yes
Conversiontime	60us/channel

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Analog output module

CE RoHS

DF50-M-8AO-I-5

Analog output module, 8 channels, current type

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-8AO-I-5
Number of channels	8
Data size	16 Byte
Current output range	0-20mA, 4-20mA
Signal type	Single-ended
Connection type	2-line
Overcurrent protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Resolution	16 Bit
Output accuracy	±0.50%
Temperature coefficient	<30 ppm/K
Independent channel configuration	Yes
Conversiontime	60us/channel

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Temperature module

CE RoHS

DF50-M-4RTD-PT

Thermal Resistance (RTD) measurement module, 16 bit resolution, 4 channels

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-4RTD-PT
Number of channels	4
Data size	8 Byte
Signal type	Thermal resistance
Signal type	Pt100, Pt200, Pt500, Pt1000, Ni100, Ni120, Ni 200, Ni500, Ni1000, Cu10, 40 Ω, 80 Ω, 150 Ω,300 Ω, 500 Ω, 1 kΩ, 2 kΩ, 4 kΩ
Connection type	2/3/4-line
Reverse protection	Yes
Isolation method	Magnetic isolation between each channel and the field layer, and there is no isolation between channels
Fault diagnosis	Yes
Resolution	16bit,0.1℃/ each number
Frequency interference suppression	50Hz | 60Hz | 400Hz
Diagnosis	Disconnection, Parameter assignment error
Process alarm	Upper/Lower limit, per channel
Temperature coefficient	±50ppm/K max.
Measuring range	Thermal resistance
Precision	'max. 0.2 % FSR / 0.3 % FSR for Ni sensors / 0.6 % FSR for Cu10
Conversion time	100-800ms, configurable

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Temperature module

CE RoHS

DF50-M-8TC

Thermocouple (TC) measurement module,16 bit resolution, 8 channels

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-8TC
Number of channels	8
Data size	16 Byte
Signal type	Thermocouple
Signal type	K、E、T、J、B、S、R、N、C、L
Cold End compensation	Internal and external (accuracy ≤3K)
Diagnosis	Yes
Temperature coefficient	≤ 50 ppm/K
Connection type	2-line
Reverse protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Internal Resistance	/
Resolution	16bit,0.1℃/ resolution
Frequency interference suppression	10Hz | 50Hz | 60Hz | 400Hz
Diagnosis	Disconnection, Parameter assignment error
Process alarm	Upper/Lower limit, per channel
Temperature coefficient	±0.5%
Measuring range	-270°C ~ 1370°C
Precision	± 0.3%
Conversion time	125ms

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Pulse counting module

CE RoHS

DF50-M-2CNT-PIL-24

24V Pulse counting module,2 channel

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-2CNT-PIL-24
Maximum frequency count	1Mhz
Number of channels	2
Data size	20 Byte
Input signal type	Incremental encoder AB or pulse/direction signal
Input signal type	24V DC
Input connection type	2-line / 4-line
Filtering time	0.01 to 1 ms
Reverse protection	Yes
Isolation method	Isolate from the field layer optocoupler
Fault diagnosis	Yes, us response, error code can be queried by upper computer
Resolution	32 Bit
Precision	±1 pulse

Power Supply Parameters

Connection type	PUSH-IN type terminal block
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Pulse counting module

CE RoHS

DF50-M-2CNT-PIL-5

5V Pulse counting module,2 channel

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-2CNT-PIL-5
Maximum frequency count	1Mhz
Number of channels	2
Data size	20 Byte
Input signal type	Incremental encoder AB or pulse/direction signal
Input signal type	5V DC
Input connection type	2-line / 4-line
Filtering time	0.01 to 1 ms
Reverse protection	Yes
Isolation method	Isolate from the field layer optocoupler
Fault diagnosis	Yes, us response, error code can be queried by upper computer
Resolution	32 Bit
Precision	±1 pulse

Power Supply Parameters

Connection type	PUSH-IN type terminal block
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Serial communication module

CE RoHS

DF50-M-1COM-232/485/422

Serial communication module, 1 channel

Pin Definition



Wiring Diagram









Specification

Product	DF50-M-1COM-232/485/422
Interface	RS232/RS485/RS422
Number of channels	1
Agreement	Modbus RTU Free protocol transparent mode
BAUD	1200bps - 256000bps
Data bits	7bit / 8bit
Check bit	None / Even / Odd
Stop bit	1bit / 2bit
Maximum data frame length	64byte
Termination resistor	Built in 120 Ωterminal resistor
Firmware upgrade function	Support

Serial communication module

CE RoHS

Product	DF50-M-1COM-232/485/422

Power Supply Parameters

Connection type	PUSH-IN type terminal block
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

LED Status Indicator

PW	Green: Internal bus power supply is normal
ST	Power on stage: green on: module initialization abnormal, green off: module initialization normal
	Operation phase: Green flashing: The internal bus of the module is working normally, green off: The internal bus of the module is working abnormally
COM	On: Input signal valid Off: Input signal invalid
MST	On: Input signal valid Off: Input signal invalid
SLV	On: Input signal valid Off: Input signal invalid
232	In 232 mode, on: connection normal off: connection abnormal
485	In 485 mode, on: connection normal off: connection abnormal
422	In 422 mode, on: connection normal off: connection abnormal
TS	Flashing: Normal communication transmission Off: Abnormal communication transmission
RX	Flashing: normal communication reception Off: abnormal communication reception
EP	On: External power supply normal Off: External power supply normal

Voltage distribution module

CE RoHS

DF50-M-DC-U-0

Voltage distribution module, 16 channel 0VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-DC-U-0
Number of channels	16

Power Supply Parameters

Connection type	PUSH-IN type terminal block
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Voltage distribution module

CE RoHS

DF50-M-DC-U-24



Voltage distribution module, 16 channel 24VDC

Pin Definition



Wiring Diagram



Specification

Product	DF50-M-DC-U-24
Number of channels	16

Power Supply Parameters

Connection type	PUSH-IN type terminal block
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

IO-Link communication modules

CE RoHS

DF50-M-4IOL

IO-Link communication module, 4 channels

Pin Definition



Wiring Diagram



C/Q for IO-Link Mode Wiring Diagrams



Wiring when C/Q is DI



Wiring when C/Q is DO

Specification

Product	DF50-M-4IOL
Number of channels	4

IO-Link Input Mode

Connection type	3-line/5-line
Port type	A type

Digital Input Mode

Input description	When the IO-Link port is set to DI
Input type	PNP
Connect system	3-line
Input Voltage	24 V DC
"0" signal	-0.3 V DC ... 8 V DC
"1" signal	12.9 V DC ... 24.3 V DC

Digital Output Mode

Output description	When the IO-Link port is set to DO
Output type	PNP
Connection method	Push-in
Connect system	2,3-line
Rated output voltage	24 V DC
Rated current per channel	500 mA

IO-Link communication modules

CE RoHS

Product	DF50-M-4IOL

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

LED Status Indicator

PW	Green: Internal bus power supply is normal,green off: The internal bus of the module is working abnormally
ST	Power on stage: green on: module initialization abnormal, green off: module initialization normal
	Operation phase: Green flashing: The internal bus of the module is working normally, green off: The internal bus of the module is working abnormally
L0~L3	Green on: the corresponding channel IO-LINK normal communication, green flash: the corresponding channel does not have IO-LINK slave access, green off: the corresponding channel is not configured as IO-LINK mode
F0~F3	Red light: the corresponding channel reports an error, red off: the corresponding channel does not report an error
D0~D3	Green on: DI input valid signal, green off: DI no input valid signal
EP	On: External power supply normal Off: External power supply normal

DF50 series dimension

DF50 series bus coupler dimension



DF50 series I/O module & Terminal cover dimension



DF58 series I/O

Small **Compact** **Convenient**

- The DF58 series I/O system adopts 100M backplane bus for high-speed response to requirements
- Comprehensively improve I/O performance and compatibility
- Tool free use, greatly improving convenience
- The bus coupler supports 32 modules, and only when there are more than 16 extension modules, an additional power module is required

DF58 Series I/O Modules



Bus coupler

- The bus coupler comes with 8 digital inputs
- Supports multiple industrial Ethernet bus protocols
- 100M high-speed backplane bus, supporting up to 32 modules
- 16 modules do not require additional power modules; 17-32 modules require an additional power module

Tool free

- No tools required for module installation and disassembly
- No tools required to install and remove front connectors
- No tools required for wiring and dismantling

I/O module

- Digital input compatible with both PNP and NPN signals
- The analog input/output module is compatible with current and voltage, supports multiple ranges and each channel can be independently selected, and supports 2, 3, and 4 wire connection methods

Appearance

- 12mm ultra-thin volume, sharp blade shape
- The module has an identification system
- The module is grounded through the back metal connection DIN-rail
- Distinguish wiring holes with different functions by color







- PUSH-IN, no tools required for wire connection and disassembly

- Pluggable front connector



- Tool free manual operation lever
- The module is grounded through the back metal connection DIN-rail

- Bus coupler can support up to 32 modules



- Module has identification
- The module indicator system contains information such as signals, power, faults ...

- Communication between modules through side connecting finger
- Module power supply is connected through side metal clips

PROFINET Bus coupler

CE RoHS

DF58-C-PN-RT

PROFINET, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two PROFINET interface (RJ45,10/100Mbps).
- With Media Redundancy Protocol.

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected To 24V is NPN, and connected to 0V is PNP

Specification

Product	DF58-C-PN-RT
Communication protocol	PROFINET
Transmission rate	100Mbps, full duplex
Transmission distance	100 meters
PDO data	512 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	PROFINET specification
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Features	RT, conforming to Class C, MRP, automatic addressing/topology detection
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Minimum cycle time	1ms

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>15V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.678mA
Fault diagnosis	4.07mA
Typical input current	2.46mA
Fault diagnosis	4.7mA
Filtering time	No filtering, 0.25ms, 0.5ms, 1ms (factory setting), 2ms, 4ms, 8ms, 16ms, 32ms
Hardware response time	100us

PROFINET Bus coupler

CE RoHS

Product	DF58-C-PN-RT

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	0.35A ~ 6A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Supply system voltage	5VDC
Supply system current	Max.2A
Supply load voltage	24V...36VDC
Supply load current (MAX)	10A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
SYS	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
LED Sys 24v	Green:The system power is working(24V)
LED Load 24V	Green: The load power is working
LED Sys 5V	Green:The system power is working(5V)

EtherCAT Bus coupler

CE RoHS

DF58-C-EC

EtherCAT, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two EtherCAT interface (RJ45,100Mbps).

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected
To 24V is NPN, and connected to 0V is PNP

Specification

Product	DF58-C-EC
Communication protocol	EtherCAT
Transmission rate	100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	EtherCAT specification, DIP switch
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Alias range	1~254
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Connection type	2 X RJ45, with switch function

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>15V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.678mA
Fault diagnosis	4.07mA
Typical input current	2.46mA
Fault diagnosis	4.7mA
Filtering time	No filtering, 0.25ms, 0.5ms, 1ms (factory setting), 2ms, 4ms, 8ms, 16ms, 32ms
Hardware response time	100us

EtherCAT Bus coupler CE RoHS

Product	DF58-C-EC

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	0.35A ~ 6A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Supply system voltage	5VDC
Supply system current	Max.2A
Supply load voltage	24V...36VDC
Supply load current (MAX)	10A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
SYS	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
LED Sys 24v	Green:The system power is working(24V)
LED Load 24V	Green: The load power is working
LED Sys 5V	Green:The system power is working(5V)

CC-LINK IE Field Basic Bus coupler

CE RoHS

DF58-C-CC-FB



CC-LINK IE Field Basic, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- CC-LINK IE Field Basic interface (RJ45,10/100Mbps).

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected
To 24V is NPN, and connected to 0V is PNP

Specification

Product	DF58-C-CC-FB
Communication protocol	CC-LINK IE Field Basic
Transmission rate	100Mbps, full duplex
Transmission distance	100 meters
PDO data	576 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	CC-LINK IE Field Basic specification, DIP switch
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Address range	1~254
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Connection type	2 X RJ45, with switch function

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>15V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.678mA
Fault diagnosis	4.07mA
Typical input current	2.46mA
Fault diagnosis	4.7mA
Filtering time	No filtering, 0.25ms, 0.5ms, 1ms (factory setting), 2ms, 4ms, 8ms, 16ms, 32ms
Hardware response time	100us

CC-LINK IE Field Basic Bus coupler

CE RoHS

Product	DF58-C-CC-FB

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	0.35A ~ 6A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Supply system voltage	5VDC
Supply system current	Max3A
Supply load voltage	24V...36VDC
Supply load current (MAX)	10A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
SYS	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
LED Sys 24v	Green:The system power is working(24V)
LED Load 24V	Green: The load power is working
LED Sys 5V	Green:The system power is working(5V)

Modbus TCP/IP Bus coupler

CE RoHS

DF58-C-MD-TCP

Modbus TCP/IP, 1 RJ45, extensible 16 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Modbus TCP/IP interface (RJ45,10/100Mbps)

Wiring Diagram



Pin Definition



COM is the common terminal of DI0~DI7, connected
To 24V is NPN, and connected to 0V is PNP

Specification

Product	DF58-C-MD-TCP
Communication protocol	Modbus TCP/IP
Transmission rate	100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	Modbus TCP/IP specification, DIP switch
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Address range	1~254
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Support Modbus function	02,03,05,06,15,16

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>15V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.678mA
Fault diagnosis	4.07mA
Typical input current	2.46mA
Fault diagnosis	4.7mA
Filtering time	No filtering, 0.25ms, 0.5ms, 1ms (factory setting), 2ms, 4ms, 8ms, 16ms, 32ms
Hardware response time	100us

Modbus TCP/IP Bus coupler CE RoHS

Product	DF58-C-MD-TCP

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	0.35A ~ 6A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Supply system voltage	5VDC
Supply system current	Max3A
Supply load voltage	24V...36VDC
Supply load current (MAX)	10A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
SYS	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
LED Sys 24v	Green:The system power is working(24V)
LED Load 24V	Green: The load power is working
LED Sys 5V	Green:The system power is working(5V)

EtherNet/IP Bus coupler

CE RoHS

DF58-C-EN-IP



EtherNet/IP, 2 RJ45, extensible 32 modules, 24VDC

Features

- With a power module.
- LED display working status, alarm and bus fault prompt.
- Two EtherNet/IP interface (RJ45,10/100Mbps).

Pin Definition



Wiring Diagram



COM is the common terminal of DI0~DI7, connected
To 24V is NPN, and connected to 0V is PNP

Specification

Product	DF58-C-EN-IP
Communication protocol	EtherNet/IP
Transmission rate	100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	EtherNet/IP specification, DIP switch
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Minimum cycle time	1ms
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm

Digital Inputs Specification

Number of channels	8
Data size	1 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>15V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.678mA
Fault diagnosis	4.07mA
Typical input current	2.46mA
Fault diagnosis	4.7mA
Filtering time	No filtering, 0.25ms, 0.5ms, 1ms (factory setting), 2ms, 4ms, 8ms, 16ms, 32ms
Hardware response time	100us

EtherNet/IP Bus coupler

CE RoHS

Product	DF58-C-EN-IP

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Working current	0.35A ~ 6A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm
Supply system voltage	5VDC
Supply system current	Max3A
Supply load voltage	24V...36VDC
Supply load current (MAX)	10A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 48mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

LED Status Indicator

PWR	Green: Power is working
RUN	Green: I/O system is running
SYS	Blinking green: The module is working
ERR	Red: An error occurred between I/O system and module
LED Sys 24v	Green:The system power is working(24V)
LED Load 24V	Green: The load power is working
LED Sys 5V	Green:The system power is working(5V)

Digital input module

CE RoHS

DF58-M-16DI-P/N

Digital input module, 16 ports, PNP/NPN,24VDC

Pin Definition



COM is the common terminal of DI0~DI7, connected To 24V is NPN, and connected to 0V is PNP

Wiring Diagram



NPN PNP

Specification

Product	DF58-M-16DI-P/N
Number of channels	16
Data size	2 Byte
Signal type	NPN & PNP
"0" signal voltage	<5V
"1" signal voltage	>15V
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Fault diagnosis	Yes
Typical input current	0.678mA
Fault diagnosis	4.07mA
Typical input current	2.46mA
Fault diagnosis	4.7mA
Filtering time	No filtering, 0.25ms, 0.5ms, 1ms (factory setting), 2ms, 4ms, 8ms, 16ms, 32ms,
Hardware response time	100us

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<15mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

Digital output module

CE RoHS

DF58-M-16DO-N

Digital output module, 16 ports, NPN, 24VDC

Pin Definition



Wiring Diagram



NPN

Specification

Product	DF58-M-16DO-N
Number of channels	16
Data size	2 Byte
Signal type	NPN
"0" signal voltage	high-impedance state
"1" signal voltage	0V DC
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Switching Frequency (resistance/lamp load)	<1000Hz
Switching Frequency (Inductive load)	<0.2Hz
Response Time of the Protection Circuit	< 100μs
Output current per channel(MAX)	500 mA
Load type	Inductance, resistance, lamp

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<75mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

Digital output module

CE RoHS

DF58-M-16DO-P

Digital output module, 16 ports, PNP, 24VDC

Pin Definition



Wiring Diagram



PNP

Specification

Product	DF58-M-16DO-P
Number of channels	16
Data size	2 Byte
Signal type	PNP
"0" signal voltage	High-impedance state
"1" signal voltage	24V DC
Connection type	1-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
Switching Frequency (resistance/lamp load)	<1000Hz
Switching Frequency (Inductive load)	<0.2Hz
Response Time of the Protection Circuit	< 100μs
Output current per channel(MAX)	500 mA
Load type	Inductance, resistance, lamp

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<75mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

Analog input module

CE RoHS

DF58-M-4AI-UI-6

Analog input module, 4 channels, voltage type, current type

Pin Definition



Wiring Diagram



Specification

Product	DF58-M-4AI-UI-6
Number of channels	4
Data size	8 Byte
Voltage test range	±10V、0-10V、2-10V、±5V、0-5V、1-5V
Current test range	±20mA、0-20mA、4-20mA
Connection type	2/3/4-line
Reverse protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Internal Resistance	>450KΩ
Resolution	16 Bit
Signal type	difference
Conversion digital quantity range configuration	Default configuration (- 27648 to 27648), support ± 32000
Precision	0.20%
Conversion time	400us/channel
Sampling rate	20-300Hz (Configuration)

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<120mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

Analog output module

CE RoHS

DF58-M-4AO-UI-6

Analog output module, 4 channels, voltage type, current type

Pin Definition



Wiring Diagram



Specification

Product	DF58-M-4AO-UI-6
Number of channels	4
Data size	8 Byte
Voltage output range	±10V、0-10V、2-10V、±5V、0-5V、1-5V
Current output range	±20mA、0-20mA、4-20mA
Signal type	Differential signal
Connection type	2/3/4-line
Overcurrent protection	Yes
Isolation method	Magnetic isolation
Fault diagnosis	Yes
Resolution	16 Bit
Precision	0.10%
Load type	Sensibility, resistance, tolerance
Conversion digital quantity range configuration	Default configuration (- 27684 to 27684), support ± 32000
Conversiontime	150us/channel

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<110mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

Temperature module

CE RoHS

DF58-M-4RTD-PT

Thermal Resistance (RTD) measurement module, 16 bit resolution, 4 channels

Pin Definition



Wiring Diagram



Specification

Product	DF58-M-4RTD-PT
Number of channels	4
Data size	8 Byte
Signal type	Thermal resistance
Signal type	Pt100, Pt200, Pt500, Pt1000, Ni100, Ni120, Ni 200, Ni500, Ni1000, Cu10, 40 Ω, 80 Ω, 150 Ω,300 Ω, 500 Ω, 1 kΩ, 2 kΩ, 4 kΩ
Connection type	2/3/4-line
Reverse protection	Yes
Isolation method	Magnetic isolation between each channel and the field layer, and isolation between channels
Fault diagnosis	Yes
Resolution	16bit,0.1℃/ each number
Frequency interference suppression	10Hz | 50Hz | 60Hz | 400Hz
Diagnosis	Disconnection, Parameter assignment error
Process alarm	Upper/Lower limit, per channel
Temperature coefficient	±50ppm/K max.
Internal resistance	>500Ω
Precision	'max. 0.2 % FSR / 0.3 % FSR for Ni sensors / 0.6 % FSR for Cu10
Conversion time	100ms/4 channels

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

Pulse counting module

CE RoHS

DF58-M-2CNT-PIL-24



24VPulse counting module,2 port,24V

Pin Definition



NPN, TP1_in+ — Load_24V, TP1_in- — Signal
PNP, TP1_in+ — Signal, TP1_in- — Load_0V

Wiring Diagram



Specification

Product	DF58-M-2CNT-PIL-24
Maximum frequency count	1Mhz
Number of channels	2
Data size	20 Byte
Input signal type	Incremental encoder AB or pulse/direction signal
Input signal type	24V DC
Input connection type	2-Line / 4-Line
Filtering time	0.01 to 1 ms
Reverse protection	Yes
Isolation method	Isolate from the field layer optocoupler
Fault diagnosis	Yes, us response, error code can be queried by upper computer
Resolution	32 Bit
Precision	±1 pulse

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 66.8mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

System power supply module

CE RoHS

DF58-M-DC-U-5

System power supply module, 24VDC to 5VDC

Pin Definition



Wiring Diagram



Specification

Product	DF58-M-DC-U-5
Number of channels	1
Isolation method	System power supply to site power supply: isolation module

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 66.8mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5...95%RH(non-condensing)

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
Reverse power protection	YES
Supply system voltage	5VDC
Supply system current	Max.2A@5V
Supply load voltage	24V DC +20 %/ -15 %
Supply load current (MAX)	10A
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Temperature module

CE RoHS

DF58-M-4TC

Thermocouple (TC) measurement module,
16 bit resolution, 4 channels

Wiring Diagram



CJC is the NTC compensation interface

Pin Definition



Specification

Product	DF58-M-4TC
Number of channels	4
Data size	8 Byte
Signal type	Thermal resistance
Signal type	E(-200 ~ 1000°C), S(-50 ~ 1,768°C), J(210~1,200°C), T(-200 ~ 400°C),K(-200~1,372°C), B(-50 ~ 1,820°C), N(-200 ~ 1300°C), C(0~2,315°C), R(-50 ~ 1,768°C), L(-200 ~ 900°C), U(-200 ~ 600°C)
Connection type	2/3/4-line
Reverse protection	Yes
Isolation method	Magnetic isolation between each channel and the field layer, and isolation between channels
Fault diagnosis	Yes
Resolution	16bit,0.1℃/ each number
Frequency interference suppression	10Hz | 50Hz | 60Hz | 400Hz
Diagnosis	Disconnection, Parameter assignment error
Process alarm	Upper/Lower limit, per channel
Temperature coefficient	≤50ppm/K .
Internal resistance	>500Ω
Precision	'max. 0.2 % FSR / 0.3 % FSR for Ni sensors / 0.6 % FSR for Cu10
Conversion time	36…. 240ms, adjustable

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5…95%RH(non-condensing)

Temperature module

CE RoHS

DF58-M-8TC

Thermocouple (TC) measurement module,
16 bit resolution, 8 channels

Wiring Diagram



Pin Definition



Specification

Product	DF58-M-8TC
Number of channels	4
Data size	16 Byte
Signal type	Thermal resistance
Signal type	E(-200 ~ 1000°C), S(-50 ~ 1,768°C), J(210~1,200°C), T(-200 ~ 400°C),K(-200~1,372°C), B(-50 ~ 1,820°C), N(-200 ~ 1300°C), C(0~2,315°C), R(-50 ~ 1,768°C), L(-200 ~ 900°C), U(-200 ~ 600°C)
Connection type	2-line
Reverse protection	Yes
Isolation method	Magnetic isolation between each channel and the field layer, and isolation between channels
Fault diagnosis	Yes
Resolution	16bit,0.1℃/ each number
Frequency interference suppression	10Hz | 50Hz | 60Hz | 400Hz
Diagnosis	Disconnection, Parameter assignment error
Process alarm	Upper/Lower limit, per channel
Temperature coefficient	≤50ppm/K .
Internal resistance	>500Ω
Precision	'max. 0.2 % FSR / 0.3 % FSR for Ni sensors / 0.6 % FSR for Cu10
Conversion time	36…. 240ms, adjustable

Power Supply Parameters

Connection type	PUSH-IN type terminal block
Working voltage	24V DC +20 %/ -15 %
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8…10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5…95%RH(non-condensing)

DF58 series dimension

DF58 series bus coupler dimension



DF58 series I/O module & Terminal cover dimension



DF20 series I/O



- The DF20 series I/O system is the first generation I/O product
- Long term stable and reliable on-site application performance
- Pull back spring wiring, high vibration resistance
- The bus coupler supports 32 modules, all modules are powered from the side, and power modules are configured as needed
- Supports PROFINET, EtherCAT, EtherNet/IP, Modbus TCP/IP, CC-LINK IE Field Basic bus protocols

Model	Functionality	Coupler Support Module List				
		DF20-C-PN-RT-V10	DF20-C-EC	DF20-C-EN-IP	DF20-C-MD-TCP-V1	DF20-C-CC-FB
Digital Module						
DF20-M-8DI-N	8-Channel Digital Input Module, NPN Type	✓	✓	✓	✓	✓
DF20-M-8DI-P	8 Channel Digital Input Module, PNP Type	✓	✓	✓	✓	✓
DF20-M-16DI-N	16 Channel Digital Input Module, NPN Type	✓	✓	✓	✓	✓
DF20-M-16DI-P	16 Channel Digital Input Module, PNP Type	✓	✓	✓	✓	✓
DF20-M-32DI-N	32 Channel Digital Input Module, NPN Type	✓	✓	✓	✓	✓
DF20-M-32DI-P	32 Channel Digital Input Module, PNP Type	✓	✓	✓	✓	✓
DF20-M-4DO-R	4 Channel Relay Output, 5A	✓	✓	✓	✓	✓
DF20-M-8DO-N	8 Channel Digital Output Module, NPN Type	✓	✓	✓	✓	✓
DF20-M-8DO-P	8 Channel Digital Output Module, PNP Type	✓	✓	✓	✓	✓
DF20-M-16DO-N	16 Channel Digital Output Module, NPN Type	✓	✓	✓	✓	✓
DF20-M-16DO-P	16 Channel Digital Output Module, PNP Type	✓	✓	✓	✓	✓
DF20-M-32DO-N	32 Channel Digital Output Module, NPN Type	✓	✓	✓	✓	✓
DF20-M-32DO-P	32-Channel Digital Output Module, PNP Type	✓	✓	✓	✓	✓
DF20-M-8DIO-N	8-Channel Digital Input + 8-Channel Digital Output, NPN Type	✓	✓	✓	✓	✓
DF20-M-8DIO-P	8-channel digital input + 8-channel digital output, PNP type	✓	✓	✓	✓	✓
Analog Module						
DF20-M-4AI-U-0	4-channel analog input, voltage type, ±10V, 16bit	✓	✓	✓	✓	✓
DF20-M-4AI-U-1	4-channel analog input, voltage type, 0-10V, 16bit	✓	✓	✓	✓	✓
DF20-M-4AI-I-2	4-channel analog input, current type, 0-20ma, 16bit	✓	✓	✓	✓	✓
DF20-M-4AI-I-3	4-channel analog input, current type, 4-20ma, 16bit	✓	✓	✓	✓	✓
DF20-M-4AI-U-4	4-channel analog input, voltage type, ±10V/±5V/0-10V/2-10V/0-5V/1-5V,16bit	✓	✓	✓	✓	✓
DF20-M-8AI-U-4	8-channel analog input, voltage type, ±10V/±5V/0-10V/2-10V/0-5V/1-5V,16bit	✓	✓	✓	✓	✓
DF20-M-4AI-I-5	4-channel analog input, current type, 0-20ma/4-20ma,16bit	✓	✓	✓	✓	✓
DF20-M-8AI-I-5	8-channel analog input, current type,0-20ma/4-20ma,16bit	✓	✓	✓	✓	✓
DF20-M-2LC-S-5	2-channel analog input, Wheatstone bridge/pressure transducer type	✓	✓	✓	✓	✓
DF20-M-2RTD-PT	2-channel analog input, RTD type	✓	✓	✓	✓	✓
DF20-M-4RTD-PT	4-channel analog input, RTD Type	✓	✓	✓	✓	✓
DF20-M-4TC-KETJ	4-channel analog input, Thermocouple Type	✓	✓	✓	✓	✓
DF20-M-8TC-KETJ	8-channel analog input, Thermocouple Type	✓	✓	✓	✓	✓
DF20-M-4AO-U-0	4-channel analog output, voltage type, ±10V, 16bit	✓	✓	✓	✓	✓
DF20-M-4AO-U-1	4-channel analog output, voltage type, 0-10V, 16bit	✓	✓	✓	✓	✓
DF20-M-4AO-I-2	4-channel analog output, current type, 0-20ma, 16bit	✓	✓	✓	✓	✓
DF20-M-4AO-I-3	4-channel analog output, current type, 4-20ma, 16bit	✓	✓	✓	✓	✓

Model	Functionality	Coupler Support Module List				
		DF20-C-PN-RT-V10	DF20-C-EC	DF20-C-EN-IP	DF20-C-MD-TCP-V1	DF20-C-CC-FB
Analog Module						
DF20-M-4AO-U-4	4-channel analog output, voltage type, ±10V/±5V/0-10V/2-10V/0-5V/1-5V,16bit	✓	✓	✓	✓	✓
DF20-M-8AO-U-4	8-channel analog output, voltage type, ±10V/±5V/0-10V/2-10V/0-5V/1-5V,16bit	✓	✓	✓	✓	✓
DF20-M-4AO-I-5	4-channel analog output, current type, 0-20ma/4-20ma,16bit	✓	✓	✓	✓	✓
DF20-M-8AO-I-5	8-channel analog output, current type, 0-20ma/4-20ma, 16bit	✓	✓	✓	✓	✓
Protocol Converter						
DF20-M-1COM-232/485/422	1-channel 485/232/422 communication module, supports FreeRun and Modbus RTU mode	✓	✓	✓	✗	✓
DF20-M-4IOL	4-channel IO-LINK communication module, support MASTER mode	✓	✓	✗	✗	✗
Pulse Counting / Output						
DF20-M-1CNT-EL-5	1 Channel Count Input, Incremental Encoder, 5V	✓	✓	✓	✓	✓
DF20-M-1CNT-EL-4	1 Channel Count Input, Incremental Encoder, 24V	✓	✓	✓	✓	✓
DF20-M-2CNT-PIL-5	2-Channel Pulse Count Input, 5V	✓	✓	✓	✓	✓
DF20-M-2CNT-PIL-4	2-Channel Count Input, Incremental Encoder, 24V	✓	✓	✓	✓	✓
DF20-M-2CNT-EL-5	2 Channel Count Input, Incremental Encoder or Pulse Direction, 5V	✓	✓	✓	✓	✓
DF20-M-1CNT-ELP-5	1 Channel Position Compare Trigger, Incremental Encoder Input, 422 Level Trigger Output, 5V	✓	✗	✗	✗	✗
DF20-M-2PWM	2-channel pulse output, support driver pointing and positioning function, support PWM output	✓	✓	✓	✓	✓
Auxiliary Modules						
DF20-M-DC-UD-5	Power extension module, system power 5V/2A, power 24V/8A	✓	✓	✓	✓	✓
DF20-M-DC-U-24	Power 24V distribution module	✓	✓	✓	✓	✓
DF20-M-DC-U-0	Power 0V distribution module	✓	✓	✓	✓	✓

PROFINET Bus coupler

CE RoHS

DF20-C-PN-RT-V10

PROFINET, 2 RJ45, extensible 32 modules, 24VDC

Wiring Diagram



DF20-C-PN-RT-V10

Specification

Product	DF20-C-PN-RT-V10
Communication protocol	PROFINET
Transmission rate	10/100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	Yes
Address setting	PROFINET specification
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Features	RT, conforming to Class C, MRP, automatic addressing/topology detection
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Minimum cycle time	1ms

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 48mm X 69mm
Installation type	35mm DIN

Power Supply Parameters

Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
Current without load	<350mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire	0.2mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm
Supply system voltage	5VDC
Supply system current	2A
Supply load voltage	24V…32VDC
Supply load current (MAX)	5A

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

EtherCAT Bus coupler

CE RoHS

DF20-C-EC

EtherCAT, 2 RJ45, extensible 31 modules, 24VDC

Wiring Diagram



DF20-C-EC

Specification

Product	DF20-C-EC
Communication protocol	EtherCAT
Connection type	2 X RJ45, with switch function
Transmission rate	10/100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	31
Address mapping	Yes
Address setting	EtherCAT specification, DIP switch
Alias range	1~254
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation

Power Supply Parameters

Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
Current without load	<150mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire	0.2mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm
Supply system voltage	5VDC
Supply system current	Max.0.6A
Supply load voltage	24V…32VDC
Supply load current (MAX)	5A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 48mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

EtherNet/IP Bus coupler

CE RoHS

DF20-C-EN-IP

EtherNet/IP, 2 RJ45, extensible 32 modules, 24VDC

Wiring Diagram



DF20-C-EN-IP

Specification

Product	DF20-C-EN-IP
Communication protocol	EtherNet/IP
Transmission rate	10/100Mbps, full duplex
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	32
Address mapping	yes
Address setting	EtherNet/IP specification, DIP switch
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation
Alarm function	Diagnostic alarm, process alarm, plug and unplug connector alarm
Minimum cycle time	1ms

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 48mm X 69mm
Installation type	35mm DIN

Power Supply Parameters

Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
Current without load	<350mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire	0.2mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm
Supply system voltage	5VDC
Supply system current	Max.0.4A
Supply load voltage	24V…32VDC
Supply load current (MAX)	5A

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Modbus TCP/IP Bus coupler

CE RoHS

DF20-C-MD-TCP-V1

Modbus TCP/IP, 1 RJ45, extensible 16 modules, 24VDC

Wiring Diagram



DF20-C-MD-TCP-V1

Specification

Product	DF20-C-MD-TCP-V1
Communication protocol	Modbus TCP/IP
Transmission rate	10/100Mbps
Transmission distance	100 meters
PDO data	1024 bytes
Number of extensible modules	16
Support Modbus function	02,03,05,06,15,16
Address mapping	Yes
Address setting	Modbus TCP/IP specification, DIP switch
Address range	2~253
Transmission medium	Class 5 twisted pair cable
Isolation method	Electrical isolation

Power Supply Parameters

Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
Current without load	<150mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm
Supply system voltage	5VDC
Supply system current	Max.0.6A
Supply load voltage	24V…32VDC
Supply load current (MAX)	5A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 48mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

CC-LINK IEFB IP20 I/O System

CE RoHS

DF20-C-CC-FB

CC-LINK IE Field Basic, 1 RJ45, expandable 32 modules, 24VDC

Wiring Diagram



DF20-C-CC-FB

Specification

Product	DF20-C-CC-FB	
Communication protocol	CC-LINK IE Field Basic	
Transmission rate	10/100Mbps	
Transmission distance	100 meters	
Maximum data volume	RX, RY	4×64 bits
	RWr, RWw	4×32 Words
Number of extensible modules	32	
Address mapping	Yes	
Address setting	CC-LINK IE Field Basic specification, DIP switch	
Address range	1~253	
Transmission medium	Class 5 twisted pair cable	
Isolation method	Electrical isolation	

Power Supply Parameters

Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
Current without load	<150mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm
Supply system voltage	5VDC
Supply system current	Max.0.6A
Supply load voltage	24V…32VDC
Supply load current (MAX)	5A

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 48mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

Digital input module

CE RoHS

DF20-M-8DI-N	DF20-M-8DI-P	DF20-M-16DI-N	DF20-M-16DI-P	DF20-M-32DI-N	DF20-M-32DI-P
					
NPN , 24VDC Digital input module, 8 ports, NPN, 24VDC	PNP , 24VDC Digital input module, 8 ports, PNP, 24VDC	NPN , 24VDC Digital input module, 16 ports, NPN, 24VDC	PNP , 24VDC Digital input module, 16 ports, PNP, 24VDC	NPN , 24VDC Digital input module, 32 ports, NPN, 24VDC	PNP , 24VDC Digital input module, 32 ports, PNP, 24VDC

Specification

Product	DF20-M-8DI-N	DF20-M-8DI-P	DF20-M-16DI-N	DF20-M-16DI-P	DF20-M-32DI-N	DF20-M-32DI-P
Number of channels	8		16		32	
Data size	1 Byte		2 Byte		4 Byte	
Signal type	NPN	PNP	NPN	PNP	NPN	PNP
"0" signal voltage	18V…32V	0V…4V	18V…32V	0V…4V	18V…32V	0V…4V
"1" signal voltage	0V…4V	18V…32V	0V…4V	18V…32V	0V…4V	18V…32V
Connection type	1-line					
Reverse protection	Yes					
Isolation method	Photoelectric isolation					
Fault diagnosis	Yes					
Typical input current	3mA					
Filtering time	0.3ms					
Precision	0.20%					

Power Supply Parameters

Connection type	Spring terminal blocks		
Working voltage	24V DC +20 %/ -15 %		
System feed current	<14mA	<15mA	<30mA
Maximum area of wire	2.5mm²	1.5mm²	
Maximum area of wire (AWG)	AWG14	AWG16	
The minimum area of a wire	0.2mm²	0.2mm²	
The minimum area of a wire (AWG)	AWG28	AWG28	
Strip length	8…9mm	8…9mm	

Digital input module

CE RoHS

Product	DF20-M-8DI-N	DF20-M-8DI-P	DF20-M-16DI-N	DF20-M-16DI-P	DF20-M-32DI-N	DF20-M-32DI-P

Mechanical Structure

Protection grade	IP20	
Size(H X W X D)	100mm X 12mm X 69mm	100mm X 24mm X 69mm
Installation type	35mm DIN	

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

LED Status Indicator

Channel light	Green: The input signal of each channel is working.

Wiring Diagram

Pin	Description
1	Input 0
2	Input 1
3	Input 2
4	Input 3
5	Input 4
6	Input 5
7	Input 6
8	Input 7



DF20-M-8DI-N

Pin	Description	Pin	Description
1	Input 0	9	Input 8
2	Input 1	10	Input 9
3	Input 2	11	Input 10
4	Input 3	12	Input 11
5	Input 4	13	Input 12
6	Input 5	14	Input 13
7	Input 6	15	Input 14
8	Input 7	16	Input 15



DF20-M-16DI-N

Pin	Description
1	Input 0
2	Input 1
3	Input 2
4	Input 3
5	Input 4
6	Input 5
7	Input 6
8	Input 7



DF20-M-8DI-P

Pin	Description	Pin	Description
1	Input 0	9	Input 8
2	Input 1	10	Input 9
3	Input 2	11	Input 10
4	Input 3	12	Input 11
5	Input 4	13	Input 12
6	Input 5	14	Input 13
7	Input 6	15	Input 14
8	Input 7	16	Input 15



DF20-M-16DI-P

Pin	Description	Pin	Description	Pin	Description	Pin	Description
1	Input 0	9	Input 8	17	Input 16	25	Input 24
2	Input 1	10	Input 9	18	Input 17	26	Input 25
3	Input 2	11	Input 10	19	Input 18	27	Input 26
4	Input 3	12	Input 11	20	Input 19	28	Input 27
5	Input 4	13	Input 12	21	Input 20	29	Input 28
6	Input 5	14	Input 13	22	Input 21	30	Input 29
7	Input 6	15	Input 14	23	Input 22	31	Input 30
8	Input 7	16	Input 15	24	Input 23	32	Input 31



DF20-M-32DI-N

Pin	Description	Pin	Description	Pin	Description	Pin	Description
1	Input 0	9	Input 8	17	Input 16	25	Input 24
2	Input 1	10	Input 9	18	Input 17	26	Input 25
3	Input 2	11	Input 10	19	Input 18	27	Input 26
4	Input 3	12	Input 11	20	Input 19	28	Input 27
5	Input 4	13	Input 12	21	Input 20	29	Input 28
6	Input 5	14	Input 13	22	Input 21	30	Input 29
7	Input 6	15	Input 14	23	Input 22	31	Input 30
8	Input 7	16	Input 15	24	Input 23	32	Input 31



DF20-M-32DI-P

Digital output module

CE RoHS

DF20-M-8DO-N	DF20-M-8DO-P	DF20-M-16DO-N	DF20-M-16DO-P	DF20-M-32DO-N	DF20-M-32DO-P
					
NPN , 24VDC Digital output module, 8 ports, NPN, 24VDC	PNP , 24VDC Digital output module, 8 ports, PNP, 24VDC	NPN , 24VDC Digital output module, 16 ports, NPN, 24VDC	PNP , 24VDC Digital output module, 16 ports, PNP, 24VDC	NPN , 24VDC Digital output module, 32 ports, NPN, 24VDC	PNP , 24VDC Digital output module, 32 ports, PNP, 24VDC

Specification

Product	DF20-M-8DO-N	DF20-M-8DO-P	DF20-M-16DO-N	DF20-M-16DO-P	DF20-M-32DO-N	DF20-M-32DO-P
Number of channels	8		16		32	
Data size	1 Byte		2 Byte		4 Byte	
Signal type	NPN	PNP	NPN	PNP	NPN	PNP
"0" signal voltage	High-impedance state	High-impedance state	High-impedance state	High-impedance state	High-impedance state	High-impedance state
"1" signal voltage	0V DC	24V DC	0V DC	24V DC	0V DC	24V DC
Connection type	1-line					
Reverse protection	Yes					
Isolation method	Photoelectric isolation					
Switching Frequency (resistance/lamp load)	<1000Hz					
Switching Frequency (Inductive load)	<0.2Hz					
Response Time of the Protection Circuit	< 100μs					
Output current per channel(MAX)	500 mA					
Load type	Inductance, resistance, lamp					

Power Supply Parameters

Connection type	Spring terminal blocks		
Working voltage	24V DC +20 %/ -15 %		
System feed current	<50mA	<75mA	<100mA
Maximum area of wire	2.5mm²	1.5mm²	
Maximum area of wire (AWG)	AWG14	AWG16	
The minimum area of a wire	0.2mm²	0.2mm²	
The minimum area of a wire (AWG)	AWG28	AWG28	
Strip length	8…9mm	8…9mm	

Digital output module

CE RoHS

Product	DF20-M-8DO-N	DF20-M-8DO-P	DF20-M-16DO-N	DF20-M-16DO-P	DF20-M-32DO-N	DF20-M-32DO-P

Mechanical Structure

Protection grade	IP20	
Size(H X W X D)	100mm X 12mm X 69mm	100mm X 24mm X 69mm
Installation type	35mm DIN	

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

LED Status Indicator

Channel light	Green: The output signal of each channel is working.

Wiring Diagram

Pin	Description
1	Output 0
2	Output 1
3	Output 2
4	Output 3
5	Output 4
6	Output 5
7	Output 6
8	Output 7



DF20-M-8DO-N

Pin	Description	Pin	Description
1	Output 0	9	Output 8
2	Output 1	10	Output 9
3	Output 2	11	Output 10
4	Output 3	12	Output 11
5	Output 4	13	Output 12
6	Output 5	14	Output 13
7	Output 6	15	Output 14
8	Output 7	16	Output 15



DF20-M-16DO-N

Pin	Description
1	Output 0
2	Output 1
3	Output 2
4	Output 3
5	Output 4
6	Output 5
7	Output 6
8	Output 7



DF20-M-8DO-P

Pin	Description	Pin	Description
1	Output 0	9	Output 8
2	Output 1	10	Output 9
3	Output 2	11	Output 10
4	Output 3	12	Output 11
5	Output 4	13	Output 12
6	Output 5	14	Output 13
7	Output 6	15	Output 14
8	Output 7	16	Output 15



DF20-M-16DO-P

Pin	Description	Pin	Description	Pin	Description	Pin	Description
1	Output 0	9	Output 8	17	Output 16	25	Output 24
2	Output 1	10	Output 9	18	Output 17	26	Output 25
3	Output 2	11	Output 10	19	Output 18	27	Output 26
4	Output 3	12	Output 11	20	Output 19	28	Output 27
5	Output 4	13	Output 12	21	Output 20	29	Output 28
6	Output 5	14	Output 13	22	Output 21	30	Output 29
7	Output 6	15	Output 14	23	Output 22	31	Output 30
8	Output 7	16	Output 15	24	Output 23	32	Output 31



DF20-M-32DO-N

Pin	Description	Pin	Description	Pin	Description	Pin	Description
1	Output 0	9	Output 8	17	Output 16	25	Output 24
2	Output 1	10	Output 9	18	Output 17	26	Output 25
3	Output 2	11	Output 10	19	Output 18	27	Output 26
4	Output 3	12	Output 11	20	Output 19	28	Output 27
5	Output 4	13	Output 12	21	Output 20	29	Output 28
6	Output 5	14	Output 13	22	Output 21	30	Output 29
7	Output 6	15	Output 14	23	Output 22	31	Output 30
8	Output 7	16	Output 15	24	Output 23	32	Output 31



DF20-M-32DO-P

Relay output module

CE RoHS

DF20-M-4DO-R



Relay output module, 4 ports, 24VDC

Wiring Diagram



DF20-M-4DO-R

Specification

Product	DF20-M-4DO-R
Number of channels	4
Data size	1 Byte
Contact type	N.O. Contacts
Connection type	2-line
Reverse protection	Yes
Isolation method	Photoelectric isolation
OFF to ON	MAX.10ms
ON to OFF	Max.5ms
Response Time of the Protection Circuit	< 100μs
Output current per channel(MAX)	5A
Load type	Inductance, resistance, lamp

Power Supply Parameters

Product	DF20-M-4DO-R
Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
System feed current	<60mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.2mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 67mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…75℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Digital input output module

CE RoHS

DF20-M-8DIO-N

Digital input output module, 8 ports, NPN, 24VDC

DF20-M-8DIO-P

Digital input output module, 8 ports, PNP, 24VDC

Wiring Diagram



DF20-M-8DIO-N



DF20-M-8DIO-P

Specification

Product	DF20-M-8DIO-N	DF20-M-8DIO-P
Number of channels	16	
Data size	1 Byte	
Signal type	NPN	PNP
"0" signal voltage	High-impedance state	High-impedance state
"1" signal voltage	0V DC	24V DC
Connection type	1-line	
Reverse protection	Yes	

Output Parameter

Isolation method	Photoelectric isolation
Switching Frequency (resistance/lamp load)	<1000Hz
Switching Frequency (Inductive load)	<0.2Hz
Response Time of the Protection Circuit	< 100μs
Output current per channel(MAX)	500 mA
Load type	Inductance, resistance, lamp

Power Supply Parameters

Product	DF20-M-8DIO-N	DF20-M-8DIO-P
Connection type	Spring terminal blocks	
Working voltage	24V DC +20 %/ -15 %	
System feed current	<60mA	
Maximum area of wire	1.5mm²	
Maximum area of wire (AWG)	AWG16	
The minimum area of a wire	0.2mm²	
The minimum area of a wire (AWG)	AWG28	
Strip length	8…9mm	

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 67mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…75℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Analog input module

CE RoHS

DF20-M-4AI-U-0	DF20-M-4AI-U-1	DF20-M-4AI-U-4	DF20-M-8AI-U-4
			
Analog input module,4 ports, -10...10V, voltage type	Analog input module,4 ports,0...10V,voltage type	Analog input module, 4 ports, (0...+10V)(-10...+10V), voltage type	Analog input module, 8 ports, (0...+10V)(-10...+10V),voltage type

Specification

Product	DF20-M-4AI-U-0	DF20-M-4AI-U-1	DF20-M-4AI-U-4	DF20-M-8AI-U-4
Number of channels	4			8
Data size	8 Byte			16 Byte
Measuring range	Voltage U (-10... 10 V)	Voltage U (0... 10 V)	Voltage U (0...+10V) (-10...+10V)	Voltage U (0...+10V)(-10...+10V)
Signal type	Differential signal			
Connection type	2-line			
Reverse protection	Yes			
Isolation method	Magnetic isolation			
Fault diagnosis	Yes			
Internal resistance	>450KΩ			
Resolution	16 Bit			
Measuring range (Profinet/Ethernet IP)	(-10...+10V): -27648~27648	(0...+10V): 0~27648	(0...+10V): 0~27648 (-10...+10V): -27648~27648	(0...+10V): 0~27648 (-10...+10V): -27648~27648
Measuring range(Others)	(-10...+10V): -32768~32767	(0...+10V): 0~65535	(0...+10V): 0~32767 (-10...+10V): -32768~32767	(0...+10V) : 0~32767 (-10...+10V) : -32768~32767
Precision	0.20%			
Conversion time	< 1ms			
Sampling rate	20-300Hz (Configuration)			

Power Supply Parameters

Connection type	Spring terminal blocks	
Working voltage	24V DC +20 %/ -15 %	
System feed current	<120mA	<200mA
Maximum area of wire	2.5mm²	1.5mm²
Maximum area of wire (AWG)	AWG14	AWG16
The minimum area of a wire	0.2mm²	0.2mm²
The minimum area of a wire (AWG)	AWG28	AWG28
Strip length	8...9mm	8...9mm

Analog input module

CE RoHS

Product	DF20-M-4AI-U-0	DF20-M-4AI-U-1	DF20-M-4AI-U-4	DF20-M-8AI-U-4

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

LED Status Indicator

LED1	Green : Power is working
LED2	Green blinks : I/O system and modules working properly

Wiring Diagram

Pin	Description
1	AI1 +
2	AI1 -
3	AI2 +
4	AI2 -
5	AI3 +
6	AI3 -
7	AI4 +
8	AI4 -



DF20-M-4AI-U-0

Pin	Description
1	AI1 +
2	AI1 -
3	AI2 +
4	AI2 -
5	AI3 +
6	AI3 -
7	AI4 +
8	AI4 -



DF20-M-4AI-U-1

Pin	Description
1	AI1 +
2	AI1 -
3	AI2 +
4	AI2 -
5	AI3 +
6	AI3 -
7	AI4 +
8	AI4 -



DF20-M-4AI-U-4

Pin	Description	Pin	Description
1	AI1 +	1	Ai5 +
2	AI1 -	2	Ai5 -
3	AI2 +	3	Ai6 +
4	AI2 -	4	Ai6 -
5	AI3 +	5	Ai7 +
6	AI3 -	6	Ai7 -
7	AI4 +	7	Ai8 +
8	AI4 -	8	Ai8 -



DF20-M-8AI-U-4

Analog input module

CE RoHS

DF20-M-4AI-I-2	DF20-M-4AI-I-3	DF20-M-4AI-I-5	DF20-M-8AI-I-5
			
Analog input module,4 ports,0... 20mA,current type	Analog input module,4 ports,4... 20mA, current type	Analog input module, 4 ports, (0…20mA)(4…20mA), current type	Analog input module, 8 ports, (0…20mA)(4…20mA),current type

Specification

Product	DF20-M-4AI-I-2	DF20-M-4AI-I-3	DF20-M-4AI-I-5	DF20-M-8AI-I-5
Number of channels	4			8
Data size	8 Byte			16 Byte
Measuring range	Current(0..20ma)	Current(4..20ma)	Current I(0…20mA)(4…20mA)	Current I(0…20mA)(4…20mA)
Signal type	Differential signal			
Connection type	2-line			
Reverse protection	Yes			
Isolation method	Magnetic isolation			
Fault diagnosis	Yes			
Internal Resistance	100Ω			
Resolution	16 Bit			
Measuring range(Profinet/Ethernet IP)	(0..20ma)0~27648	(4..20ma)0~27648	(0/4..20ma)0~27648	(0/4..20ma)0~27648
Measuring range(Others)	(0..20ma)0~65535	(4..20ma)0~65535	(0/4..20ma)0~65535	(0/4..20ma)0~65535
Precision	0.20%/±50ppm/K max.			
Conversion time	< 1ms			
Sampling rate	20-300Hz (Configuration)			

Power Supply Parameters

Connection type	Spring terminal blocks	
Working voltage	24V DC +20 %/ -15 %	
System feed current	<120mA	<200mA
Maximum area of wire	2.5mm²	1.5mm²
Maximum area of wire (AWG)	AWG14	AWG16
The minimum area of a wire	0.2mm²	0.2mm²
The minimum area of a wire (AWG)	AWG28	AWG28
Strip length	8...9mm	8...9mm

Analog input module

CE RoHS

Product	DF20-M-4AI-I-2	DF20-M-4AI-I-3	DF20-M-4AI-I-5	DF20-M-8AI-I-5
Mechanical Structure				
Protection grade	IP20			
Size(H X W X D)	100mm X 12mm X 69mm			
Installation type	35mm DIN			
Work Environment				
Working temperature	-25...60℃			
Storage temperature	-40...85℃			
Relative humidity	5... 95%RH(non-condensing)			
LED Status Indicator				
LED1	Green : Power is working			
LED2	Green blinks : I/O system and modules working properly			

Wiring Diagram

Pin	Description
1	AI1 +
2	AI1 -
3	AI2 +
4	AI2 -
5	AI3 +
6	AI3 -
7	AI4 +
8	AI4 -



DF20-M-4AI-I-2

Pin	Description
1	AI1 +
2	AI1 -
3	AI2 +
4	AI2 -
5	AI3 +
6	AI3 -
7	AI4 +
8	AI4 -



DF20-M-4AI-I-3

Pin	Description
1	AI1 +
2	AI1 -
3	AI2 +
4	AI2 -
5	AI3 +
6	AI3 -
7	AI4 +
8	AI4 -



DF20-M-4AI-I-5

Pin	Description	Pin	Description
1	AI1 +	9	AI5 +
2	AI1 -	10	AI5 -
3	AI2 +	11	AI6 +
4	AI2 -	12	AI6 -
5	AI3 +	13	AI7 +
6	AI3 -	14	AI7 -
7	AI4 +	15	AI8 +
8	AI4 -	16	AI8 -



DF20-M-8AI-I-5

Analog output module

CE RoHS

DF20-M-4AO-U-0	DF20-M-4AO-U-1	DF20-M-4AO-U-4	DF20-M-4AO-I-2	DF20-M-4AO-I-3	DF20-M-4AO-I-5
					
Analog output module,4 ports, -10… 10V,voltage type	Analog output module,4 ports, 0… 10V,voltage type	Analog output module, 4 ports, -10...+10V,0... 10V,voltage type	Analog output module,4 ports, 0… 20 mA,current type	Analog output module,4 ports, 4… 20 mA,current type	Analog output module,4 ports, 0...20mA,4... 20 mA,current type

Specification

Product	DF20-M-4AO-U-0	DF20-M-4AO-U-1	DF20-M-4AO-U-4	DF20-M-4AO-I-2	DF20-M-4AO-I-3	DF20-M-4AO-I-5
Number of channels	4					
Data size	8 Byte					
Signal type	Differential signal					
Connection type	2-line					
Overcurrent protection	Yes					
Isolation method	Magnetic isolation					
Fault diagnosis	Yes					
Resolution	16 Bit					
Precision	0.10%					
Measuring range (Profinet/Ethernet IP)	(-10...+10V)-27648~27648	(0…+10V):0~27648	(0...+10V): 0~27648 (-10...+10V): -27648~27648	(0..20ma)0~27648	(4..20ma)0~27648	(0/4..20ma)0~27648
Measuring range(Others)	(-10...+10V)-32768~32767	(0…+10V): 0~65535	(0...+10V): 0~32767 (-10...+10V): -32768~32767	(0..20ma)0~65535	(4..20ma)0~65535	(0/4..20ma)0~65535
Temperature coefficient	<20 ppm					
Conversiontime	≤ 1ms					
Load impedance	>1KΩ			<500Ω		

Power Supply Parameters

Connection type	Spring terminal blocks	
Working voltage	24V DC +20 %/ -15 %	
System feed current	<200mA	<400mA
Maximum area of wire	2.5mm²	
Maximum area of wire (AWG)	AWG14	
The minimum area of a wire	0.2mm²	
The minimum area of a wire (AWG)	AWG28	
Strip length	8…9mm	

Analog output module

CE RoHS

Product	DF20-M-4AO-U-0	DF20-M-4AO-U-1	DF20-M-4AO-U-4	DF20-M-4AO-I-2	DF20-M-4AO-I-3	DF20-M-4AO-I-5
Mechanical Structure						
Protection grade	IP20					
Size(H X W X D)	100mm X 12mm X 69mm					
Installation type	35mm DIN					
Work Environment						
Working temperature	-25…60℃					
Storage temperature	-40…85℃					
Relative humidity	5… 95%RH(non-condensing)					
LED Status Indicator						
LED1	Green： Power is working					
LED2	Green blinks：I/O system and modules working properly					

Wiring Diagram

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
5	AO3 +
6	AO3 -
7	AO4 +
8	AO4 -



DF20-M-4AO-U-0

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
5	AO3 +
6	AO3 -
7	AO4 +
8	AO4 -



DF20-M-4AO-U-1

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
5	AO3 +
6	AO3 -
7	AO4 +
8	AO4 -



DF20-M-4AO-U-4

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
5	AO3 +
6	AO3 -
7	AO4 +
8	AO4 -



DF20-M-4AO-I-2

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
5	AO3 +
6	AO3 -
7	AO4 +
8	AO4 -



DF20-M-4AO-I-3

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
5	AO3 +
6	AO3 -
7	AO4 +
8	AO4 -



DF20-M-4AO-I-5

Analog output module

CE RoHS

DF20-M-8AO-U-4



Analog output module, 8 ports, -10...+10V,0... 10V,voltage type

DF20-M-8AO-1-5



Analog output module,8 ports, 0...20mA,4... 20 mA,current type

Specification

Product	DF20-M-8AO-U-4	DF20-M-8AO-1-5
Number of channels	8	
Data size	8 Byte	
Signal type	Differential signal / Single-Ended	
Connection type	2-line	
Overcurrent protection	Yes	
Isolation method	Magnetic isolation	
Fault diagnosis	Yes	
Resolution	16 Bit	
Precision	0.10%	
Measuring range (Profinet/Ethernet IP)	(0...+10V): 0~27648 (-10...+10V): -27648~27648	(0/4..20ma)0~27648
Measuring range(Others)	(0...+10V): 0~32767 (-10...+10V): -32768~32767	(0/4..20ma)0~65535
Temperature coefficient	<20 ppm	
Conversiontime	≤ 1ms	
Load impedance	>1KΩ	<500Ω

Power Supply Parameters

Connection type	Spring terminal blocks	
Working voltage	24V DC +20 %/ -15 %	
System feed current	<400mA	<800mA
Maximum area of wire	2.5mm²	
Maximum area of wire (AWG)	AWG14	
The minimum area of a wire	0.2mm²	
The minimum area of a wire (AWG)	AWG28	
Strip length	8...9mm	

Analog output module

CE RoHS

Product	DF20-M-8AO-U-4	DF20-M-8AO-1-5
Mechanical Structure		
Protection grade	IP20	
Size(H X W X D)	100mm X 12mm X 67mm	
Installation type	35mm DIN	
Work Environment		
Working temperature	-25...75℃	
Storage temperature	-40...85℃	
Relative humidity	5... 95%RH(non-condensing)	
LED Status Indicator		
LED1	Green: Signal on Channel 1.	
LED2	Green: Signal on Channel 2.	
LED3	Green: Signal on Channel 3.	
LED4	Green: Signal on Channel 4.	
LED5	Green: Signal on Channel 5.	
LED6	Green: Signal on Channel 6.	
LED7	Green: Signal on Channel 7.	
LED8	Green: Signal on Channel 8.	
PWR	Green: Power is working.	
L/A	Green: I/O system and modules working properly.	

Wiring Diagram

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
13	AO7 +
14	AO7 -
15	AO8 +
16	AO8 -



DF20-M-8AO-U-4

Pin	Description
1	AO1 +
2	AO1 -
3	AO2 +
4	AO2 -
13	AO7 +
14	AO7 -
15	AO8 +
16	AO8 -



DF20-M-8AO-1-5

Temperature module

CE RoHS

DF20-M-2RTD-PT

Thermal Resistance (RTD) measurement module, 16 bit resolution, 2 channels

DF20-M-4RTD-PT

Thermal Resistance (RTD) measurement module, 16 bit resolution,4 channels

Wiring Diagram



DF20-M-2RTD-PT



DF20-M-4RTD-PT

Specification

Product	DF20-M-2RTD-PT	DF20-M-4RTD-PT
Number of channels	2	4
Data size	4 Byte	8 Byte
Signal type	Thermal resistance	
Signal type	PT100、PT1000	
Connection type	2/3/4-line	2/3-line
Reverse protection	Yes	
Isolation method	Magnetic isolation	
Fault diagnosis	Yes	
Resolution	16bit,0.1℃/ each number	
Frequency interference suppression	10Hz | 50Hz | 60Hz | 400Hz	
Diagnosis	Disconnection, Parameter assignment error	
Process alarm	Upper/Lower limit, per channel	
Temperature coefficient	±50ppm/K max.	
Measuring range	-200°C ~ 850°C	
Precision	±0.3%	
Conversion time	150ms	200ms

Power Supply Parameters

Product	DF20-M-2RTD-PT	DF20-M-4RTD-PT
Connection type	Spring terminal blocks	
Working voltage	24V DC +20 %/ -15 %	
System feed current	<60mA	<100mA
Maximum area of wire	2.5mm²	1.5mm²
Maximum area of wire (AWG)	AWG14	AWG16
The minimum area of a wire	0.2mm²	0.2mm²
The minimum area of a wire (AWG)	AWG28	AWG28
Strip length	8…9mm	8…9mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Temperature module

CE RoHS

DF20-M-4TC-KETJ

Thermocouple (TC) module, 4 inputs, 16 bit resolution

DF20-M-8TC-KETJ

Thermocouple (TC) module,8 inputs,16 bit resolution

Wiring Diagram



DF20-M-4TC-KETJ

DF20-M-8TC-KETJ

Specification

Product	DF20-M-4TC-KETJ	DF20-M-8TC-KETJ
Number of channels	4	8
Data size	8 Byte	16 Byte
Signal type	Thermocouple	
Signal type	E(-30~900℃), J(-210~1200℃) T(-270~400℃), K(-30~1370℃)	
Cold End compensation	Internal and external (accuracy ≤3K)	
Diagnosis	Yes	
Temperature coefficient	≤ 50 ppm/K	
Connection type	2-line	
Reverse protection	Yes	
Isolation method	Magnetic isolation	
Fault diagnosis	Yes	
Internal Resistance	/	
Resolution	16bit,0.1℃/ resolution	
Frequency interference suppression	10Hz | 50Hz | 60Hz | 400Hz	
Diagnosis	Disconnection, Parameter assignment error	
Process alarm	Upper/Lower limit, per channel	
Temperature coefficient	±0.5%	
Measuring range	-270°C ~ 1370°C	
Precision	± 0.3%	
Conversion time	125ms	

Power Supply Parameters

Product	DF20-M-2RTD-PT	DF20-M-4RTD-PT
Connection type	Spring terminal blocks	
Working voltage	24V DC +20 %/ -15 %	
System feed current	<70mA	<100mA
Maximum area of wire	2.5mm²	1.5mm²
Maximum area of wire (AWG)	AWG14	AWG16
The minimum area of a wire	0.2mm²	0.2mm²
The minimum area of a wire (AWG)	AWG28	AWG28
Strip length	8…9mm	8…9mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Pulse Counting Module

CE RoHS

DF20-M-1CNT-EL-4	DF20-M-1CNT-EL-5	DF20-M-1CNT-ELP-5	DF20-M-2CNT-PIL-4	DF20-M-2CNT-PIL-5
				
Encoder input module, 1 port,24V	Encoder input module, 1 port,5V	Encoder input /pulse output module,1 port,5V	Pulse counting module, 2 port,24V	Pulse counting module, 2 port,5V

Specification

Product	DF20-M-1CNT-EL-4	DF20-M-1CNT-EL-5	DF20-M-1CNT-ELP-5	DF20-M-2CNT-PIL-4	DF20-M-2CNT-PIL-5
Maximum frequency count	1Mhz	1Mhz	1Mhz	1Mhz	1Mhz
Number of channels	1			2	
Data size	12 Byte			28 Byte	
Input signal type	Incremental encoder			Pulse signal	
Input signal type	24V DC	5V DC	5V DC	24V DC	5V DC
Input connection type	4-line			2-line	
Output signal type	/	/	422 type	/	
Reverse protection	Yes				
Isolation method	Magnetic isolation				
Fault diagnosis	Yes				
Resolution	32 Bit				
Precision	±1 pulse				

Power Supply Parameters

Connection type	Spring terminal blocks				
System feed current	<30mA	<30mA	<200mA	<30mA	<30mA
Maximum area of wire	2.5mm²				
Maximum area of wire (AWG)	AWG14				
The minimum area of a wire	0.2mm²				
The minimum area of a wire (AWG)	AWG28				
Strip length	8…9mm				

Pulse Counting Module

CE RoHS

Product	DF20-M-1CNT-EL-4	DF20-M-1CNT-EL-5	DF20-M-1CNT-ELP-5	DF20-M-2CNT-PIL-4	DF20-M-2CNT-PIL-5
Mechanical Structure					
Protection grade	IP20				
Size(H X W X D)	100mm X 12mm X 69mm				
Installation type	35mm DIN				
Work Environment					
Working temperature	-25…60℃				
Storage temperature	-40…85℃				
Relative humidity	5… 95%RH(non-condensing)				
LED Status Indicator					
LED1	Green： Power is working				
LED2	Green blinks：I/O system and modules working properly				

Wiring Diagram

Pin	Description	Notes
1	24V	NPN:1=24V,2=signal
2	0V	PNP:1=signal,2=0V…
3	ENCA+ / ENCA	
4	ENCA- / 0V	
5	ENCB+ / ENCB	
6	ENCB- / 0V	
7	PE	
8	PE	



DF20-M-1CNT-EL-4

Pin	Description	Notes
1	24V	NPN:1=24V,2=signal
2	0V	PNP:1=signal,2=0V…
3	ENCA+ / ENCA	
4	ENCA- / 0V	
5	ENCB+ / ENCB	
6	ENCB- / 0V	
7	PE	
8	PE	



DF20-M-1CNT-EL-5

Pin	Description	Notes
1	24V	NPN:1=24V,2=signal
2	0V	PNP:1=signal,2=0V…
3	ENCA+ / ENCA	
4	ENCA- / 0V	
5	ENCB+ / ENCB	
6	ENCB- / 0V	
7	RS422_TR_out+	
8	RS422_TR_out-	



DF20-M-1CNT-ELP-5

Pin	Description	Notes
1	24V	NPN:1=24V,2=signal
2	0V	PNP:1=signal,2=0V…
3	Signal1_24V	
4	Signal1	
5	24V	NPN:5=24V,6=signal
6	0V	PNP:5=signal,6=0V…
7	Signal2_24V	
8	Signal2	



DF20-M-2CNT-PIL-4

Pin	Description	Notes
1	24V	NPN:1=24V,2=signal
2	0V	PNP:1=signal,2=0V…
3	Signal1_24V	
4	Signal1	
5	24V	NPN:5=24V,6=signal
6	0V	PNP:5=signal,6=0V…
7	Signal2_24V	
8	Signal2	



DF20-M-2CNT-PIL-5

Pulse Counting Module

CE RoHS

DF20-M-2CNT-EL-4

Pulse counting module,
2 port,24V

DF20-M-2CNT-EL-5

Pulse counting module,
2 port,5V

Specification

Product	DF20-M-2CNT-EL-4	DF20-M-2CNT-EL-5
Maximum frequency count	1Mhz	1Mhz
Number of channels	2	
Data size	28 Byte	
Input signal type	Pulse signal / Incremental encoder	
Input signal type	24V DC	5V DC
Input connection type	2-line / 4-line	
Output signal type	/	
Reverse protection	Yes	
Isolation method	Magnetic isolation	
Fault diagnosis	Yes	
Resolution	32 Bit	
Precision	±1 pulse	

Power Supply Parameters

Connection type	Spring terminal blocks
System feed current	<30mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire	0.2mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8...9mm

Pulse Counting Module

CE RoHS

Product	DF20-M-2CNT-EL-4	DF20-M-2CNT-EL-5
Mechanical Structure		
Protection grade	IP20	
Size(H X W X D)	100mm X 12mm X 67mm	
Installation type	35mm DIN	
Work Environment		
Working temperature	-25...75℃	
Storage temperature	-40...85℃	
Relative humidity	5... 95%RH(non-condensing)	
LED Status Indicator		
PWR	Green: Internal bus power supply is normal	
STA	Power on stage: green on: module initialization abnormal, green off: module initialization normal	
	Operation phase: Green flashing: The internal bus of the module is working normally, green off: The internal bus of the module is working abnormally	
TP1/TP2	On: Input signal valid Off: Input signal invalid	
A1/A2	On: Input signal valid Off: Input signal invalid	
B1/B2	On: Input signal valid Off: Input signal invalid	
UP1/UP2	On: encoder rotates in the forward direction Off: the encoder is stationary or rotating in the opposite direction	
DN1/DN2	On: encoder rotates in the forward direction Off: the encoder is stationary or rotating in the opposite direction	
FP	On: Module power is normal Off: Module power is abnormal	

Wiring Diagram



DF20-M-2CNT-EL-4



DF20-M-2CNT-EL-5

Pulse output module

DF20-M-2PWM

Pulse output module,2 port,24V

Wiring Diagram



Pin	Description	Pin	Description
1	A 1+	2	A 1-
3	B 1+	4	B 1-
5	A 2+	6	A 2-
7	B 2+	8	B 2-
9	24V	10	24V
11	P1	12	D1
13	P2	14	D2
15	GND	16	GND

DF20-M-2PWM

Specification

Product	DF20-M-2PWM
Maximum frequency count	4Mhz
Number of channels	2
Data size	28 Byte
Output signal type	Pulse signal / PWM
Output connection type	24V DC
Isolation method	2-line / 4-line
Fault diagnosis	Magnetic isolation
Resolution	Yes
Precision	32 Bit
	±1 pulse

Power Supply Parameters

Product	DF20-M-2PWM
Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
System feed current	<150mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire	0.2mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 67mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…75℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

Bridge Module

CE RoHS

DF20-M-2LC-S-5



Bridge measurement module, 16-bit resolution, 2-channel

Wiring Diagram



Pin	描述 Description
1	Ref power 5V
2	Ref power 0V
3	Signal1 +
4	Signal1 -
5	Signal2 +
6	Signal2 -
7	PE
8	PE

DF20-M-2LC-S-5

Specification

Product	DF20-M-2LC-S-5
Measuring range	0-10mV
Number of channels	2
Signal type	Load CellBridge, pressure sensor, Load Cell
Connection type	4-line
Reverse protection	Yes
Isolation method	Magnetic isolation
Data size	8 Byte
Fault diagnosis	Yes
Internal resistance	>500KΩ
Resolution16bit	16bit
Frequency interference suppression	10Hz | 50Hz | 60Hz | 400Hz
Diagnosis	Parameter assignment error
Precision	0.20%
Measuring range	-32768~32767
Conversion time	3.3ms

Power Supply Parameters

Product	DF20-M-2LC-S-5
Connection type	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %
System feed current	<210mA
Maximum area of wire	2.5mm²
Maximum area of wire (AWG)	AWG14
The minimum area of a wire	0.2mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8…9mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

LED Status Indicator

LED1	Green: Power is working
LED2	Green blinks: I/O system and modules working properly

Voltage distribution module

CE RoHS

DF20-M-DC-U-24	DF20-M-DC-U-0	DF20-M-T-8L	DF20-M-DC-UD-5
			
Voltage distribution module, 16 channel 24VDC	Voltage distribution module, 16 channel 0VDC	Extended module, 8channel, 2 line	Voltage distribution module, 24VDC to 5VDC

Specification

Product	DF20-M-DC-U-24	DF20-M-DC-U-0	DF20-M-T-8L	DF20-M-DC-UD-5
Number of channels	16	16	8	1
Isolation method	/	/	/	/

Power Supply Parameters

Connection type	Spring terminal blocks	Spring terminal blocks	Spring terminal blocks	Spring terminal blocks
Working voltage	24V DC +20 %/ -15 %	0V DC	0V…36VDC	24V DC +20 %/ -15 %
Reverse power protection	/			YES
Supply system voltage	/			5VDC
Supply system current	/			Max.2A
Supply load voltage	24V DC +20 %/ -15 %	0VDC	Voltage distribution	24V DC +20 %/ -15 %
Supply load current (MAX)	5A			8A
Maximum area of wire	1.5mm²			2.5mm²
Maximum area of wire (AWG)	AWG16			AWG14
The minimum area of a wire	0.2mm²			0.2mm²
The minimum area of a wire (AWG)	AWG28			AWG28
Strip length	8…9mm			8…9mm

Voltage distribution module

Product	DF20-M-DC-U-24	DF20-M-DC-U-0	DF20-M-T-8L	DF20-M-DC-UD-5

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 69mm
Installation type	35mm DIN

Work Environment

Working temperature	-25…60℃
Storage temperature	-40…85℃
Relative humidity	5… 95%RH(non-condensing)

LED Status Indicator

POWER-1、POWER-2	/	Green: The system power is working.
POWER-7、POWER-8	/	Green: The load power is working.

Wiring Diagram

Pin	Description	Pin	Description
1	Load_24V	9	Load_24V
2	Load_24V	10	Load_24V
3	Load_24V	11	Load_24V
4	Load_24V	12	Load_24V
5	Load_24V	13	Load_24V
6	Load_24V	14	Load_24V
7	Load_24V	15	Load_24V
8	Load_24V	16	Load_24V



DF20-M-DC-U-24

Pin	Description	Pin	Description
1	Load_0V	9	Load_0V
2	Load_0V	10	Load_0V
3	Load_0V	11	Load_0V
4	Load_0V	12	Load_0V
5	Load_0V	13	Load_0V
6	Load_0V	14	Load_0V
7	Load_0V	15	Load_0V
8	Load_0V	16	Load_0V



DF20-M-DC-U-0

Pin	Description	Pin	Description
1	Signal1	9	Signal5
2	Signal1	10	Signal5
3	Signal2	11	Signal6
4	Signal2	12	Signal6
5	Signal3	13	Signal7
6	Signal3	14	Signal7
7	Signal4	15	Signal8
8	Signal4	16	Signal8



DF20-M-T-8L

Pin	Description
1	System_24V
2	System_0V
3	Load_24V
4	Load_24V
5	Load_0V
6	Load_0V
7	PE
8	PE



DF20-M-DC-UD-5

Serial communication module

CE RoHS

DF20-M-1COM-232/485/422

Serial communication module, 1 channel

Specification

Product	DF20-M-1COM-232/485/422
Interface	RS232/RS485/RS422
Number of channels	1
Agreement	Modbus RTU/ASCII master and slave modes; Free protocol transparent mode
BAUD	2400bps - 500000bps
Data bits	7bit/8bit
Check bit	None/Even/Odd/Space/Mark
Stop bit	1bit/2bit
Maximum data frame length	128 byte

Power Supply Parameters

Connection type	Spring terminal blocks
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG26
Strip length	8...10mm

Mechanical Structure

Protection grade	IP20
Size(H X W X D)	111mm X 12mm X 75mm
Installation type	35mm DIN

Serial communication module

CE RoHS

Product	DF20-M-1COM-232/485/422

Work Environment

Working temperature	-25...60℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

LED Status Indicator

PW	Green: Internal bus power supply is normal
ST	Power on stage: green on: module initialization abnormal, green off: module initialization normal
	Operation phase: Green flashing: The internal bus of the module is working normally, green off: The internal bus of the module is working abnormally
COM	On: Input signal valid Off: Input signal invalid
MST	On: Input signal valid Off: Input signal invalid
SLV	On: Input signal valid Off: Input signal invalid
232	In 232 mode, on: connection normal off: connection abnormal
485	In 485 mode, on: connection normal off: connection abnormal
422	In 422 mode, on: connection normal off: connection abnormal
TS	On: Normal communication transmission Off: Abnormal communication transmission
RX	On: normal communication reception Off: abnormal communication reception
EP	On: External power supply normal Off: External power supply normal

Wiring Diagram



Pin	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
RS485	A	B			GND				24V+	GND	5V+	GND				
RS422	TX+	TX-	RX+	RX-												
RS232													CTS	RTS	RXD	TXD

IO-Link communication modules

CE RoHS

DF20-M-4IOL



IO-Link communication modules, 4 channel

Specification	
Product	DF50-M-4IOL
Number of channels	4
IO-Link Input Mode	
Connection type	3-line/5-line
Port type	A type
Digital Input Mode	
Input description	When the IO-Link port is set to DI
Input type	PNP
Connect system	3-line
Input Voltage	24 V DC
"0" signal	-0.3 V DC ... 8 V DC
"1" signal	12.9 V DC ... 24.3 V DC
Digital Output Mode	
Output description	When the IO-Link port is set to DO
Output type	PNP
Connection method	Push-in
Connect system	2,3-line
Rated output voltage	24 V DC
Rated current per channel	500 mA

Power Supply Parameters	
Product	DF50-M-4IOL
Connection type	Spring terminal blocks
System feed current	<100mA
Maximum area of wire	1.5mm²
Maximum area of wire (AWG)	AWG16
The minimum area of a wire	0.14mm²
The minimum area of a wire (AWG)	AWG28
Strip length	8...9mm
Mechanical Structure	
Protection grade	IP20
Size(H X W X D)	100mm X 12mm X 67mm
Installation type	35mm DIN
Work Environment	
Working temperature	-25...75℃
Storage temperature	-40...85℃
Relative humidity	5... 95%RH(non-condensing)

IO-Link communication modules

CE RoHS

Product	DF20-M-4IOL

LED Status Indicator

PWR	Green: Internal bus power supply is normal
STA	Power on stage: green on: module initialization abnormal, green off: module initialization normal
	Operation phase: Green flashing: The internal bus of the module is working normally, Green off: The internal bus of the module is working abnormally
L0~L3	Green on: Corresponding channel IO-LINK communicates normally Green blinks: No IO-LINK slave access on the corresponding channel Green off: the corresponding channel is not configured for IO-LINK mode
F0~F3	Red on: corresponding channel reports error Red off: no error on the corresponding channel
I0~I3	Green on: DI input valid signal Green off: DI does not input valid signal

Wiring Diagram

Pin	Description	Pin	Description
1	C/Q 0	2	DI 0
3	L+ 0	4	L- 0
5	C/Q 1	6	DI 1
7	L+ 1	8	L- 1
9	C/Q 2	10	DI 2
11	L+2	12	L- 2
13	C/Q 3	14	DI 3
15	L+ 3	16	L- 3



DF20-M-4IOL

DF20 series dimension

DF20 series bus coupler & Terminal cover dimension



DF20 series I/O module dimension



Module with 8 wiring holes

Module with 16 wiring holes

Module with 32 wiring holes

DEGSON Fieldbus High performance IP67 I/O

Reliable

Robust

Durable

- Supports multiple mainstream fieldbus protocols
- Flexible and suitable for multiple applications and work environments
- IP67/IP65 high protection structure
- Rich models and I/O types
- Extended Bus Technology (DH Bus) fully isolated, high-speed
- A single fieldbus node can scale up to 512DI/512DO/128AI/128AO

Application Extension Graph



IO-Link

IO-Link

Universal Smart Easy



Pin layout: IEC 60947-5-2

Pin	Signal	Definition	Standard
1	L+	24 V	IEC 61131-2
2	I/Q	Not connected, DI, or DO	IEC 61131-2
3	L-	0 V	IEC 61131-2
4	Q	"Switching signal" (SIO)	IEC 61131-2
	C	"Coded switching" (COM1, COM2, COM3)	IEC 61131-9

- IO-Link is the world's first standardized I/O technology for communication with sensors and actuators (IEC 61131-9)
- No additional requirements for cable materials are required, and the conventional 3-wire connection method can achieve powerful point-to-point communication
- IO-Link is not a fieldbus, but a further development of classic sensor and actuator connection technology

DH Bus

- DEGSON High performance Bus
- DEGSON internal communication protocol for efficient remote extension modules
- DH Bus single link can extend up to 16 modules, with a maximum length of 120m, and adjacent stations with a maximum length of 15m
- The last DH Bus station needs to increase terminal resistance to ensure stable and reliable communication



Fieldbus Module

DFH67-PN-IOL2A4B-DHB2

Internal version

Category and quantity of data/signal interfaces

- IOL: IO-Link (A: Class A; B:Class B)
- DHB: DH Bus (DEGOSN High performance Bus)
- DI: Digital Input (P: PNP; N:NPN)
- DO: Digital Output (P: PNP; N: NPN)

Category of Fieldbus interface

- PN: PROFINET
- EC: EtherCAT
- EIP: EtherNET/IP
- CLI: CC-Link IE Field Basic
- MT: ModbusTCP

Product Series

- DEGSON Fieldbus High performance IP67 I/O



Fieldbus module with DH Bus interface



Fieldbus module without DH Bus interface

DEGSON Fieldbus High performance IP67 I/O

Fieldbus Module

NO.	Order NO.		Fieldbus interface					Data/Signal interfaces				
			PROFINET	EtherCAT	EtherNET/IP	CC-Link IE	Modbus TCP	IO-Link Class A	IO-Link Class B	DH Bus	DI	DO
1	DFH67-PN-IOL2A4B-DHB2		●					2	4	2	2 PNP	
2	DFH67-PN-IOL6A-DHB2		●					6		2	6 PNP	
3	DFH67-PN-IOL8A		●					8			8 PNP	
4	DFH67-EC-IOL2A4B-DHB2			●				2	4	2	2 PNP	
5	DFH67-EC-IOL6A-DHB2			●				6		2	6 PNP	
6	DFH67-EC-IOL8A			●				8			8 PNP	
7	DFH67-EIP-IOL2A4B-DHB2				●			2	4	2	2 PNP	
8	DFH67-EIP-IOL6A-DHB2				●			6		2	6 PNP	
9	DFH67-EIP-IOL8A				●			8			8 PNP	
10	DFH67-CLI-IOL2A4B-DHB2					●		2	4	2	2 PNP	
11	DFH67-CLI-IOL6A-DHB2					●		6		2	6 PNP	
12	DFH67-CLI-IOL8A					●		8			8 PNP	
13	DFH67-PN-DI12P-DHB2		●							2	12 PNP	
14	DFH67-PN-DI12N-DHB2		●							2	12 NPN	
15	DFH67-EC-DI12P-DHB2			●						2	12 PNP	
16	DFH67-EC-DI12N-DHB2			●						2	12 NPN	
17	DFH67-EIP-DIO12P-DHB2	1*			●					2	12 PNP (Configurable)	
18	DFH67-EIP-DIO12N-DHB2	1*			●					2	12 NPN (Configurable)	
19	DFH67-CLI-DIO12P-DHB2	1*				●				2	12 PNP (Configurable)	
20	DFH67-CLI-DIO12N-DHB2	1*				●				2	12 NPN (Configurable)	
21	DFH67-MT-DIO12P-DHB2	1*					●			2	12 PNP (Configurable)	
22	DFH67-MT-DIO12N-DHB2	1*					●			2	12 NPN (Configurable)	

1*: This model requires less usage and has a longer lead time.

IO-Link module

DFH67-IOLA-DIO16P-M12

Internal version

Signal interface specification
- M08
- M12

Category and quantity of signal interfaces
- DI: Digital Input (P: PNP; N: NPN)
- DO: Digital Output (P: PNP; N:NPN)
- AI: Analog Input (I: Current ; U: Voltage)
- AO: Analog Output (I: Current ; U: Voltage)
- RTD: Resistance Temperature Detector
- TC: Thermocouple signal

Category of data interface
- IOLA: IO-Link Class A
- IOLB: IO-Link Class B
- DHB1: With 1 DH Bus extension port

Product Series
- DEGSON Fieldbus High performance IP67 I/O



IO-Link module with DH Bus interface



IO-Link module without DH Bus interface

IO-Link module

NO.	Order NO.		Data interfaces			Signal interfaces									
			IO-Link Class A	IO-Link Class B	DH Bus	DI-P	DO-P	DI-N	DO-N	AI-I	AO-I	AI-U	AO-U	RTD	TC
1	DFH67-IOLA-DIO16P-M12		●			16 (Configurable)									
2	DFH67-IOLA-DIO16N-M12		●					16 (Configurable)							
3	DFH67-IOLA-DHB1-DIO16P-M12		●		1	16 (Configurable)									
4	DFH67-IOLA-DHB1-DIO16N-M12		●		1			16 (Configurable)							
5	DFH67-IOLA-DHB1-AI4I-AO4I-M12	1*	●		1					4	4				
6	DFH67-IOLA-DHB1-AI4U-AO4U-M12	1*	●		1							4	4		
7	DFH67-IOLA-DHB1-AI8I-M12	1*	●		1					8					
8	DFH67-IOLA-DHB1-AI8U-M12	1*	●		1							8			
9	DFH67-IOLA-DHB1-AI4I-M12	1*	●		1					4					
10	DFH67-IOLA-DHB1-AI4U-M12	1*	●		1							4			

1*: This model requires less usage and has a longer lead time.

DH Bus module

DFH67-DHB-DIO16P-M12

Internal version

Signal interface specification
- M08
- M12

Category and quantity of signal interfaces
- DI: Digital Input (P: PNP; N: NPN)
- DO: Digital Output (P: PNP; N:NPN)
- AI: Analog Input (I: Current ; U: Voltage)
- AO: Analog Output (I: Current ; U: Voltage)
- RTD: Resistance Temperature Detector
- TC:Thermocouple signal

DH Bus interface
- DEGOSN High performance Bus

Product Series
- DEGSON Fieldbus High performance IP67 I/O



DH Bus module for M12 signal interface



DH Bus module for M8 signal interface

DH Bus module

NO.	Order NO.		Data interfaces			Signal interfaces									
			IO-Link Class A	IO-Link Class B	DH Bus	DI-P	DO-P	DI-N	DO-N	AI-I	AO-I	AI-U	AO-U	RTD	TC
1	DFH67-DHB-DIO16P-M12				●	16 (Configurable)									
2	DFH67-DHB-DIO16N-M12				●			16 (Configurable)							
3	DFH67-DHB-DI16P-M12				●	16									
4	DFH67-DHB-DI16N-M12				●			16							
5	DFH67-DHB-DI8P-M08				●	8									
6	DFH67-DHB-DI8N-M08				●			8							
7	DFH67-DHB-DO16P-M12				●		16								
8	DFH67-DHB-DO16N-M12				●				16						
9	DFH67-DHB-DO8P-M08				●		8								
10	DFH67-DHB-DO8N-M08				●				8						
11	DFH67-DHB-DI8P-DO8P-M12				●	8	8								
12	DFH67-DHB-DI8N-DO8N-M12				●			8	8						
13	DFH67-DHB-DI4P-DO4P-M08	1*			●	4	4								
14	DFH67-DHB-DI4N-DO4N-M08	1*			●			4	4						
15	DFH67-DHB-AI8I-M12				●					8					
16	DFH67-DHB-AI8U-M12				●							8			
17	DFH67-DHB-AI4I-M12				●					4					
18	DFH67-DHB-AI4U-M12				●							4			
19	DFH67-DHB-AO4I-AO4U-M12				●						4		4		
20	DFH67-DHB-AO8I-M12	1*			●						8				
21	DFH67-DHB-AO8U-M12	1*			●								8		
22	DFH67-DHB-AO4I-M12	1*			●						4				
23	DFH67-DHB-AO4U-M12	1*			●								4		
24	DFH67-DHB-AI4I-AO4I-M12	1*			●					4	4				
25	DFH67-DHB-AI4U-AO4U-M12	1*			●							4	4		
26	DFH67-DHB-RTD8-M12				●									8	
27	DFH67-DHB-RTD4-M12				●									4	
28	DFH67-DHB-TC8-M12	1*			●										8
29	DFH67-DHB-TC4-M12	1*			●										4

1*: This model requires less usage and has a longer lead time.

IO-Link Master

CE RoHS



PROFINET-RT PROTOCOL

Features

- Designed according to IO-Link v1.1 specifications
- IO-Link master supports COM1/COM2/COM3
- IO-Link Interface supports Class-A or Class-B type
- Support DH BUS extension

Ordering Data

Order No.	DFH67-PN-IOL2A4B-DHB2	DFH67-PN-IOL6A-DHB2	DFH67-PN-IOL8A
Description	PROFINET-RT slave & IO-Link master 2* Class A + 4*Class B 2*DH BUS interface	PROFINET-RT slave & IO-Link master 6* Class A 2*DH BUS interface	PROFINET-RT slave & IO-Link master 8* Class A

Fieldbus

Protocol	PROFINET-RT
Operation mode	Automatic negotiation ; Auto MDI/MDIX
Transmission speed	10/100 Mbps
IP allocation	Programming software configuration, or allocation by master
Topology	Yes
MRP	Yes

Power Supply

Working voltage	24 VDC (18…30 VDC)
Current consumption	Max. 200mA
System and Input	Us，Max. 8A
Actuators	Ua，Max. 8A
Electrical isolation	Us/Ua：24V isolated，0V isolation

Interface Type

Power supply	2 * L-code 5pin，Plug(input) + Socket(output)	
Fieldbus	2 * M12 D-code 4pin，Socket	
Signal	6 * M12 A-code 5pin，Socket	8 * M12 A-code 5pin，Socket
DH Bus interface	2 * M12 B-code 5pin，Socket	/
Number of DH Bus modules	Max. 32 (16 × 2)	/
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m	/

Electrical Parameters

IO-Link channels	6	6	8
Interface Type	2*Class-A + 4*Class-B	6*Class-A	8*Class-A
IO-Link version	IO-Link V1.1		
Transmission speed	COM1 (4.8kbps)、COM2 (38.4kbps)、COM3 (230.4kbps)		

IO-Link Master CE RoHS

Ordering Data

Order No.	DFH67-PN-IOL2A4B-DHB2	DFH67-PN-IOL6A-DHB2	DFH67-PN-IOL8A

Electrical Parameters

Signal type	DI/DO/IO-Link Configurable by software		
Number of inputs	Max. 8	Max. 12	Max. 16
Us current (Pin1&Pin3)	IO-Link interface : Max. 1.6A ; Signal interface: Max. 200mA		
Ua current (Pin2&Pin5)	Per channel : Max. 2A	/	
Input signal type	PNP type		
Input filter time	Max. 1.6ms		
Number of outputs	Max. 6	Max. 6	Max. 8
Output current	Per channel : Max. 2A		
Output signal type	PNP/NPN type(configurable)		
Output switch frequency	Resistive load : 100Hz ; Inductive load : 5Hz		

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

IO-Link Master

CE RoHS



EtherCAT PROTOCOL

Features

- Designed according to IO-Link v1.1 specifications
- IO-Link master supports COM1/COM2/COM3
- IO-Link Interface supports Class-A or Class-B type
- Support DH BUS extension

Ordering Data

Order No.	DFH67-EC-IOL2A4B-DHB2	DFH67-EC-IOL6A-DHB2	DFH67-EC-IOL8A
Description	EtherCAT slave & IO-Link master 2* Class A + 4*Class B 2*DH BUS interface	EtherCAT slave & IO-Link master 6* Class A 2*DH BUS interface	EtherCAT slave & IO-Link master 8* Class A

Fieldbus

Protocol	EtherCAT
Operation mode	Automatic negotiation ; Auto MDI/MDIX
Transmission speed	10/100 Mbps
IP allocation	System automatic allocation or DIP switch setting
Topology	Yes

Power Supply

Working voltage	24 VDC (18...30 VDC)
Current consumption	Max. 200mA
System and Input	Us，Max. 8A
Actuators	Ua，Max. 8A
Electrical isolation	Us/Ua：24V isolated，0V isolation

Interface Type

Power supply	2 * L-code 5pin，Plug(input) + Socket(output)	
Fieldbus	2 * M12 D-code 4pin，Socket	
Signal	6 * M12 A-code 5pin，Socket	8 * M12 A-code 5pin，Socket
DH Bus interface	2 * M12 B-code 5pin，Socket	/
Number of DH Bus modules	Max. 32 (16 × 2)	/
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m	/

Electrical Parameters

IO-Link channels	6	6	8
Interface Type	2*Class-A + 4*Class-B	6*Class-A	8*Class-A
IO-Link version	IO-Link V1.1		
Transmission speed	COM1 (4.8kbps)、COM2 (38.4kbps)、COM3 (230.4kbps)		

IO-Link Master

CE RoHS

Ordering Data

Order No.	DFH67-EC-IOL2A4B-DHB2	DFH67-EC-IOL6A-DHB2	DFH67-EC-IOL8A

Electrical Parameters

Signal type	DI/DO/IO-Link Configurable by software		
Number of inputs	Max. 8	Max. 12	Max. 16
Us current (Pin1&Pin3)	IO-Link interface : Max. 1.6A ; Signal interface: Max. 200mA		
Ua current (Pin2&Pin5)	Per channel : Max. 2A	/	
Input signal type	PNP type		
Input filter time	Max. 1.6ms		
Number of outputs	Max. 6	Max. 6	Max. 8
Output current	Per channel : Max. 2A		
Output signal type	PNP/NPN type(configurable)		
Output switch frequency	Resistive load : 100Hz ; Inductive load : 5Hz		

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

IO-Link Master

CE RoHS



CC-Link IE Field Basic PROTOCOL

Features

- Designed according to IO-Link v1.1 specifications
- IO-Link master supports COM1/COM2/COM3
- IO-Link Interface supports Class-A or Class-B type
- Support DH BUS extension

Ordering Data

Order No.	DFH67-CLI-IOL2A4B-DHB2	DFH67-CLI-IOL6A-DHB2	DFH67-CLI-IOL8A
Description	CC-Link IEFB slave & IO-Link master 2* Class A + 4*Class B 2*DH BUS interface	CC-Link IEFB slave & IO-Link master 6* Class A 2*DH BUS interface	CC-Link IEFB slave & IO-Link master 8* Class A

Fieldbus

Protocol	CC-Link IE Field Basic
Operation mode	Remote device station
Transmission speed	10/100 Mbps
IP allocation	Web server configuration or DIP switch setting
Topology	Yes

Power Supply

Working voltage	24 VDC (18...30 VDC)
Current consumption	Max. 200mA
System and Input	Us，Max. 8A
Actuators	Ua，Max. 8A
Electrical isolation	Us/Ua：24V isolated，0V isolation

Interface Type

Power supply	2 * L-code 5pin，Plug(input) + Socket(output)	
Fieldbus	2 * M12 D-code 4pin，Socket	
Signal	6 * M12 A-code 5pin，Socket	8 * M12 A-code 5pin，Socket
DH Bus interface	2 * M12 B-code 5pin，Socket	/
Number of DH Bus modules	Max. 32 (16 × 2)	/
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m	/

Electrical Parameters

IO-Link channels	6	6	8
Interface Type	2*Class-A + 4*Class-B	6*Class-A	8*Class-A
IO-Link version	IO-Link V1.1		
Transmission speed	COM1 (4.8kbps)、COM2 (38.4kbps)、COM3 (230.4kbps)		

IO-Link Master CE RoHS

Ordering Data

Order No.	DFH67-CLI-IOL2A4B-DHB2	DFH67-CLI-IOL6A-DHB2	DFH67-CLI-IOL8A

Electrical Parameters

Signal type	DI/DO/IO-Link Configurable by software		
Number of inputs	Max. 8	Max. 12	Max. 16
Us current (Pin1&Pin3)	IO-Link interface : Max. 1.6A ; Signal interface: Max. 200mA		
Ua current (Pin2&Pin5)	Per channel : Max. 2A	/	
Input signal type	PNP type		
Input filter time	Max. 1.6ms		
Number of outputs	Max. 6	Max. 6	Max. 8
Output current	Per channel : Max. 2A		
Output signal type	PNP/NPN type(configurable)		
Output switch frequency	Resistive load : 100Hz ; Inductive load : 5Hz		

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

IO-Link Master

CE RoHS



EtherNet/IP PROTOCOL

Features

- Designed according to IO-Link v1.1 specifications
- IO-Link master supports COM1/COM2/COM3
- IO-Link Interface supports Class-A or Class-B type
- Support DH BUS extension

Ordering Data

Order No.	DFH67-EIP-IOL2A4B-DHB2	DFH67-EIP-IOL6A-DHB2	DFH67-EIP-IOL8A
Description	EtherNet/IP slave & IO-Link master 2* Class A + 4*Class B 2*DH BUS interface	EtherNet/IP slave & IO-Link master 6* Class A 2*DH BUS interface	EtherNet/IP slave & IO-Link master 8* Class A

Fieldbus

Protocol	EtherNet/IP
Operation mode	Automatic negotiation ; Auto MDI/MDIX
Transmission speed	10/100 Mbps
IP allocation	Web server configuration or DIP switch setting
Topology	Yes

Power Supply

Working voltage	24 VDC (18…30 VDC)
Current consumption	Max. 200mA
System and Input	Us，Max. 8A
Actuators	Ua，Max. 8A
Electrical isolation	Us/Ua：24V isolated，0V isolation

Interface Type

Power supply	2 * L-code 5pin，Plug(input) + Socket(output)		
Fieldbus	2 * M12 D-code 4pin，Socket		
Signal	6 * M12 A-code 5pin，Socket		8 * M12 A-code 5pin，Socket
DH Bus interface	2 * M12 B-code 5pin，Socket		/
Number of DH Bus modules	Max. 32 (16 × 2)		/
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m		/

Electrical Parameters

IO-Link channels	6	6	8
Interface Type	2*Class-A + 4*Class-B	6*Class-A	8*Class-A
IO-Link version	IO-Link V1.1		
Transmission speed	COM1 (4.8kbps)、COM2 (38.4kbps)、COM3 (230.4kbps)		

IO-Link Master

CE RoHS

Ordering Data

Order No.	DFH67-EIP-IOL2A4B-DHB2	DFH67-EIP-IOL6A-DHB2	DFH67-EIP-IOL8A

Electrical Parameters

Signal type	DI/DO/IO-Link Configurable by software		
Number of inputs	Max. 8	Max. 12	Max. 16
Us current (Pin1&Pin3)	IO-Link interface : Max. 1.6A ; Signal interface: Max. 200mA		
Ua current (Pin2&Pin5)	Per channel : Max. 2A	/	
Input signal type	PNP type		
Input filter time	Max. 1.6ms		
Number of outputs	Max. 6	Max. 6	Max. 8
Output current	Per channel : Max. 2A		
Output signal type	PNP/NPN type(configurable)		
Output switch frequency	Resistive load : 100Hz ; Inductive load : 5Hz		

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

IO-Link Master

CE RoHS

Dimension

M12-MASTER



Power supply interface



Power supply L-code plug (Metal) - PWR1
1-System and signal power supply Us+
2-Actuator Power supply Ua-
3-System and signal power supply Us-
4-Actuator Power supply Ua+
5-PE-Protective grounding PE



Power supply L-code socket (Metal) - PWR2

Fieldbus & DH BUS interface



Fieldbus interface D-code socket(Metal) - ETH1/ETH2
1-Transmitter Tx+
2-Receiver Rx+
3-Transmitter Tx-
4-Receiver Rx-



DH Bus B-code socket (Black) - D01/D02
1-Power supply 24V+
2-Data signal A
3-Data signal B
4-Power supply GND
5-ADR 1

IO-Link interface

M12 A-code socket (Green)



IO-Link Class-A interface (Green)
1-Power supply 24V+
2-Digital Input/Output
3-Power supply GND
4-IO-Link C/Q
5-Protective grounding PE

IO-Link Class-B interface (Green)
1-Power supply 24V+
2-Actuator power supply P24
3-Power supply GND
4-IO-Link C/Q
5-Actuator power supply N24

IO-Link digital device

CE RoHS

Features

- Input/Output photoelectric isolation
- Input or Output configurable
- Overvoltage and short circuit protection function
- Designed according to IO-Link v1.1 specifications, Communication rate : COM2

Ordering Data

Order No.	DFH67-IOLA-DHB1-DIO16P-M12	DFH67-IOLA-DHB1-DIO16N-M12
Description	16 DI/DO , PNP , 8*M12	16 DI/DO , NPN , 8*M12

Interface Type

IO-Link interface	1 * M12 A-code 4pin Plug
DH Bus interface	1 * M12 B-code 5pin Socket
Power	IO Link interface power supply : 24V, 1.6A
Signal	8 * M12 A-code 5pin , Socket

Electrical Parameters

Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	Max. 16 , PNP type	Max. 16 , NPN type
Input signal type	Sensor, Limit switch, Contact, etc	
Input filter time	Max. 2ms	
Number of outputs	Max. 16 , PNP type	Max. 16 , NPN type
Output signal type	Actuators, Indicator lights, Mini electromagnetic valves, etc	
Output current	Per channel : Max. 0.3A , Total : Max. 1.5A	
Output switch frequency	Resistive load : 100Hz ; Inductive load : 5Hz	
Extending capability	Up to 3 DH BUS extension modules (up to 1 analog or temperature module) , Total length not exceeding 60m	

IO-Link Parameters

Interface Type	CLASS A
IO-Link version	IO-Link V1.1
Transmission speed	COM2 (38.4kbps)
Process data	2 input bytes, 2 output bytes

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

IO-Link digital device

CE RoHS

Features

- Input/Output photoelectric isolation
- Input or Output configurable
- Overvoltage and short circuit protection function
- Designed according to IO-Link v1.1 specifications, Communication rate : COM2

Ordering Data		
Order No.	DFH67-IOLA-DIO16P-M12	DFH67-IOLA-DIO16N-M12
Description	16 DI/DO，PNP，8*M12	16 DI/DO，NPN，8*M12
Interface Type		
IO-Link interface	1 * M12 A-code 4pin Plug	
Power	1 * M12 L-code 5pin Plug : 24V，8A	
Signal	8 * M12 A-code 5pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	Max. 16，PNP type	Max. 16，NPN type
Input signal type	Sensor, Limit switch, Contact, etc	
Input filter time	Max. 2ms	
Number of outputs	Max. 16，PNP type	Max. 16，NPN type
Output signal type	Actuators, Indicator lights, Mini electromagnetic valves, etc	
Output current	Per channel : Max. 0.5A , Total : Max. 8A	
Output switch frequency	Resistive load : 100Hz ; Inductive load : 5Hz	
Extending capability	No	
IO-Link Parameters		
Interface Type	CLASS A	
IO-Link version	IO-Link V1.1	
Transmission speed	COM2（38.4kbps）	
Process data	2 input bytes, 2 output bytes	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

IO-Link analog device

CE RoHS

Features

- Resolution : 16 bit
- Interface Type : Class-A
- Designed according to IO-Link v1.1 specifications, Communication rate : COM2

Ordering Data		
Order No.	DFH67-IOLA-DHB1-AI4I-AO4I-M12	DFH67-IOLA-DHB1-AI4U-AO4U-M12
Description	4 AI+4AO , Current type , 8*M12	4 AI+4AO , Voltage type , 8*M12
Interface Type		
IO-Link interface	1 * M12 A-code 4pin Plug	
DH Bus interface	1 * M12 B-code 5pin Socket	
Power	IO Link interface power supply : 24V, 1.6A	
Signal	8 * M12 A-code 5pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	4	
Input signal type	4AI（0~20mA，First 4 channels）	4AI（±10V，First 4 channels）
Input impedance	< 450Ω	> 1kΩ
Number of outputs	4	
Output signal type	4AO（0~20mA，Last 4 channels）	4AO（±10V，Last 4 channels）
Resolution	16Bit	
Conversion time	Max. 300us	
Precision	± 0.3%	
Extending capability	Up to 3 DH BUS extension modules (up to 1 analog or temperature module)，Total length not exceeding 60m	
IO-Link Parameters		
Interface Type	CLASS A	
IO-Link version	IO-Link V1.1	
Transmission speed	COM2（38.4kbps）	
Process data	8 input bytes, 8 output bytes	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

IO-Link analog device

CE RoHS

Features

- Designed according to IO-Link v1.1 specifications，Communication rate : COM2
- Interface Type : Class-A

Ordering Data

Order No.	DFH67-IOLA-DHB1-AI4I-M12	DFH67-IOLA-DHB1-AI4U-M12	DFH67-IOLA-DHB1-AI8I-M12	DFH67-IOLA-DHB1-AI8U-M12
Description	4 AI , Current type , 8*M12	4 AI , Voltage type , 8*M12	8 AI , Current type , 8*M12	8 AI , Voltage type , 8*M12

Interface Type

IO-Link interface	1 * M12 A-code 4pin Plug
DH Bus interface	1 * M12 B-code 5pin Socket
Power	IO Link interface power supply : 24V, 1.6A
Signal	8 * M12 A-code 5pin，Socket

Electrical Parameters

Supply voltage	24 VDC (18...30V)			
Current consumption	Max. 50mA			
Number of inputs	4 (First 4 channels)		8	
Input signal type	0~20mA	±10V	0~20mA	±10V
Input impedance	Current input : 250Ω ; Voltage input : 1MΩ			
Resolution	16Bit			
Conversion time	Max. 300us			
Precision	± 0.3%			
Extending capability	Up to 3 DH BUS extension modules (up to 1 analog or temperature module)， Total length not exceeding 60m			

IO-Link Parameters

Interface Type	CLASS A	
IO-Link version	IO-Link V1.1	
Transmission speed	COM2 (38.4kbps)	
Process data	8 input bytes	16 input bytes

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

IO-Link module

CE RoHS

Dimension



IO-Link interface



IO-Link Class - A Plug (Metal)
1-Power supply 24V+
2-NC
3-Power supply GND
4-IO-Link C/Q

Power supply interface / DH Bus interface



Power supply L-code plug (Metal) - PWR1
1-System and signal power supply Us+
2-Actuator Power supply Ua-
3-System and signal power supply Us-
4-Actuator Power supply Ua+
5-PE-Protective grounding PE



DH Bus B-code socket (Metal) - BUS1
1-Power supply 24V+
2-Data signal A
3-Data signal B
4-Power supply GND
5-ADR 1

M12 Input/Output



Digital signal interface M12 A-code socket (Green)
1-Power supply 24V+
2-Digital Input/Output B
3-Power supply GND
4-Digital Input/Output A
5-Protective grounding PE

Analog/Temperature signal interface M12 A-code socket (Green)
1- a-
2- A-
3- NC
4- A+
5- NC

Fieldbus interface module

CE RoHS

Features

- Advanced diagnostic function
- Fieldbus and Power adopt isolation technology and are reliable
- Supports 2 chain path; Max. 32 modules(16×2)
- Standalone configuration file
- Support DH BUS extension

PROFINET-RT PROTOCOL

Ordering Data		
Order No.	DFH67-PN-DI12P-DHB2	DFH67-PN-DI12N-DHB2
Description	PROFINET-RT protocol 6*A-Code 12DI , PNP type 2*B-Code DH BUS interface	PROFINET-RT protocol 6*A-Code 12DI , NPN type 2*B-Code DH BUS interface

Fieldbus	
Protocol	PROFINET-RT
Operation mode	Automatic negotiation ; Auto MDI/MDIX
Transmission speed	10/100 Mbps
IP allocation	Programming software configuration, or allocation by master

Power Supply	
Working voltage	24 VDC (18…30 VDC)
Current consumption	Max. 200 mA
System and Input	Us , Max. 8A
Actuators	Ua , Max. 8A
DH Bus interface power supply	Current of each DH Bus interface : Max. 4A
Electrical isolation	Module/Input power supply Ui and Output power supply Uo : 24V isolated , 0V connected

Interface Type	
Power supply	2 * M12 L-code 5pinPlug(input) + Socket(output)
Fieldbus	2 * M12 D-code 4pin , Socket
Signal	6 * M12 A-code 5pin , Socket
DH Bus interface	2 * M12 B-code 5pin , Socket
Number of DH Bus modules	Max. 32 (16 × 2)
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m

DEGSON Fieldbus High performance IP67 I/O

Fieldbus interface module CE RoHS

Ordering Data		
Order No.	DFH67-PN-DI12P-DHB2	DFH67-PN-DI12N-DHB2

Electrical Parameters		
Number and type of I/O	12DI PNP	12DI NPN
Input power supply current	Per channel : Max. 200mA	
Input filter time	Max. 10ms	

Diagnostic	
Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication
Extension	LED indication

General Data	
Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

Fieldbus interface module

CE RoHS

EtherCAT PROTOCOL

Features

- Advanced diagnostic function
- Fieldbus and Power adopt isolation technology and are reliable
- Supports 2 chain path; Max. 32 modules(16×2)
- Standalone configuration file
- Support DH BUS extension

Ordering Data

Order No.	DFH67-EC-DI12P-DHB2	DFH67-EC-DI12N-DHB2
Description	EtherCAT protocol 6*A-Code 12DI , PNP type 2*B-Code DH BUS interface	EtherCAT protocol 6*A-Code 12DI , NPN type 2*B-Code DH BUS interface

Fieldbus

Protocol	EtherCAT
Operation mode	Automatic negotiation ; Auto MDI/MDIX
Transmission speed	10/100 Mbps
IP allocation	System automatic allocation or DIP switch setting

Power Supply

Working voltage	24 VDC (18…30 VDC)
Current consumption	Max. 200 mA
System and Input	Us，Max. 8A
Actuators	Ua，Max. 8A
DH Bus interface power supply	Current of each DH Bus interface : Max. 4A
Electrical isolation	Module/Input power supply Ui and Output power supply Uo : 24V isolated，0V connected

Interface Type

Power supply	2 * M12 L-code 5pinPlug(input) + Socket(output)
Fieldbus	2 * M12 D-code 4pin，Socket
Signal	6 * M12 A-code 5pin，Socket
DH Bus interface	2 * M12 B-code 5pin，Socket
Number of DH Bus modules	Max. 32 (16 × 2)
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m

DEGSON Fieldbus High performance IP67 I/O

Fieldbus interface module CE RoHS

Ordering Data

Order No.	DFH67-EC-DI12P-DHB2	DFH67-EC-DI12N-DHB2

Electrical Parameters

Number and type of I/O	12DI PNP	12DI NPN
Input power supply current	Per channel : Max. 200mA	
Input filter time	Max. 1.6ms	

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication
Extension	LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

Fieldbus interface module

CE RoHS

CC-Link IE Field Basic PROTOCOL

Features

- Advanced diagnostic function
- Fieldbus and Power adopt isolation technology and are reliable
- Supports 2 chain path; Max. 32 modules(16×2)
- Support DH BUS extension
- Input or Output configurable

Ordering Data

Order No.	DFH67-CLI-DIO12P-DHB2	DFH67-CLI-DIO12N-DHB2
Description	CC-Link IE Field Basic protocol 6*A-Code 12DI/DO(configurable) , PNP type 2*B-Code DH BUS interface	CC-Link IE Field Basic protocol 6*A-Code 12DI/DO(configurable) , NPN type 2*B-Code DH BUS interface

Fieldbus

Protocol	CC-Link IE Field Basic
Operation mode	Automatic negotiation ; Auto MDI/MDIX
Transmission speed	10/100 Mbps
IP allocation	Web server configuration or DIP switch setting

Power Supply

Working voltage	24 VDC (18…30 VDC)
Current consumption	Max. 200 mA
System and Input	Us，Max. 8A
Actuators	Ua，Max. 8A
DH Bus interface power supply	Current of each DH Bus interface : Max. 4A
Electrical isolation	Module/Input power supply Ui and Output power supply Uo : 24V isolated，0V connected

Interface Type

Power supply	2 * M12 L-code 5pinPlug(input) + Socket(output)
Fieldbus	2 * M12 D-code 4pin，Socket
Signal	6 * M12 A-code 5pin，Socket
DH Bus interface	2 * M12 B-code 5pin，Socket
Number of DH Bus modules	Max. 32 (16 × 2)
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m

DEGSON Fieldbus High performance IP67 I/O

Fieldbus interface module CE RoHS

Ordering Data

Order No.	DFH67-CLI-DIO12P-DHB2	DFH67-CLI-DIO12N-DHB2

Electrical Parameters

Number and type of I/O	12DI/DO(configurable) , PNP type	12DI/DO(configurable) , NPN type
Input power supply current	Per channel : Max. 200mA	
Input filter time	Max. 10ms	

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication
Extension	LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

Fieldbus interface module

CE RoHS

EtherNet/IP PROTOCOL

Features

- Advanced diagnostic function
- Fieldbus and Power adopt isolation technology and are reliable
- Supports 2 chain path; Max. 32 modules(16×2)
- Standalone configuration file
- Support DH BUS extension
- Input or Output configurable

Ordering Data		
Order No.	DFH67-EIP-DIO12P-DHB2	DFH67-EIP-DIO12N-DHB2
Description	EtherNet/IP protocol 6*A-Code 12DI/DO(configurable) , PNP type 2*B-Code DH BUS interface	EtherNet/IP protocol 6*A-Code 12DI/DO(configurable) , NPN type 2*B-Code DH BUS interface
Fieldbus		
Protocol	EtherNet/IP	
Operation mode	Automatic negotiation ; Auto MDI/MDIX	
Transmission speed	10/100 Mbps	
IP allocation	Web server configuration or DIP switch setting	
Power Supply		
Working voltage	24 VDC (18...30 VDC)	
Current consumption	Max. 200 mA	
System and Input	Us , Max. 8A	
Actuators	Ua , Max. 8A	
DH Bus interface power supply	Current of single chain path : Max. 4A	
Electrical isolation	Module/Input power supply Ui and Output power supply Uo : 24V isolated , 0V connected	
Interface Type		
Power supply	2 * M12 L-code 5pinPlug(input) + Socket(output)	
Fieldbus	2 * M12 D-code 4pin , Socket	
Signal	6 * M12 A-code 5pin , Socket	
DH Bus interface	2 * M12 B-code 5pin , Socket	
Number of DH Bus modules	Max. 32 (16 × 2)	
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m	

DEGSON Fieldbus High performance IP67 I/O

Fieldbus interface module CE RoHS

Ordering Data		
Order No.	DFH67-EIP-DIO12P-DHB2	DFH67-EIP-DIO12N-DHB2
Electrical Parameters		
Number and type of I/O	12DI/DO(configurable) , PNP type	12DI/DO(configurable) , NPN type
Input power supply current	Per channel : Max. 200mA	
Input filter time	Max. 20ms	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
Extension	LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

Fieldbus interface module

CE RoHS

Modbus-TCP PROTOCOL

Features

- Advanced diagnostic function
- Fieldbus and Power adopt isolation technology and are reliable
- Supports 2 chain path; Max. 32 modules(16×2)
- Standalone configuration file
- Support DH BUS extension
- Input or Output configurable

Ordering Data		
Order No.	DFH67-MT-DIO12P-DHB2	DFH67-MT-DIO12N-DHB2
Description	Modbus-TCP protocol 6*A-Code 12DI/DO(configurable) , PNP type 2*B-Code DH BUS interface	Modbus-TCP protocol 6*A-Code 12DI/DO(configurable) , NPN type 2*B-Code DH BUS interface
Fieldbus		
Protocol	Modbus-TCP	
Operation mode	Automatic negotiation ; Auto MDI/MDIX	
Transmission speed	10/100 Mbps	
IP allocation	Web server configuration or DIP switch setting	
Power Supply		
Working voltage	24 VDC (18...30 VDC)	
Current consumption	Max. 200 mA	
System and Input	Us , Max. 8A	
Actuators	Ua , Max. 8A	
DH Bus interface power supply	Current of single chain path : Max. 4A	
Electrical isolation	Module/Input power supply Ui and Output power supply Uo : 24V isolated , 0V connected	
Interface Type		
Power supply	2 * M12 L-code 5pinPlug(input) + Socket(output)	
Fieldbus	2 * M12 D-code 4pin , Socket	
Signal	6 * M12 A-code 5pin , Socket	
DH Bus interface	2 * M12 B-code 5pin , Socket	
Number of DH Bus modules	Max. 32 (16 × 2)	
Extension distance of DH Bus	Single chain pasth: Max. 120m; Between adjacent modules: Max. 15m	

DEGSON Fieldbus High performance IP67 I/O

Fieldbus interface module CE RoHS

Ordering Data		
Order No.	DFH67-MT-DIO12P-DHB2	DFH67-MT-DIO12N-DHB2
Electrical Parameters		
Number and type of I/O	12DI/DO(configurable) , PNP type	12DI/DO(configurable) , NPN type
Input power supply current	Per channel : Max. 200mA	
Input filter time	Max. 20ms	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
Extension	LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

Fieldbus interface module

CE RoHS

Dimension



Power supply interface



Power supply L-code plug (Metal) - PWR1
1-System and signal power supply Us+
2-Actuator Power supply Ua-
3-System and signal power supply Us-
4-Actuator Power supply Ua+
5-PE-Protective grounding PE



Power supply L-code socket (Metal) - PWR2

Fieldbus & DH BUS interface



Fieldbus interface D-code socket(Metal) - ETH1/ETH2
1-Transmitter Tx+
2-Receiver Rx+
3-Transmitter Tx-
4-Receiver Rx-



DH Bus B-code socket (Black) - D01/D02
1-Power supply 24V+
2-Data signal A
3-Data signal B
4-Power supply GND
5-ADR 1

I/O signal interface



I/O signal interface M12 A-code socket (Green)
1-Power supply 24V+
2-Digital Input/Output B
3-Power supply GND
4-Digital Input/Output A
5-Protective grounding PE

DH BUS extension module

CE RoHS

16 digital inputs module

Features

- Input/Output photoelectric isolation
- Hardware filtering time 500us
- Output photoelectric isolation
- Overvoltage and short circuit protection function
- DH BUS and Channel adopt isolation technology and are reliable

Ordering Data

Order No.	DFH67-DHB-DI16P-M12	DFH67-DHB-DI16N-M12
Description	16DI , PNP , 8*M12	16DI , NPN , 8*M12

Interface Type

DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)
Power	DH Bus interface includes power supply
Signal	8 * M12 A-code 5pin , Socket

Electrical Parameters

Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	16	
Input power supply current	Per channel : Max. 200mA	
Input signal type	PNP type Sensors, Limit switch, Contact, etc	NPN type Sensors, Limit switch, Contact, etc
Input filter time	Max. 2ms	
Number of outputs	/	
Output current	/	
Output signal type	/	
Output switch frequency	/	

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

DH BUS extension module

CE RoHS



Features

- Input/Output photoelectric isolation
- Hardware filtering time 500us
- Output photoelectric isolation
- Overvoltage and short circuit protection function
- DH BUS and Channel adopt isolation technology and are reliable

16 digital outputs module

Ordering Data		
Order No.	DFH67-DHB-DO16P-M12	DFH67-DHB-DO16N-M12
Description	16DO，PNP，8*M12	16DO，NPN，8*M12
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M12 A-code 5pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	/	
Input power supply current	/	
Input signal type	/	
Input filter time	/	
Number of outputs	16	
Output current	Per channel : Max. 0.5A	
Output signal type	PNP type, actuator, Indicator, etc	NPN type, actuator, Indicator, etc
Output switch frequency	Resistive load : 100Hz, Inductive load : 5Hz	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DH BUS extension module

CE RoHS

Features

- Input/Output photoelectric isolation
- Hardware filtering time 500us
- Output photoelectric isolation
- Overvoltage and short circuit protection function
- DH BUS and Channel adopt isolation technology and are reliable

8 digital inputs + 8 digital outputs module

Ordering Data		
Order No.	DFH67-DHB-DI8P-DO8P-M12	DFH67-DHB-DI8N-DO8N-M12
Description	8DI+8DO,PNP,8*M12	8DI+8DO,NPN,8*M12
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M12 A-code 5pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	8	
Input power supply current	Per channel : Max. 200mA	
Input signal type	PNP type Sensors, Limit switch, Contact, etc	NPN type Sensors, Limit switch, Contact, etc
Input filter time	Max. 2ms	
Number of outputs	8	
Output current	Per channel : Max. 0.5A	
Output signal type	PNP type, actuator, Indicator, etc	NPN type, actuator, Indicator, etc
Output switch frequency	Resistive load : 100Hz, Inductive load : 5Hz	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DH BUS extension module

CE RoHS

Features

- Input photoelectric isolation
- Hardware filtering time 500us
- Overvoltage and short circuit protection function
- DH BUS and Channel adopt isolation technology and are reliable

8 digital inputs module

Ordering Data		
Order No.	DFH67-DHB-DI8P-M08	DFH67-DHB-DI8N-M08
Description	8DI , PNP , 8*M8	8DI , NPN , 8*M8
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M8 A-code 3pin , Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	8	
Input power supply current	Per channel : Max. 200mA	
Input signal type	PNP type Sensors, Limit switch, Contact, etc	NPN type Sensors, Limit switch, Contact, etc
Input filter time	Max. 2ms	
Number of outputs	/	
Output current	/	
Output signal type	/	
Output switch frequency	/	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DEGSON Fieldbus High performance IP67 I/O

DH BUS extension module

CE RoHS

Features

- Input photoelectric isolation
- Hardware filtering time 500us
- Overvoltage and short circuit protection function
- DH BUS and Channel adopt isolation technology and are reliable

8 digital outputs module

Ordering Data		
Order No.	DFH67-DHB-DO8P-M08	DFH67-DHB-DO8N-M08
Description	8DO , PNP , 8*M8	8DO , NPN , 8*M8
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M8 A-code 3pin , Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	/	
Input power supply current	/	
Input signal type	/	
Input filter time	/	
Number of outputs	8	
Output current	Per channel : Max. 0.5A , Total : Max. 4A	
Output signal type	NPN type, actuator, Indicator, etc	
Output switch frequency	Resistive load : 100Hz, Inductive load : 5Hz	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DH BUS extension module

CE RoHS

Features

- Input photoelectric isolation
- Hardware filtering time 500us
- Overvoltage and short circuit protection function
- DH BUS and Channel adopt isolation technology and are reliable

4 digital inputs + 4 digital outputs module

Ordering Data		
Order No.	DFH67-DHB-DI4P-DO4P-M08	DFH67-DHB-DI4N-DO4N-M08
Description	4DI+4DO,PNP,8*M8	4DI+4DO,NPN,8*M8
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M8 A-code 3pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	4	
Input power supply current	Per channel : Max. 200mA	
Input signal type	PNP type Sensors, Limit switch, Contact, etc	NPN type Sensors, Limit switch, Contact, etc
Input filter time	Max. 2ms	
Number of outputs	4	
Output current	Per channel : Max. 0.5A , Total : Max. 4A	
Output signal type	PNP type, actuator, Indicator, etc	NPN type, actuator, Indicator, etc
Output switch frequency	Resistive load : 100Hz, Inductive load : 5Hz	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DH BUS extension module

CE RoHS

Features

- Input/Output photoelectric isolation
- Hardware filtering time 500us
- Input or Output configurable
- Overvoltage and short circuit protection function
- DH BUS and Channel adopt isolation technology and are reliable

16 configurable digital I/O module

Ordering Data		
Order No.	DFH67-DHB-DIO16P-M12	DFH67-DHB-DIO16N-M12
Description	16 DI/DO，PNP，8*M12	16 DI/DO，NPN，8*M12
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M12 A-code 5pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	Max. 16	
Input power supply current	Per channel : Max. 200mA	
Input signal type	PNP type Sensors, Limit switch, Contact, etc	NPN type Sensors, Limit switch, Contact, etc
Input filter time	Max. 2ms	
Number of outputs	Max. 16	
Output current	Per channel : Max. 0.5A , Total : Max. 4A	
Output signal type	PNP type, actuator, Indicator, etc	NPN type, actuator, Indicator, etc
Output switch frequency	Resistive load : 100Hz, Inductive load : 5Hz	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DH BUS extension module

CE RoHS

Features

- Rich variety and wide application range
- The measure range configured through XML file, more flexible
- DH BUS and Channel adopt isolation technology and are reliable

Analog input module

Ordering Data				
Order No.	DFH67-DHB-AI4I-M12	DFH67-DHB-AI8I-M12	DFH67-DHB-AI4U-M12	DFH67-DHB-AI8U-M12
Description	4AI（Current type），16 bit，4*M12	8AI（Current type），16 bit，8*M12	4AI（Voltage type），16 bit，4*M12	8AI（Voltage type），16 bit，8*M12
Interface Type				
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)			
Power	DH Bus interface includes power supply			
Signal	4 * M12 A-code 5pin，Socket	8 * M12 A-code 5pin，Socket	4 * M12 A-code 5pin，Socket	8 * M12 A-code 5pin，Socket
Electrical Parameters				
Supply voltage	24 VDC (18…30V)			
Current consumption	Max. 50mA			
Number of inputs	4	8	4	8
Input power supply current	Per channel : Max. 200mA			
Input signal type	0...20mA , 4...20mA , ±20mA		0...10V , ±10V	
Input impedance	250Ω		1MΩ	
Resolution	16 Bit			
Conversion time	Max. 300us			
Precision	± 0.3%			
Diagnostic				
Communication status	LED indication, Communication message			
Power supply	Yes, Low voltage alarm			
Short circuit/Overload	Yes, LED indication			
General Data				
Degree of protection	IP67			
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C			
Installation	2-hole fixing			

DH BUS extension module

CE RoHS

Features

- Resolution : 16 bit
- The measure range configured through XML file, more flexible
- DH BUS and Channel adopt isolation technology and are reliable

8 channel analog output module

Ordering Data			
Order No.	DFH67-DHB-AO4I-AO4U-M12	DFH67-DHB- AO8I-M12	DFH67-DHB-AO8U-M12
Description	4AO(Current type)+4AO(Voltage type),16 bit,8*M12	8AO(Current type),16 bit,8*M12	8AO(Voltage type),16 bit,8*M12
Interface Type			
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)		
Power	DH Bus interface includes power supply		
Signal	8 * M12 A-code 5pin，Socket		
Electrical Parameters			
Supply voltage	24 VDC (18…30V)		
Current consumption	Max. 50mA		
Number of outputs	8		
Output signal type	First 4 channels（0…20mA,4…20mA） Last 4 channels（0…10V,±10V）	0…20mA，4…20mA	0…10V，±10V
Output impedance	Current type :<500Ω; Voltage type :>1kΩ	< 450Ω	> 1kΩ
Resolution	16 Bit		
Conversion time	Max. 300us		
Precision	± 0.3%		
Diagnostic			
Communication status	LED indication, Communication message		
Power supply	Yes, Low voltage alarm		
Short circuit/Overload	Yes, LED indication		
General Data			
Degree of protection	IP67		
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C		
Installation	2-hole fixing		

DH BUS extension module

CE RoHS

Features

- Resolution : 16 bit
- The measure range configured through XML file, more flexible
- DH BUS and Channel adopt isolation technology and are reliable

4 channel analog output module

Ordering Data		
Order No.	DFH67-DHB-AO4I-M12	DFH67-DHB-AO4U-M12
Description	4AO(Current type),16 bit,4*M12	4AO(Voltage type),16 bit,4*M12
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M12 A-code 5pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of outputs	4	
Output signal type	0…20mA，4…20mA	0…10V，±10V
Output impedance	< 450Ω	> 1kΩ
Resolution	16 Bit	
Conversion time	Max. 300us	
Precision	± 0.3%	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DH BUS extension module

CE RoHS

Features

- Resolution : 16 bit
- The measure range configured through XML file, more flexible
- DH BUS and Channel adopt isolation technology and are reliable

4 analog inputs + 4 analog outputs module

Ordering Data		
Order No.	DFH67-DHB-AI4I-AO4I-M12	DFH67-DHB-AI4U-AO4U-M12
Description	4AI+4AO(Current type),16 bit,8*M12	4AI+4AO(Voltage type),16 bit,8*M12
Interface Type		
DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)	
Power	DH Bus interface includes power supply	
Signal	8 * M12 A-code 5pin，Socket	
Electrical Parameters		
Supply voltage	24 VDC (18…30V)	
Current consumption	Max. 50mA	
Number of inputs	4	4
Input signal type	0…20mA，4…20mA，±20mA	0…10V，±10V
Input impedance	250Ω	1MΩ
Number of outputs	4	4
Output signal type	0…20mA，4…20mA	0…10V，±10V
Output impedance	< 450Ω	> 1kΩ
Resolution	16 bit	
Conversion time	Max. 300us	
Precision	± 0.3%	
Diagnostic		
Communication status	LED indication, Communication message	
Power supply	Yes, Low voltage alarm	
Short circuit/Overload	Yes, LED indication	
General Data		
Degree of protection	IP67	
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C	
Installation	2-hole fixing	

DH BUS extension module

CE RoHS



Features

- Resolution : 16 bit
- The measure range configured through XML file, more flexible
- Advanced filtering algorithm for more stable sampling
- DH BUS and Channel adopt isolation technology and are reliable

Temperature measuring module

Ordering Data

Order No.	DFH67-DHB-RTD4-M12	DFH67-DHB-RTD8-M12	DFH67-DHB-TC4-M12 Planned model	DFH67-DHB-TC8-M12 Planned model
Description	4RTD , Thermal resistance , 16 bit , 4*M12	8RTD , Thermal resistance , 16 bit , 8*M12	4TC , Thermocouple, 16 bit , 4*M12	8TC , Thermocouple, 16 bit , 8*M12

Interface Type

DH Bus	2 * M12 B-code 5pin Plug(input) + Socket(output)			
Power	DH Bus interface includes power supply			
Signal	4 * M12 A-code 5pin，Socket	8 * M12 A-code 5pin，Socket	4 * M12 A-code 5pin，Socket	8 * M12 A-code 5pin，Socket

Electrical Parameters

Supply voltage	24 VDC (18…30V)			
Current consumption	Max. 50mA			
Number of inputs	4	8	4	8
Input power supply current	Per channel : Max. 200mA			
Input signal type	Pt 100，Pt1000，Ni100， Ni1000， 0~150/300/600/3000 Ω		B,E,J,K,N,R,S,T Type	
Resolution	16 Bit			
Conversion time	Max. 300us			
Precision	± 0.3%			

Diagnostic

Communication status	LED indication, Communication message
Power supply	Yes, Low voltage alarm
Short circuit/Overload	Yes, LED indication

General Data

Degree of protection	IP67
Temperature range	Operation temperature : -20~60 °C ; Storage temperature : -40~85 °C
Installation	2-hole fixing

DH BUS extension module

CE RoHS

Dimension



DH Bus interface



DH Bus B-code plug (Metal) - BUS1
1-Power supply 24V+
2-Data signal A
3-Data signal B
4-Power supply GND
5-ADR 1



DH Bus B-code socket (Metal) - BUS2
1-Power supply 24V+
2-Data signal A
3-Data signal B
4-Power supply GND
5-ADR 1

M12 Input/Output



Digital signal interface M12 A-code socket (Green)
1-Power supply 24V+
2-Digital Input/Output B
3-Power supply GND
4-Digital Input/Output A
5-Protective grounding PE



Analog/Temperature signal interface M12 A-code socket (Green)
1- a-
2- A-
3- NC
4- A+
5- NC

M8 Input/Output



DI/DO signal interface M8 A-code socket (Green)
1-Power supply 24V+
3-Power supply GND
4-Digital Input/Output

Upper control - Fieldbus module Cable



A-end			B-end			Cable		Order NO.
Connect Target	Style	Shape	Connect Target	Style	Shape	Material	Length	
Power connection at the power supply end	Wire	/	Fieldbus module Power input interface M12 L-code 5pin plug	M12 L-code 5pin socket	Straight	PVC	3m 5m 10m 15m 20m	PM-M12L-05P-FF-SL7C03-00Z(H) PM-M12L-05P-FF-SL7C05-00Z(H) PM-M12L-05P-FF-SL7C10-00Z(H) PM-M12L-05P-FF-SL7C15-00Z(H) PM-M12L-05P-FF-SL7C20-00Z(H)
					Angled		3m 5m 10m 15m 20m	PM-M12L-05P-FF-SR7C03-00Z(H) PM-M12L-05P-FF-SR7C05-00Z(H) PM-M12L-05P-FF-SR7C10-00Z(H) PM-M12L-05P-FF-SR7C15-00Z(H) PM-M12L-05P-FF-SR7C20-00Z(H)
					Straight	PUR	3m 5m 10m 15m 20m	PM-M12L-05P-FF-SL7D03-00Z(H) PM-M12L-05P-FF-SL7D05-00Z(H) PM-M12L-05P-FF-SL7D10-00Z(H) PM-M12L-05P-FF-SL7D15-00Z(H) PM-M12L-05P-FF-SL7D20-00Z(H)
					Angled		3m 5m 10m 15m 20m	PM-M12L-05P-FF-SR7D03-00Z(H) PM-M12L-05P-FF-SR7D05-00Z(H) PM-M12L-05P-FF-SR7D10-00Z(H) PM-M12L-05P-FF-SR7D15-00Z(H) PM-M12L-05P-FF-SR7D20-00Z(H)
Network interface	RJ45	Straight	Fieldbus module Fieldbus interface M12 D-code 4pin socket	M12 D-code 4pin plug	Straight	PVC Shielded	3m 5m 10m 15m 20m	PMSH-M12D-04P-MM-SL8E03-RJ45 PMSH-M12D-04P-MM-SL8E05-RJ45 PMSH-M12D-04P-MM-SL8E10-RJ45 PMSH-M12D-04P-MM-SL8E15-RJ45 PMSH-M12D-04P-MM-SL8E20-RJ45
					Angled		3m 5m 10m 15m 20m	PMSH-M12D-04P-MM-SR8E03-RJ45 PMSH-M12D-04P-MM-SR8E05-RJ45 PMSH-M12D-04P-MM-SR8E10-RJ45 PMSH-M12D-04P-MM-SR8E15-RJ45 PMSH-M12D-04P-MM-SR8E20-RJ45
					Straight	PUR Shielded	3m 5m 10m 15m 20m	PMSH-M12D-04P-MM-SL8F03-RJ45 PMSH-M12D-04P-MM-SL8F05-RJ45 PMSH-M12D-04P-MM-SL8F10-RJ45 PMSH-M12D-04P-MM-SL8F15-RJ45 PMSH-M12D-04P-MM-SL8F20-RJ45
					Angled		3m 5m 10m 15m 20m	PMSH-M12D-04P-MM-SR8F03-RJ45 PMSH-M12D-04P-MM-SR8F05-RJ45 PMSH-M12D-04P-MM-SR8F10-RJ45 PMSH-M12D-04P-MM-SR8F15-RJ45 PMSH-M12D-04P-MM-SR8F20-RJ45

Note 1: L-code angled cables have a long lead time and should be carefully purchased
Note 2: Other lengths of cables are not in regular stock. If necessary, please contact sales personnel

Fieldbus module - Fieldbus module Cable



A-end			B-end			Cable		Order NO.
Connect Target	Style	Shape	Connect Target	Style	Shape	Material	Length	
Fieldbus module Power input interface M12 L-code 5pin socket	M12 L-code 5pin plug	Straight	Fieldbus module Power input interface M12 L-code 5pin plug	M12 L-code 5pin socket	Straight	PVC	3m 5m 10m 15m 20m	PM-M12L-05P-FL-ML-7C01-00Z(H) PM-M12L-05P-FL-ML-7C02-00Z(H) PM-M12L-05P-FL-ML-7C03-00Z(H) PM-M12L-05P-FL-ML-7C05-00Z(H) PM-M12L-05P-FL-ML-7C10-00Z(H)
		Angled			Angled		3m 5m 10m 15m 20m	PM-M12L-05P-FR-MR-7C01-00Z(H) PM-M12L-05P-FR-MR-7C02-00Z(H) PM-M12L-05P-FR-MR-7C03-00Z(H) PM-M12L-05P-FR-MR-7C05-00Z(H) PM-M12L-05P-FR-MR-7C10-00Z(H)
		Straight			Straight	PUR	3m 5m 10m 15m 20m	PM-M12L-05P-FL-ML-7D01-00Z(H) PM-M12L-05P-FL-ML-7D02-00Z(H) PM-M12L-05P-FL-ML-7D03-00Z(H) PM-M12L-05P-FL-ML-7D05-00Z(H) PM-M12L-05P-FL-ML-7D10-00Z(H)
		Angled			Angled		3m 5m 10m 15m 20m	PM-M12L-05P-FR-MR-7D01-00Z(H) PM-M12L-05P-FR-MR-7D02-00Z(H) PM-M12L-05P-FR-MR-7D03-00Z(H) PM-M12L-05P-FR-MR-7D05-00Z(H) PM-M12L-05P-FR-MR-7D10-00Z(H)
Fieldbus module Fieldbus interface M12 D-code 4pin socket	M12 D-code 4pin plug	Straight	Fieldbus module Fieldbus interface M12 D-code 4pin socket	M12 D-code 4pin plug	Straight	PVC Shielded	3m 5m 10m 15m 20m	PMSH-M12D-04P-ML-ML-8E01-00Z(H) PMSH-M12D-04P-ML-ML-8E02-00Z(H) PMSH-M12D-04P-ML-ML-8E03-00Z(H) PMSH-M12D-04P-ML-ML-8E05-00Z(H) PMSH-M12D-04P-ML-ML-8E10-00Z(H)
		Angled			Angled		3m 5m 10m 15m 20m	PMSH-M12D-04P-MR-MR-8E01-00Z(H) PMSH-M12D-04P-MR-MR-8E02-00Z(H) PMSH-M12D-04P-MR-MR-8E03-00Z(H) PMSH-M12D-04P-MR-MR-8E05-00Z(H) PMSH-M12D-04P-MR-MR-8E10-00Z(H)
		Straight			Straight	PUR Shielded	3m 5m 10m 15m 20m	PMSH-M12D-04P-ML-ML-8F01-00Z(H) PMSH-M12D-04P-ML-ML-8F02-00Z(H) PMSH-M12D-04P-ML-ML-8F03-00Z(H) PMSH-M12D-04P-ML-ML-8F05-00Z(H) PMSH-M12D-04P-ML-ML-8F10-00Z(H)
		Angled			Angled		3m 5m 10m 15m 20m	PMSH-M12D-04P-MR-MR-8F01-00Z(H) PMSH-M12D-04P-MR-MR-8F02-00Z(H) PMSH-M12D-04P-MR-MR-8F03-00Z(H) PMSH-M12D-04P-MR-MR-8F05-00Z(H) PMSH-M12D-04P-MR-MR-8F10-00Z(H)

Note 1: L-code angled cables have a long lead time and should be carefully purchased
Note 2: Other lengths of cables are not in regular stock. If necessary, please contact sales personnel

Fieldbus module - IO-Link device Cable



A-end			B-end			Cable		Order NO.
Connect Target	Style	Shape	Connect Target	Style	Shape	Material	Length	
Fieldbus module IO-Link interface M12 A-code 5pin socket	M12 A-code 5pin plug	Straight	IO-Link module IO-Link interface M12 A-code 4pin plug	M12 A-code 5pin socket (Pin5 None)	Straight	PVC	0.3m 0.5m 1m 2m 3m 5m 10m	PM-M12A-05P-FL-ML-8C-300-00Z(H) PM-M12A-05P-FL-ML-8C-500-00Z(H) PM-M12A-05P-FL-ML-8C01-00Z(H) PM-M12A-05P-FL-ML-8C02-00Z(H) PM-M12A-05P-FL-ML-8C03-00Z(H) PM-M12A-05P-FL-ML-8C05-00Z(H) PM-M12A-05P-FL-ML-8C10-00Z(H)
		Angled			Angled		0.3m 0.5m 1m 2m 3m 5m 10m	PM-M12A-05P-FR-MR-8C-300-00Z(H) PM-M12A-05P-FR-MR-8C-500-00Z(H) PM-M12A-05P-FR-MR-8C01-00Z(H) PM-M12A-05P-FR-MR-8C02-00Z(H) PM-M12A-05P-FR-MR-8C03-00Z(H) PM-M12A-05P-FR-MR-8C05-00Z(H) PM-M12A-05P-FR-MR-8C10-00Z(H)
		Straight			Straight	PUR	0.3m 0.5m 1m 2m 3m 5m 10m	PM-M12A-05P-FL-ML-8D-300-00Z(H) PM-M12A-05P-FL-ML-8D-500-00Z(H) PM-M12A-05P-FL-ML-8D01-00Z(H) PM-M12A-05P-FL-ML-8D02-00Z(H) PM-M12A-05P-FL-ML-8D03-00Z(H) PM-M12A-05P-FL-ML-8D05-00Z(H) PM-M12A-05P-FL-ML-8D10-00Z(H)
		Angled			Angled		0.3m 0.5m 1m 2m 3m 5m 10m	PM-M12A-05P-FR-MR-8D-300-00Z(H) PM-M12A-05P-FR-MR-8D-500-00Z(H) PM-M12A-05P-FR-MR-8D01-00Z(H) PM-M12A-05P-FR-MR-8D02-00Z(H) PM-M12A-05P-FR-MR-8D03-00Z(H) PM-M12A-05P-FR-MR-8D05-00Z(H) PM-M12A-05P-FR-MR-8D10-00Z(H)

Note 1: If the IO-Link module requires L-code cables (Power supply), the selection is the same as that of Fieldbus module
Note 2: If the IO-Link module requires B-code cables (DH Bus), the selection is the same as that of DH Bus module
Note 3: Other lengths of cables are not in regular stock. If necessary, please contact sales personnel

DH Bus cable



A-end			B-end			Cable		Order NO.
Connect Target	Style	Shape	Connect Target	Style	Shape	Material	Length	
Fieldbus module DH Bus interface M12 B-code 5pin socket	M12 B-code 5pin plug	Straight	DH Bus module DH Bus interface M12 B-code 5pin plug	M12 B-code 5pin socket	Straight	PVC Shielded	0.3m 0.5m 1m 2m 3m 5m 10m	PMSH-M12B-05P-FL-ML-7P-300-00Z(H) PMSH-M12B-05P-FL-ML-7P-500-00Z(H) PMSH-M12B-05P-FL-ML-7P01-00Z(H) PMSH-M12B-05P-FL-ML-7P02-00Z(H) PMSH-M12B-05P-FL-ML-7P03-00Z(H) PMSH-M12B-05P-FL-ML-7P05-00Z(H) PMSH-M12B-05P-FL-ML-7P10-00Z(H)
		Angled			Angled		0.3m 0.5m 1m 2m 3m 5m 10m	PMSH-M12B-05P-FR-MR-7P-300-00Z(H) PMSH-M12B-05P-FR-MR-7P-500-00Z(H) PMSH-M12B-05P-FR-MR-7P01-00Z(H) PMSH-M12B-05P-FR-MR-7P02-00Z(H) PMSH-M12B-05P-FR-MR-7P03-00Z(H) PMSH-M12B-05P-FR-MR-7P05-00Z(H) PMSH-M12B-05P-FR-MR-7P10-00Z(H)
DH Bus module DH Bus interface M12 B-code 5pin socket	M12 B-code 5pin plug	Straight	DH Bus module DH Bus interface M12 B-code 5pin plug	M12 B-code 5pin socket	Straight	PVC Shielded	0.3m 0.5m 1m 2m 3m 5m 10m	PMSH-M12B-05P-FL-ML-7P-300-00Z(H) PMSH-M12B-05P-FL-ML-7P-500-00Z(H) PMSH-M12B-05P-FL-ML-7P01-00Z(H) PMSH-M12B-05P-FL-ML-7P02-00Z(H) PMSH-M12B-05P-FL-ML-7P03-00Z(H) PMSH-M12B-05P-FL-ML-7P05-00Z(H) PMSH-M12B-05P-FL-ML-7P10-00Z(H)
		Angled			Angled		0.3m 0.5m 1m 2m 3m 5m 10m	PMSH-M12B-05P-FR-MR-7P-300-00Z(H) PMSH-M12B-05P-FR-MR-7P-500-00Z(H) PMSH-M12B-05P-FR-MR-7P01-00Z(H) PMSH-M12B-05P-FR-MR-7P02-00Z(H) PMSH-M12B-05P-FR-MR-7P03-00Z(H) PMSH-M12B-05P-FR-MR-7P05-00Z(H) PMSH-M12B-05P-FR-MR-7P10-00Z(H)

Sensor / Actuator Cable



A-end			B-end			Cable		Order NO.
Connect Target	Style	Style	Connect Target	Style	Style	Material	Length	
M12 A-code interface 5pin socket	M12 A-code 5pin plug	Straight	Sensor / Actuator	Wire	Straight	PVC	1m 2m 3m 5m 10m	PM-M12A-05P-MM-SL8C01-00Z(H) PM-M12A-05P-MM-SL8C02-00Z(H) PM-M12A-05P-MM-SL8C03-00Z(H) PM-M12A-05P-MM-SL8C05-00Z(H) PM-M12A-05P-MM-SL8C10-00Z(H)
		Angled			Angled		1m 2m 3m 5m 10m	PM-M12A-05P-MM-SR8C01-00Z(H) PM-M12A-05P-MM-SR8C02-00Z(H) PM-M12A-05P-MM-SR8C03-00Z(H) PM-M12A-05P-MM-SR8C05-00Z(H) PM-M12A-05P-MM-SR8C10-00Z(H)
M8 A-code interface 3pin socket	M8 A-code 3pin plug	Straight	Sensor / Actuator	Wire	Straight	PVC	1m 2m 3m 5m 10m	PM-M8A-03P-MM-SL7C01-00Z(H) PM-M8A-03P-MM-SL7C02-00Z(H) PM-M8A-03P-MM-SL7C03-00Z(H) PM-M8A-03P-MM-SL7C05-00Z(H) PM-M8A-03P-MM-SL7C10-00Z(H)
		Angled			Angled		1m 2m 3m 5m 10m	PM-M8A-03P-MM-SR7C01-00Z(H) PM-M8A-03P-MM-SR7C02-00Z(H) PM-M8A-03P-MM-SR7C03-00Z(H) PM-M8A-03P-MM-SR7C05-00Z(H) PM-M8A-03P-MM-SR7C10-00Z(H)

Note : Other lengths of cables are not in regular stock. If necessary, please contact sales personnel

DH Bus accessories

Picture	
Description	DH Bus auxiliary power supply unit
Order NO.	DF-YB01-M12-SB5/PB5/PL5
Style	M12 B-code 5pin socket M12 B-code 5pin plug M12 L-code 5pin plug
Voltage/Current	24V / 4A
Rated voltage	60V
Pulse voltage	2500V
Protection degrees	IP67 / IP68
Notes	When the power supply is insufficient, increase the maximum 4A power supply

Picture	
Description	Termination resistor
Order NO.	DFH67-DHB-T
Style	M12 B-code 5pin plug
Resistance value	Pin4 / Pin5 = 120Ω
Protection degrees	IP67 / IP68





Accessories

Picture			
Description	M12 L-code 5pin T-type distributor	M12 A-code 5pin Y-type distributor	M12 A-code - M8 A-code Y-type distributor
Order NO.	DF-TB-M12-PL5/SL5/SL5	FY-M12A-05F-M12A-05M-Q-0100	FY-M12A-04M-M8A-03F-T-0100
Voltage/Current	24V / 4A	24V / 4A	24V / 3A
Style	Plug / Socket / Socket	Plug / Socket / Socket	M12 4pin Plug / M8 3pin Socket / M8 3pin Socket
Shielding	Unshielded	Unshielded	Unshielded
Diagram			

Description	Order NO.	MOQ	Picture
M12 Plug Cover	DF-PLUGCOVER-M12	10	
M12 Socket Cover	DF-SOCKETCOVER-M12	10	
M8 Socket Cover	DF-SOCKETCOVER-M08	10	

DSW series unmanaged switch

- Wide range working temperature: -40℃ ~ 70℃
- Wide range working voltage: DC9.6~60V & AC18~30V
- High strength cast aluminum shell, greatly improving EMC electromagnetic compatibility and heat dissipation performance, vibration and impact resistance
- High data exchange performance, backplane bandwidth: 16Gbps; MAC address table size: 4K; Package cache area: 1.5Mb
- BSP Broadcast storm suppression function improves network stability
- QoS priority function ensures priority forwarding of high demand data packets

DSW series unmanaged switch

CE RoHS

HOT

DSW-A3K

DSW-A5K

DSW-A8K

Features

- Industrial-grade Chip.
- 10/100/1000 BaseT(X)(RJ45 connector) .
- Compact size for easy installation.
- Broadcast storm protection (BSP),the Quality of Service (QoS) function.
- Die-casting aluminum alloy housing.
- IP30 protection class.
- -40 to 75°C wide operating temperature range.

Specifications

Type	DSW-A5K0005	DSW-A8K0008	DSW-A3K1020	DSW-A5K0050	DSW-A8K0080	DSW-A5K0104	DSW-A8K0206	DSW-A8K0107
Ports	5 BaseT ports	8 BaseT ports	1BaseX SFP port 2 BaseT ports	5 BaseT ports	8 BaseT ports	1 BaseX SFP port 4 BaseT ports	2 BaseX SFP port 6 BaseT ports	1 BaseX SFP port 7 BaseT ports
Bandwidth	100M	100M	1000M	1000M	1000M	100M	100M	100M

Switch Properties

Processing Type	Store-and-Forward
Backplane Bandwidth	16Gbps (Max)
MAC Table Size	4K (Max)
Packet Buffer Size	1.5Mb (Max)

DIP Switch Configuration

	Quality of Service (QoS), Broadcast Storm Protection (BSP)
	Ethernet Interface

Power Parameters

Connection	1 removable 2-contact terminal block
Input Voltage	12/24/48 VDC & 24 VAC
Operating Voltage	9.6~60 VDC & 18~30 VAC
Overload Current Protection	Supported
Reverse Polarity Protection	Supported

Physical Characteristics

Installation	DIN-rail mounting
Housing	Die-casting aluminum alloy housing
(W×H×D) Dimensions	MTX100-A3K/-A5K: 24mm x 100mm x 61.8mm MTX100-A8K: 40mm x 100mm x 61.8mm
Weight	0.23Kg (Max)
Power Consumption	5W(Max)

Environment Limits

Ambient Relative Humidity	5 to 95% (non-condensing)
Operating Temperature	- 40°C~ 75°C
Storage Temperature	- 40°C~ 85°C

Standards and Certifications

Safety	IEC/EN62368-1
UL	UL61010
EMC	EN55032 EN55035

DSW series unmanaged switch CE RoHS

Overall Dimensions

DSW-A3K/A5K



DSW-A8K



Accessories

Picture	Product	Transmission rate	Transfer mode	Matching model
	DSW-SFP-01-S-20	10/100Mbs	Single mode	DSW-A5K0104 DSW-A8K0107 DSW-A8K0206
	DSW-SFP-10-S-20	100/1000Mbs	Single mode	DSW-A3K1020

DSW series unmanaged switch

CE RoHS

DSW-A16K000G

Features

- Industrial-grade Chips
- Small size, and easy to install
- Support QoS (IEEE 802.1P/1Q and TOS/DiffServ)
- Die-cast aluminum alloy shell
- IP30 protection grade
- Redundant dual input power supply design
- -40 to 75°C wide operating temperature range
- Support DIP sound and light alarm output and 1 relay alarm port (1A@24VDC)

Specifications

Type	DSW-A16K000G
Ports	16 16 BaseT ports
Bandwidth	100M

Switch Properties

Processing Type	Store-and-Forward
Backplane Bandwidth	8.8Gbps (Max)
MAC Table Size	8K (Max)
Packet Buffer Size	4Mb (Max)

DIP Switch Configuration

DIP Switch Function	QoS (Quality of Service), BSP (Broadcast Storm Protection), Power Alarm, Port Alarm, Alarm Buzzer

Power Parameters

Connection	1 removable 6-contact terminal block
Input Voltage	12/24/48 VDC & 24 VAC, redundant dual input
Operating Voltage	9.6~60 VDC & 18~30 VAC
Overload Current Protection	Supported
Reverse Polarity Protection	Supported
Power Consumption	<10W

Physical Characteristics

Installation	DIN-rail mounting
Housing	Die-casting aluminum alloy housing
IP Grade	IP30
(W×H×D) Dimensions	52mmx140mmx110mm
Weight	<1.2 kg

Environment Limits

Ambient Relative Humidity	5 to 95% (non-condensing)
Operating Temperature	-40°C~ 75°C
Storage Temperature	-40°C~ 85°C

Standards and Certifications

Safety	IEC/EN62368-1
UL	UL61010
EMC	EN55032 EN55035

DSW series unmanaged switch

CE RoHS

Overall Dimensions

DSW-A16K000G



Accessories

Picture	Product	Transmission rate	Transfer mode	Matching model
/	/	/	/	/
/	/	/	/	/

DSW series unmanaged switch

CE RoHS

DSW-A6K2040P

DSW-A10K2080P

Features

- Full Gigabit Ethernet ports.
- 20Gbps backplane bandwidth.
- Support IEEE 802.3af/at compliant PoE.
- Each PoE port provides up to 30W output power
- PoE management: PoE device detection, PoE power management.
- Dual redundant power inputs design for DC models.
- IP40 Die-casting aluminum alloy housing.
- Fanless, -40 to 75°C wide operating temperature range.
- MTBF≥400,000 hours.

Specifications

Type	DSW-A6K2040P	DSW-A10K2080P
Ports	2 BaseX SFP port, 4 BaseT ports	2 BaseX SFP port, 8 BaseT ports
Bandwidth	1000M	1000M

Switch Properties

Processing Type	Store-and-Forward
Backplane Bandwidth	20Gbps (Max)
MAC Table Size	4K (Max)
Exchange Rate	1, 488, 000 pps / 1000M ports

Power Parameters

Connection	1 removable 5-contact terminal block
Input Voltage	DSW-A6K/A10K: 48-57VDC, Redundant dual inputs
Overload Current Protection	Supported
Reverse Polarity Protection	Supported

Physical Characteristics

Installation	DIN-rail mounting, Wall mounting
Housing	Die-casting aluminum alloy housing
Protection level	IP30
(W×H×D) Dimensions	52mmx140mmx110mm
Weight	0.7 kg
MTBF	≥400 , 000H

Environment Limits

Ambient Relative Humidity	5 to 95% (non-condensing)
Operating Temperature	- 40°C~ 75°C
Storage Temperature	- 40°C~ 85°C

Electromagnetic Characteristics

EMI	FCC 47 CFR Part 15 Class A EN55022 Class A

Standards and Certifications

Safety	FCC Part 15 Subpart B Class A	IEC/EN55022 Class A IEC60825-1
Industrial Control Industry	UL/cUL61010	
Power Industry	IEC61850-3 IEEE1613 (C37.90.x)	

DSW series unmanaged switch

CE RoHS

Overall Dimensions

DSW-A6K2040P



DSW-A10K2080P



Accessories

Picture	Product	Transmission rate	Transfer mode	Matching model
	DSW-SFP-10-S-20	100/1000Mbs	Single mode	DSW-A6K2040P DSW-A10K2080P
/	/	/	/	/

DSW series RJ45 network port EtherCAT protocol switch

CE RoHS

DSW-ECT-A4K0004

DSW-ECT-A6K0006

Features

- 4-port / 6-port 100 Mbit RJ45 interface, 10M/100M adaptive
- Metal housing, more suitable for harsh industrial environments
- Anti-electromagnetic interference, more stable communication transmission.
- Supports DC-distributed clock synchronization.
- Supports the cascading function and hot swap of network cables
- Flexible composition of a variety of topologies

Specifications

Type	DSW-ECT-A4K0004	DSW-ECT-A6K0006
Functions In The System	Coupling of EtherCAT connections	
Transmission Medium	Ethernet/EtherCAT cables (at least Category 5) shielded	
Network Interface	4*RJ45	6*RJ45
Network Protocol	EtherCAT	
Support for distributed clocks	Yes	
Delayed	Approximately 1 microsecond per port	
Transmission Speed	100M	

Power Parameters

Connection	1 removable 3-contact terminal block
Input Voltage	Rated 24VDC (allowed for 18-28VDC)
Overload Current Protection	Supported
Reverse Polarity Protection	Supported

Physical Characteristics

Installation	DIN35 rail installation	
Housing	Aluminum alloy housing	
Protection level	IP40	
（W×H×D） Dimensions	29×95×102(mm)	47×94×102(mm)

Environment Limits

Ambient Relative Humidity	5 to 90% (non-condensing)
Operating Temperature	-10°C~ 55°C

Electromagnetic Characteristics

EMI	FCC 47 CFR Part 15 Class A EN55032 Class A EN55035 Class A

Standards and Certifications

Safety	EN 62368-1

DSW series RJ45 network port EtherCAT protocol switch CE RoHS

Overall Dimensions

DSW-ECT-A4K0004



DSW-ECT-A6K0006



DSW series ST Optical fiber EtherCAT protocol switches

CE RoHS

DSW-ECT-A4K0202-S-STA

DSW-ECT-A4K0202-S-STB

Features

- 4-port (2 optical and 2 electrical) branch with ST port and built-in optical module
- Metal housing, more suitable for harsh industrial environments
- Anti-electromagnetic interference, more stable communication transmission.
- Supports DC-distributed clock synchronization.
- Supports the cascading function and hot swap of network cables
- Flexible composition of a variety of topologies

Specifications

Type	DSW-ECT-A4K0202-S-STA	DSW-ECT-A4K0202-S-STB
Functions In The System	Coupling of EtherCAT connections	
Transmission Medium	Ethernet/EtherCAT cables (at least Category 5) shielded	
Network Interface	2*RJ45，2*ST	
Network Protocol	EtherCAT	
Support for distributed clocks	Yes	
Delayed	Approximately 1 microsecond per port	
Transmission Speed	100M	
Power Parameters		
Connection	1 removable 3-contact terminal block	
Input Voltage	Rated 24VDC (allowed for 18-28VDC)	
Overload Current Protection	Supported	
Reverse Polarity Protection	Supported	
Physical Characteristics		
Installation	DIN35 rail installation	
Housing	Aluminum alloy housing	
Protection level	IP40	
Dimensions	29×95×102(mm)	
Environment Limits		
Ambient Relative Humidity	5 to 90% (non-condensing)	
Operating Temperature	-10°C~ 55°C	
Electromagnetic Characteristics		
EMI	FCC 47 CFR Part 15 Class A EN55032 Class A EN55035 Class A	
Standards and Certifications		
Safety	EN 62368-1	

DSW series ST Optical fiber EtherCAT protocol switches CE RoHS

Overall Dimensions

DSW-ECT-A4K0202-S-STA DSW-ECT-A4K0202-S-STB



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-04-P-00	JB-M8-04-N-00
Functional description	Split Plastic box, 4 channels, single signal, PNP	Split Plastic box, 4 channels, single signal, NPN

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	4	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	10…30VDC
Supply current MAX	Max 4A
Interface type	M12 Male Acode 8P IEC 61076-2-101
Torque	0.4Nm(3.54Lb-In)
Interface material	Copper alloy
Thread material	Ni

Product	JB-M8-04-P-00	JB-M8-04-N-00
Functional description	Split Plastic box, 4 channels, single signal, PNP	Split Plastic box, 4 channels, single signal, NPN

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

Mechanical Structure

Protection grade	IP67
size(L X W X H)	86.6mm X 30.6mm X 27mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box

CE RoHS

Cable				
Product	PM-M12A-08P-FF-SL8A02-00A(H)	PM-M12A-08P-FF-SL8B02-00A(H)	PM-M12A-08P-FF-SR8A02-00A(H)	PM-M12A-08P-FF-SR8B02-00A(H)
Shell material	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Straight, PVC, 2m	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Straight, PUR, 2m	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Angled, PVC, 2m	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Angled, PUR, 2m
Cable				
M12 Connector Pin drawing	 M12 Female Acode 8P		NO. / Color / NO. / Color 1 / White(WH) / 5 / Grey(GY) 2 / Brown(BN) / 6 / Pink(PK) 3 / Green(GN) / 7 / Blue(BU) 4 / Yellow(YE) / 8 / Red(RD)	
M8 Pin drawing	 M8 Female Acode 3P			
Junction Box drawing				
Wiring diagram	JB-M8-04-P-00 1 Un 3 0 V 4 Signal  M8 Female Acode 3P		JB-M8-04-N-00 1 Un 3 0 V 4 Signal  M8 Female Acode 3P	

JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-06-P-00	JB-M8-06-N-00
Functional description	Split Plastic box, 6 channels, single signal, PNP	Split Plastic box, 6 channels, single signal, PNP

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	6	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	10…30VDC
Supply current MAX	Max 4A
Interface type	M12 Male Acode 8P IEC 61076-2-101
Torque	0.4Nm(3.54Lb-In)
Interface material	Copper alloy
Thread material	Ni

Product	JB-M8-06-P-00	JB-M8-06-N-00
Functional description	Split Plastic box, 6 channels, single signal, PNP	Split Plastic box, 6 channels, single signal, PNP

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

Mechanical Structure

Protection grade	IP67
size(L X W X H)	106.6mm X 30.6mm X 27mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box

CE RoHS

Cable				
Product	PM-M12A-08P-FF-SL8A02-00A(H)	PM-M12A-08P-FF-SL8B02-00A(H)	PM-M12A-08P-FF-SR8A02-00A(H)	PM-M12A-08P-FF-SR8B02-00A(H)
Shell material	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Straight, PVC, 2m	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Straight, PUR, 2m	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Angled, PVC, 2m	M12 * 1 Female Overmolded with Cable Plug, 8P, single end, Unshielded, Angled, PUR, 2m
Cable				
M12 Connector Pin drawing	 M12 Female Acode 8P		NO. / Color / NO. / Color 1 / White(WH) / 5 / Grey(GY) 2 / Brown(BN) / 6 / Pink(PK) 3 / Green(GN) / 7 / Blue(BU) 4 / Yellow(YE) / 8 / Red(RD)	
M8 Pin drawing	 M8 Female Acode 3P			
Junction Box drawing	 			
Wiring diagram	JB-M8-06-P-00  1 Un 3 0 V 4 Signal M8 Female Acode 3P		JB-M8-06-N-00  1 Un 3 0 V 4 Signal M8 Female Acode 3P	

JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-08-P-00	JB-M8-08-N-00
Functional description	Split Plastic box, 8 channels, single signal, PNP	Split Plastic box, 8 channels, single signal, NPN

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	8	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	10…30VDC
Supply current MAX	Max 4A
Interface type	M12 Male Acode 12P IEC 61076-2-101
Torque	0.4Nm(3.54Lb-In)
Interface material	Copper alloy
Thread material	Ni

Product	JB-M8-08-P-00	JB-M8-08-N-00
Functional description	Split Plastic box, 8 channels, single signal, PNP	Split Plastic box, 8 channels, single signal, NPN

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

Mechanical Structure

Protection grade	IP67
size(L X W X H)	126.6mm X 30.6mm X 27mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box

CE RoHS

Cable				
Product	PM-M12A-12P-FF-SL8A03-00A(H)	PM-M12A-12P-FF-SL8B03-00A(H)	PM-M12A-12P-FF-SR8A03-00A(H)	PM-M12A-12P-FF-SR8B03-00A(H)
Shell material	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Straight, PVC, 3m	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Straight, PUR, 3m	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Angled, PVC, 3m	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Angled, PUR, 3m
Cable				
M12 Connector Pin drawing	 M12 Female Acode 12P			

NO.	Color	NO.	Color
1	Brown(BN)	7	Black (BK)
2	Blue(BU)	8	Grey(GY)
3	White(WH)	9	Red(RD)
4	Green(GN)	10	Violet(VT)
5	Pink(PK)	11	Grey/Pink(GY/PK)
6	Yellow(YE)	12	Red/Blue(RD/BU)

M8 Pin drawing



M8 Female Acode 3P

Junction Box drawing



Wiring diagram





JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-10-P-00	JB-M8-10-N-00
Functional description	Split Plastic box, 10 channels, single signal, PNP	Split Plastic box, 10 channels, single signal, PNP

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	10	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	10…30VDC
Supply current MAX	Max 4A
Interface type	M12 Male Acode 12P IEC 61076-2-101
Torque	0.4Nm(3.54Lb-In)
Interface material	Copper alloy
Thread material	Ni

Product	JB-M8-10-P-00	JB-M8-10-N-00
Functional description	Split Plastic box, 10 channels, single signal, PNP	Split Plastic box, 10 channels, single signal, PNP

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

Mechanical Structure

Protection grade	IP67
size(L X W X H)	146.6mm X 30.6mm X 27mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box

CE RoHS

Cable				
Product	PM-M12A-12P-FF-SL8A02-00A(H)	PM-M12A-12P-FF-SL8B02-00A(H)	PM-M12A-12P-FF-SR8A02-00A(H)	PM-M12A-12P-FF-SR8B02-00A(H)
Shell material	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Straight, PVC, 3m	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Straight, PUR, 3m	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Angled, PVC, 3m	M12 * 1 Female Overmolded with Cable Plug, 12P, single end, Unshielded, Angled, PUR, 3m
Cable				
M12 Connector Pin drawing	 M12 Female Acode 12P			

NO.	Color	NO.	Color
1	Brown(BN)	7	Black (BK)
2	Blue(BU)	8	Grey(GY)
3	White(WH)	9	Red(RD)
4	Green(GN)	10	Violet(VT)
5	Pink(PK)	11	Grey/Pink(GY/PK)
6	Yellow(YE)	12	Red/Blue(RD/BU)

M8 Pin drawing



M8 Female Acode 3P

Junction Box drawing



Wiring diagram

JB-M8-10-P-00



1	Un
3	0 V
4	Signal

M8 Female Acode 3P

JB-M8-10-N-00



1	Un
3	0 V
4	Signal

M8 Female Acode 3P

JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-04-P-A03-00	JB-M8-04-N-A03-00
Functional description	Pre-injected cable, plastic box, 4 channels, single signal, PNP, PVC, 3m	Pre-injected cable, plastic box, 4 channels, single signal, NPN, PVC, 3m

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	4	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	
Cable material	PUR/PP, 5 million times	
Cable length	3m	

Power Supply Parameters

Supply voltage	10…30VDC
Supply current MAX	Max 4A

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	86.6mm X 30.6mm X 18mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M8 Pin drawing



M8 Female Acode 3P

Junction Box drawing



Wiring diagram





JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-06-P-A03-00	JB-M8-06-N-A03-00
Functional description	Pre-injected cable, plastic box, 6 channels, single signal, PNP, PVC, 3m	Pre-injected cable, plastic box, 6 channels, single signal, NPN, PVC, 3m

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	6	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	
Cable material	PUR/PP, 5 million times	
Cable length	3m	

Power Supply Parameters

Supply voltage	10…30VDC
Supply current MAX	Max 4A

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	106.6mm X 30.6mm X 18mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M8 Pin drawing



M8 Female Acode 3P

Junction Box drawing



Wiring diagram

1	Un
3	0 V
4	Signal

JB-M8-06-P-A03-00

M8 Female Acode 3P



1	Un
3	0 V
4	Signal

JB-M8-06-N-A03-00

M8 Female Acode 3P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-08-P-A03-00	JB-M8-08-N-A03-00
Functional description	Pre-injected cable, plastic box, 8 channels, single signal, PNP, PVC, 3m	Pre-injected cable, plastic box, 8 channels, single signal, NPN, PVC, 3m

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	8	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	
Cable material	PUR/PP, 5 million times	
Cable length	3m	

Power Supply Parameters

Supply voltage	10...30VDC
Supply current MAX	Max 4A

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	126.6mm X 30.6mm X 18mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M8 Pin drawing



M8 Female Acode 3P

Junction Box drawing



Wiring diagram

JB-M8-08-P-A03-00

1	Un
3	0 V
4	Signal

M8 Female Acode 3P



JB-M8-08-N-A03-00

1	Un
3	0 V
4	Signal

M8 Female Acode 3P



JB Series Junction Box

CE RoHS



Features

- Small size, easy to install.
- You can select PNP, NPN according to the function mode of the controller.
- There is LED indicator light, you can see the working status of the product.
- IP67 level of protection.
- You can can customize the material and length of the cable.

Product

Product	JB-M8-10-P-A03-00	JB-M8-10-N-A03-00
Functional description	Pre-injected cable, plastic box, 10 channels, single signal, PNP, PVC, 3m	Pre-injected cable, plastic box, 10 channels, single signal, NPN, PVC, 3m

Performance Parameter

Signal type	PNP	NPN
Number of I/O channels	10	
Number of signal output points	1	
Shell material	PBT	
Contact material	Copper alloy	
Contact surface material	Au	
Contact material	PA	
Contact resistance	<10mΩ	
Cable material	PUR/PP, 5 million times	
Cable length	3m	

Power Supply Parameters

Supply voltage	10…30VDC
Supply current MAX	Max 4A

I/O Parameters

Rated voltage	24VDC
Rated current	1.5A
Interface type	M8 Female Acode 3P IEC 61076-2-104
Torque	0.2Nm(1.77Lb-In)
Interface material	Copper alloy
Thread material	Ni

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	146.6mm X 30.6mm X 18mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M8 Pin drawing



M8 Female Acode 3P

Junction Box drawing



Wiring diagram

1	Un
3	0 V
4	Signal

JB-M8-10-P-A03-00

M8 Female Acode 3P



1	Un
3	0 V
4	Signal

JB-M8-10-N-A03-00

M8 Female Acode 3P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.
- You can can customize the material and length of the cable.

Product

Product	JB-M12-04-P-A03-01	JB-M12-04-2P-A03-01
Functional description	Split Plastic box, 4 channels, PNP, with cable, PVC, 3m	

Performance Parameter

Signal type	PNP	
Number of I/O channels	4	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18...30VDC
Supply current MAX	Max 6A
Interface type	Cable connection

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	103mm X 58mm X 22mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-04-P-A03-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-04-2P-A03-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.
- You can can customize the material and length of the cable.

Product

Product	JB-M12-06-P-A03-01	JB-M12-06-2P-A03-01
Functional description	Split Plastic box, 6 channels, PNP, with cable, PVC, 3m	

Performance Parameter

Signal type	PNP	
Number of I/O channels	6	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18...30VDC
Supply current MAX	Max 6A
Interface type	Cable connection

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	128mm X 58mm X 22mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-06-P-A03-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-06-2P-A03-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.
- You can can customize the material and length of the cable.

Product

Product	JB-M12-08-P-A03-01	JB-M12-08-2P-A03-01
Functional description	Split Plastic box, 8 channels, PNP, with cable, PVC, 3m	

Performance Parameter

Signal type	PNP	
Number of I/O channels	8	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18...30VDC
Supply current MAX	Max 6A
Interface type	Cable connection

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	153mm X 58mm X 22mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-08-P-A03-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-08-2P-A03-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.
- You can can customize the material and length of the cable.

Product

Product	JB-M12-10-P-A03-01	JB-M12-10-2P-A03-01
Functional description	Split Plastic box, 10 channels, PNP, with cable, PVC, 3m	

Performance Parameter

Signal type	PNP	
Number of I/O channels	10	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18…30VDC
Supply current MAX	Max 6A
Interface type	Cable connection

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	178mm X 58mm X 22mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-10-P-A03-01

1	24V
2	/
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-10-2P-A03-01

1	24V
2	/
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-04-P-01	JB-M12-04-2P-01
Functional description	Split Plastic box, 4 ports, single channels, PNP, with M23 prefabricated interface	

Performance Parameter

Signal type	PNP	
Number of I/O channels	4	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18...30VDC
Supply current MAX	Max 6A
Interface type	M23 interface
Torque	1.2Nm
Interface material	Cu Alloy
Thread material	Ni

Product	JB-M12-04-P-01	JB-M12-04-2P-01
Functional description	Split Plastic box, 4 ports, double channels, PNP, with M23 prefabricated interface	

I/O Parameters

Rated voltage	24VDC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	103mm X 58mm X 32.5mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box

CE RoHS

Cable		
Product	PCSH-M23P-07P-FF-1LM-SR7A03-01Z(H)	PCSH-M23P-11P-FF-2LM-SR7A03-01Z(H)
Shell material	M23 * 1 Female Overmolded with Cable Plug, 7P, single end, Unshielded, Angled, PVC, 3m	M23 * 1 Female Overmolded with Cable Plug, 11P, single end, Unshielded, Angled, PVC, 3m
Cable		
M23 Connector Pin drawing	 M23 Female Acode 7P	 M23 Female Acode 11P

Pin Assignment

NO.	Color	NO.	Color	NO.	Color	NO.	Color
1	/	12	Green/Yellow(GN/YE)	1	Violet(VT)	12	Green/Yellow(GN/YE)
2	/	15	White(WH)	2	Red(RD)	15	White(WH)
3	Grey(GY)	16	Yellow(YE)	3	Grey(GY)	16	Yellow(YE)
5	Green(GN)	17	/	5	Green(GN)	17	Pink(PK)
6	Blue(BU)	19	Brown(BU)	6	Blue(BU)	19	Brown(BU)
11	/			11	Black (BK)		

M12 Pin drawing

M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing





Wiring diagram

JB-M12-04-P-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-04-2P-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-06-P-01	JB-M12-06-2P-01
Functional description	Split Plastic box, 6 ports, single channels, PNP, with M23 prefabricated interface	

Performance Parameter

Signal type	PNP	
Number of I/O channels	6	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18…30VDC
Supply current MAX	Max 6A
Interface type	M23 interface
Torque	1.2Nm
Interface material	Cu Alloy
Thread material	Ni

Product	JB-M12-06-P-01	JB-M12-06-2P-01
Functional description	Split Plastic box, 6 ports, double channels, PNP, with M23 prefabricated interface	

I/O Parameters

Rated voltage	24VDC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	128mm X 58mm X 32.5mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box

CE RoHS

Cable		
Product	PCSH-M23P-09P-FF-1LM-SR7A03-01Z(H)	PCSH-M23P-15P-FF-2LM-SR7A03-01Z(H)
Shell material	M23 * 1 Female Overmolded with Cable Plug, 9P, single end, Unshielded, Angled, PVC, 3m	M23 * 1 Female Overmolded with Cable Plug, 15P, single end, Unshielded, Angled, PVC, 3m
Cable		
M23 Connector Pin drawing	 M23 Female Acode 9P	 M23 Female Acode 15P

Pin Assignment

NO.	Color	NO.	Color
1	/	11	/
2	Red(RD)	12	Yellow/Green(YE/GN)
3	Grey(GY)	14	/
4	/	15	White(WH)
5	Green(GN)	16	Yellow(YE)
6	Blue(BU)	17	Pink(PK)
7	/	19	Brown(BU)
8	/		

NO.	Color	NO.	Color
1	Violet(VT)	11	Black (BK)
2	Red(RD)	12	Yellow/Green(YE/GN)
3	Grey(GY)	14	Brown/Green(BN/GN)
4	Red/Blue(RD/BU)	15	White(WH)
5	Green(GN)	16	Yellow(YE)
6	Blue(BU)	17	Pink(PK)
7	Grey/Pink(GY/PK)	19	Brown(BU)
8	White/Green(WH/GN)		

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-06-P-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-06-2P-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-08-P-01	JB-M12-08-2P-01
Functional description	Split Plastic box, 8 ports, single channels, PNP, with M23 prefabricated interface	

Performance Parameter

Signal type	PNP	
Number of I/O channels	8	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18…30VDC
Supply current MAX	Max 6A
Interface type	M23 interface
Torque	1.2Nm
Interface material	Cu Alloy
Thread material	Ni

Product	JB-M12-08-P-01	JB-M12-08-2P-01
Functional description	Split Plastic box, 8 ports, double channels, PNP, with M23 prefabricated interface	

I/O Parameters

Rated voltage	24VDC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	153mm X 58mm X 32.5mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box

CE RoHS

Cable		
Product	PCSH-M23P-11P-FF-1LM-SR7A03-01Z(H)	PCSH-M23P-19P-FF-2LM-SR7A03-01Z(H)
Shell material	M23 * 1 Female Overmolded with Cable Plug, 11P, single end, Unshielded, Angled, PVC, 3m	M23 * 1 Female Overmolded with Cable Plug, 19P, single end, Unshielded, Angled, PVC, 3m
Cable		
M23 Connector Pin drawing	 M23 Female Acode 11P	 M23 Female Acode 19P

Pin Assignment

NO.	Color	NO.	Color
1	Violet(VT)	11	Black (BK)
2	Red(RD)	12	Yellow/Green(YE/GN)
3	Grey(GY)	13	/
4	/	14	/
5	Green(GN)	15	White(WH)
6	Blue(BU)	16	Yellow(YE)
7	/	17	Pink(PK)
8	/	18	/
9	/	19	Brown(BU)
10	/		

NO.	Color	NO.	Color
1	Violet(VT)	11	Black (BK)
2	Red(RD)	12	Yellow/Green(YE/GN)
3	Grey(GY)	13	Yellow/Brown(YE/BN)
4	Red/Blue(RD/BU)	14	Brown/Green(BN/GN)
5	Green(GN)	15	White(WH)
6	Blue(BU)	16	Yellow(YE)
7	Grey/Pink(GY/PK)	17	Pink(PK)
8	White/Green(WH/GN)	18	Brown/Grey(BN/GY)
9	White/Yellow(WH/YE)	19	Brown(BU)
10	White/Grey(WH/GY)		

M12 Pin drawing

M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-08-P-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-08-2P-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-10-P-01
Functional description	Split Plastic box, 10 ports, single channel, PNP, with M23 prefabricated interface

Performance Parameter

Signal type	PNP	
Number of I/O channels	10	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18…30VDC
Supply current MAX	Max 6A
Interface type	M23 interface
Torque	1.2Nm
Interface material	Cu Alloy
Thread material	Ni

I/O Parameters

Rated voltage	24VDC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	178mm X 58mm X 32.5mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

JB Series Junction Box
CE RoHS

Cable	
Product	PCSH-M23P-13P-FF-1LM-SR7A03-01Z(H)
Shell material	M23 * 1 Female Overmolded with Cable Plug, 13P, single end, Unshielded, Angled, PVC, 3m
Cable	
M23 Connector Pin drawing	 M23 Female Acode 13P

Pin Assignment

NO.	Color	NO.	Color
1	Violet(VT)	11	Black (BK)
2	Red(RD)	12	Yellow/Green(YE/GN)
3	Grey(GY)	15	White(WH)
4	Red/Blue(RD/BU)	16	Yellow(YE)
5	Green(GN)	17	Pink(PK)
6	Blue(BU)	19	Brown(BU)
7	Grey/Pink(GY/PK)		

M12 Pin drawing

M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-10-P-01

1	24V
2	signal
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS



Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-04B-P-01	JB-M12-04B-2P-01
Functional description	Split Plastic box, 4 ports, PNP, with pluggable terminal block	

Performance Parameter

Signal type	PNP	
Number of I/O channels	4	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18...30VDC
Supply current MAX	Max 8A
Interface type	PCB interface
Torque	0.6Nm
Interface material	PA flame retardant
Thread material	PC+ABS

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	124.5mm X 58mm X 44.4mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-04B-P-01

1	24V
2	NO
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-04B-2P-01

1	24V
2	NO
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-06B-P-01	JB-M12-06B-2P-01
Functional description	Split Plastic box, 6 ports, PNP, with pluggable terminal block	

Performance Parameter

Signal type	PNP	
Number of I/O channels	6	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18...30VDC
Supply current MAX	Max 8A
Interface type	PCB interface
Torque	0.6Nm
Interface material	PA flame retardant
Thread material	PC+ABS

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	149.5mm X 58mm X 44.4mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-06B-P-01

1	24V
2	NO
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-06B-2P-01

1	24V
2	NO
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-08B-P-01	JB-M12-08B-2P-01
Functional description	Split Plastic box, 8 ports, PNP, with pluggable terminal block	

Performance Parameter

Signal type	PNP	
Number of I/O channels	8	
Number of signal output points	1	2
Shell material	PA flame retardant	
Contact material	Cu Alloy	
Contact surface material	Au	
Contact material	PA flame retardant	
Contact resistance	<10mΩ	

Power Supply Parameters

Supply voltage	18…30VDC
Supply current MAX	Max 8A
Interface type	PCB interface
Torque	0.6Nm
Interface material	PA flame retardant
Thread material	PC+ABS

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	174.5mm X 58mm X 44.4mm

Work Environment

Working temperature	-25…80℃
Storage temperature	-25…80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-08B-P-01

1	24V
2	NO
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB-M12-08B-2P-01

1	24V
2	NO
3	0V
4	signal
5	PE

M12 Female Acode 5P



JB Series Junction Box

CE RoHS

Features

- Small size, easy to install.
- There is LED indicator light, you can see the working status of the product.
- Up to IP67 protection level.

Product

Product	JB-M12-10B-P-01
Functional description	Split Plastic box, 10 ports, PNP, with pluggable terminal block

Performance Parameter

Signal type	PNP
Number of I/O channels	10
Number of signal output points	1
Shell material	PA flame retardant
Contact material	Cu Alloy
Contact surface material	Au
Contact material	PA flame retardant
Contact resistance	<10mΩ

Power Supply Parameters

Supply voltage	18...30VDC
Supply current MAX	Max 8A
Interface type	PCB interface
Torque	0.6Nm
Interface material	PA flame retardant
Thread material	PC+ABS

I/O Parameters

Rated voltage	24VDC/AC
Rated current	4A
Interface type	M12*1.0 Female
Torque	0.8Nm
Interface material	PA flame retardant
Thread material	PC+ABS

JB Series Junction Box

CE RoHS

Mechanical Structure

Protection grade	IP67
size(L X W X H)	199.5mm X 58mm X 44.4mm

Work Environment

Working temperature	-25...80℃
Storage temperature	-25...80℃

LED Status Indicator

Power lamp	Green LED
I/O lamp	Yellow LED

Product Figure

M12 Pin drawing



M12 Female Acode 5P

Junction Box drawing



Wiring diagram

JB-M12-10B-P-01

1	24V
2	NO
3	0V
4	signal
5	PE

M12 Female Acode 5P



Appendices

CE RoHS

Product	Functional description	Picture	Dimensional drawing	Wiring diagram	Wiring list
PM-M8A-03P-MM-SL7A02-00A(H)	M12 * 1 Male Overmolded with Cable Plug, 3P, single end, Unshielded, Straight, PVC, 2m				1.BN 3.BU 4.BK
PM-M8A-03P-MM-SL7B02-00A(H)	M12 * 1 Male Overmolded with Cable Plug, 3P, single end, Unshielded, Straight, PUR, 2m				
PM-M8A-03P-MM-SR7A02-00A(H)	M12 * 1 Male Overmolded with Cable Plug, 3P, single end, Unshielded, Angled, PVC, 2m				1.BN 3.BU 4.BK
PM-M8A-03P-MM-SR7B02-00A(H)	M12 * 1 Male Overmolded with Cable Plug, 3P, single end, Unshielded, Angled, PUR, 2m				
PB-M8A-03P-MM-SL7001-00A(H)	M8 * 1 Male Field Assembly Plug, 3P, Unshielded, Screw Connection, Straight				/
PB-M8A-03P-FF-SL7001-00A(H)	M8 * 1 Female Field Assembly Plug, 3P, Unshielded, Screw Connection, Straight				/

Appendices

CE RoHS

Product	Functional description	Picture	Dimensional drawing	Wiring diagram	Wiring list
PB-M12A-08P-MM-SL7001-00A(H)	M12 * 1 Male Field Assembly Plug, 8P, Unshielded, Screw Connection, Straight				/
PB-M12A-08P-MM-SR7001-00A(H)	M12 * 1 Male Field Assembly Plug, 8P, Unshielded, Screw Connection, Angled				/
PA-M12A-12P-MM-SL7001-00A(H)	M12 * 1 Male Field Assembly Plug, 12P, Unshielded, Soldering Connection, Straight				/
PA-M12A-12P-MM-SR7001-00A(H)	M12 * 1 Male Field Assembly Plug, 12P, Unshielded, Soldering Connection, Angled				/
SD-M12A-08P-FF-SF8AB0-00A(H)	M12 * 1 Female Panel Mount Receptacle, 8P, Rear Mounting, With 2m wires				1.WH 2.BN 3.GN 4.YE 5.GY 6.PK 7.BU 8.RD
PA-M12A-12P-MM-SR7001-00A(H)	M12 * 1 Female Panel Mount Receptacle, 12P, Rear Mounting, With 2m wires				1.BN 2.BU 3.WH 4.GN 5.PK 6.YW 7.BK 8.GY 9.RD 10.VT 11.GY/PK 12.RD/BU