

概要

製品情報



Bus IO-DF750-003-11-2001A(H)-30050000131

Card type IO shell,DB9 connector,LED indicator

製品の特長

- ☒ One DB9 interface
- ☒ 8-bit address interface
- ☒ Internal bus through 6 gold-plated terminals at the bottom
- ☒ Equipped with 8 channels power module, each node is equipped with LED
- ☒ Two internal gold-plated blade connectors are used for power cascade expansion
- ☒ Can be installed on DIN rail

製品認証

技術データ

製品チャート

3Dモデル

□

Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping
label	Laser screen printing
color	C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
---------------------------------	-----------

Ambient temperature (storage / transport)

-40℃～+70℃

Connection method(IO)

wiring

Spring type wiring technology

Strip length

8-9mm

Power contacts

2 blade contacts

Power load

10A

Rated current

Power: 24V Bus connector: 5V

Cross section

0.2~2.5mm²

Connectable guide cross section AWG

28~12AWG

PCB thickness

1.0mm

Dimension

length

93.5mm

width

48mm

Height

69mm

アクセサリ

Accessories

IO housing

DF750-200-11-2001A(H)

ビジネスデータ

注文番号

30050000131

パッキングユニット

20

最小注文数量

20

1 個あたりの重量（梱包を
含めない）

122.5

