

概要

製品情報



Interface module-DM50-IDC-10-10-4Y-00A(H)-30040000056

IDC module,input/output module,with screw connector and IDC stitching line,can be installed on DIN35 rail,10 positions

製品の特長

10digits to 50digits
1:1 connection
Screw connection

製品認証

技術データ

製品チャート

3Dモデル

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	10
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	IDC connection
Connection volume	1
Number of digits	10
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	10
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	66mm
width	57mm

Height	44mm
--------	------

アクセサリ

Accessories

Wire harness	DX211-1S-500-00A(H)
--------------	---------------------

ビジネスデータ

注文番号	30040000056
パッキングユニット	6
最小注文数量	12
1 個あたりの重量（梱包を 含めない）	55