

概要

製品情報



Relay module-DM72-RMUS-16-PN-1-44-01A(H)-30030000102

Subminiature Relay Module, with relay Socket, 16 relays can be installed, with relay Socket, with indicator light, Honfa relay, PNP or NPN signal can be input

製品の特長

- ☒ Each signal channel and power supply voltage have LED status indicators
- ☒ Pluggable subminiature relay, with a set of normally open contacts, one-to-one output at the output
- ☒ Suitable for NPN, PNP controller
- ☒ Freewheeling diode for each signal path

製品認証

技術データ

製品チャート

3Dモデル

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
---------------------------------	------------------

Ambient temperature (storage / transport)	-20 °C ... 70 °C
---	------------------

Standards/Regulations

Standards/Regulations	IEC61810
-----------------------	----------

Pollution level	3
-----------------	---

Overvoltage category	III
----------------------	-----

Dimension

length	103mm
--------	-------

width	90mm
-------	------

Height	60mm
Overview	
Installation location	Arbitrary
Number of channels	16
Shell Insulation Materials	PVC/PA66
color	green

アクセサリ

ビジネスデータ	
注文番号	30030000102
パッキングユニット	1
最小注文数量	10
1 個あたりの重量（梱包を 含めない）	256