

概要

製品情報



40A-GM-2.5-92116000498

40A silver gold male pins,Adapter wire specification2.5mm²

製品の特長

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

製品認証

技術データ

製品チャート

3Dモデル

□

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm ²)	2.5mm ²
Conductor cross sections(AWG)	14AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	9mm
working life-mating cycles	≥500

アクセサリ

ビジネスデータ

注文番号	92116000498
パッキングユニット	100
最小注文数量	100
1 個あたりの重量（梱包を 含めない）	3.142