

概要

製品情報



5A-GF-0.52-92116900030

5A silver gold female pins,Adapter wire specification0.52mm²

製品の特長

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

製品認証

技術データ

製品チャート

3Dモデル

□

Marking

classification	Contact
Series	5A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Gold plate
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections（mm ² ）	0.52mm ²
Conductor cross sections(AWG)	20AWG
Working current	≤10A
Contact resistance	≤3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	8mm
working life-mating cycles	≥500

アクセサリ

ビジネスデータ

注文番号	92116900030
パッキングユニット	100
最小注文数量	100
1 個あたりの重量（梱包を 含めない）	0.241