

概要

製品情報



DME-005-MS-21020000132

Heavy-duty insert, Number of contacts: 5, Dimension: 1 module Spaces, Rated voltage : 400V, Rated current: 16A, Male insert, Cage clamp connector

製品の特長

- ☒ Spring cage connection technology, high vibration resistance;
- ☒ No special tools required, maintenance-free ;
- ☒ Less materials, easy to manage;
- ☒ Modular products, easy to assemble and maintain .

製品認証



技術データ

製品チャート

3Dモデル

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	1 module
Number of positions	5
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	400V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3/3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

アクセサリ

Accessories

Screwdriver	/
-------------	---

ビジネスデータ	
注文番号	21020000132
パッキングユニット	100
最小注文数量	5
1 個あたりの重量（梱包を 含めない）	17.1