


概要

製品情報



DMK-003-MC-21020000142

Heavy-duty insert, Number of contacts: 3, Dimension: 1 module Spaces, Rated voltage : 500V, Rated current: 40A, Male insert, Crimping connector

製品の特長

- ☒ Crimping connection technology, applicable to a wide range of wire specifications ;
- ☒ Modular products, easy to assemble and maintain .

製品認証



技術データ

製品チャート

3Dモデル

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Male
Dimension	1 module
Number of positions	3
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	40A
	500V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	1.5-10mm²
Conductor cross sections(AWG)	16-8AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

アクセサリ

Accessories

Crimping tool Removal tool	/
----------------------------	---

ビジネスデータ	
注文番号	21020000142
パッキングユニット	100
最小注文数量	5
1 個あたりの重量（梱包を 含めない）	13.5