


概要

製品情報



DMK7-002-F(6-16mm²)-21020000272

Heavy-duty insert, Number of contacts: 2, Dimension: 1 module Spaces, Rated voltage : 1000V, Rated current: 70A, Female insert, axial Screw connector

製品の特長

- ☑ Axial Screw connection technology, applicable to a wide range of wire specifications;
- ☑ Less materials, easy to manage;
- ☑ Modular products, easy to assemble and maintain .

製品認証



技術データ

製品チャート

3Dモデル

□

Marking

classification	Insert
Series	DM

versions

Connection method	Axial screw connection
Female/Male	Female
Dimension	1 module
Number of positions	2
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Material (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	70A
	1000V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.5mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Rated torque	2N.m(6mm²) 3N.m(10mm²) 4N.m(16mm²) 5N.m(22mm²)
Conductor cross sections (mm²)	6-16mm²
Conductor cross sections(AWG)	10-6AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

アクセサリ

Accessories

Screwdriver	/
-------------	---

ビジネスデータ	
注文番号	21020000272
パッキングユニット	100
最小注文数量	5
1 個あたりの重量（梱包を 含めない）	29.5