

概要

製品情報



D2MK-002-M(16-35mm²)-21020000259

Heavy-duty insert, Number of contacts: 2, Dimension: 2 module Spaces, Rated voltage : 1000V, Rated current: 100A, Male insert, axial Screw connector

製品の特長

- ☒ Axial Screw connection technology, applicable to a wide range of wire specifications;
- ☒ Less materials, easy to manage;
- ☒ Modular products, easy to assemble and maintain .

製品認証



技術データ

製品チャート

3Dモデル

□

Marking

classification	Insert
Series	DM

versions

Connection method	Axial screw connection
Female/Male	Male
Dimension	2 module
Number of positions	2
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	100A
	1000V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	13mm
Rated torque	8N.m(25/35mm²) 9N.m(50mm²) 10N.m(70mm²)
Conductor cross sections (mm²)	16-35mm²
Conductor cross sections(AWG)	6-2AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

アクセサリ

Accessories

SW 4 internal hexagonal wrench

/

ビジネスデータ

注文番号	21020000259
パッキングユニット	100
最小注文数量	5
1 個あたりの重量（梱包を 含めない）	80