

概要

製品情報



DK-8/0-M-21020000061

Heavy-duty insert, Number of contacts: 8/0+PE, Dimension: 24B, Rated voltage : 690V, Rated current: 100A, Male insert, axial Screw connector

製品の特長

- ☑ Axial Screw connection technology, applicable to a wide range of wire specifications;
- ☑ Less materials, easy to manage;
- ☑ With grounding protection。

製品認証



技術データ

製品チャート

3Dモデル

□

Marking

classification	Insert
Series	DK

versions

Connection method	Axial screw connection
Female/Male	Male
Dimension	24B
Number of positions	8/0
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	100A
	690V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.5mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	13mm
Rated torque	6N.m(10mm²) 6N.m(16mm²) 7N.m(25mm²)
Conductor cross sections (mm²)	10-25mm²
Conductor cross sections(AWG)	7-3AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

アクセサリ

Accessories

Screwdriver

/

ビジネスデータ

注文番号	21020000061
パッキングユニット	100
最小注文数量	5
1 個あたりの重量（梱包を 含めない）	304.44