


概要

製品情報



DK-4/0-F-21020000123

Heavy-duty insert, Number of contacts: 4/0+PE, Dimension: 16B, Rated voltage : 690V, Rated current: 80A, Female insert, Screw connector

製品の特長

- ☑ Screw connection technology, applicable to a wide range of wire specifications;
- ☑ No need special tools, easy to operate;
- ☑ Less materials, easy to manage;
- ☑ With grounding protection。

製品認証



技術データ

製品チャート

3Dモデル

□

Marking

classification	Insert
Series	DK

versions

Connection method	Screw connection
Female/Male	Female
Dimension	16B
Number of positions	4/0
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	80A
	690V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	14mm
Rated torque	1.2N.m(1.5mm²) 2N.m(2.5mm²) 3N.m(4/6/10/16mm²)
Conductor cross sections (mm²)	1.5-16mm²
Conductor cross sections(AWG)	16-6AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

アクセサリ

Accessories

Screwdriver

/

ビジネスデータ

注文番号	21020000123
パッキングユニット	100
最小注文数量	5
1 個あたりの重量（梱包を 含めない）	115