


概要

製品情報



DSB-012-M-21020000244

Heavy-duty insert, Number of contacts: 12+PE, Dimension: 32B, Rated voltage :500V, Rated current: 35A, Male insert, Screw connector

製品の特長

- ☑Screw connection technology, applicable to a wide range of wire specifications;
- ☑No need special tools, easy to operate;
- ☑Less materials, easy to manage;
- ☑With grounding protection。

製品認証



技術データ

製品チャート

3Dモデル

□

Marking

classification	Insert
Series	DSB

versions

Connection method	Screw connection
Female/Male	Male
Dimension	32B
Number of positions	12
PE Contacts	Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	35A
	500V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	7.5mm
Rated torque	1.2N.m
Conductor cross sections (mm²)	1.5-6mm²
Conductor cross sections(AWG)	16-10AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

アクセサリ

Accessories

Screwdriver

/

ビジネスデータ

注文番号	21020000244
パッキングユニット	100
最小注文数量	5
1 個あたりの重量（梱包を 含めない）	162