

## 概要

### 製品情報



## DA-004-FS-21020000102

Heavy-duty insert, Number of contacts: 4+PE, Dimension: 3A, Rated voltage : 400/230V, Rated current: 10A, Female insert, Cage clamp connector

### 製品の特長

- ☒ Spring cage connection technology, high vibration resistance;
- ☒ No special tools required, maintenance-free ;
- ☒ Less materials, easy to manage;
- ☒ With grounding protection。

### 製品認証



## 技術データ

### 製品チャート

### 3Dモデル

□

### Marking

|                |        |
|----------------|--------|
| classification | Insert |
| Series         | DA     |

### versions

|                     |                        |
|---------------------|------------------------|
| Connection method   | Spring cage connection |
| Female/Male         | Female                 |
| Dimension           | 3A                     |
| Number of positions | 4                      |
| PE Contacts         | Yes                    |

Material characteristics

|                     |                             |
|---------------------|-----------------------------|
| Material (insert)   | Polycarbonate (PC)          |
| Materia (Contact)   | Copper alloy                |
| Surface (Contact)   | Silver plated               |
| Flammability rating | V-0                         |
| color               | Grey/White (RAL 7032)       |
| RoHS                | Comply with RoHS exemptions |

Electrical parameters

|                                      |            |
|--------------------------------------|------------|
| Rated current                        | 10A        |
|                                      | 400/230V   |
| Rated pulse voltage                  | 4KV        |
| Pollution level                      | 3          |
| On the basis of UL /CSARated current | 600V       |
| Insulation resistance                | ≥10000MΩ   |
| Contact resistance                   | ≤1mΩ       |
| Temperature range                    | -40℃~+125℃ |
| working life-mating cycles           | ≥500 time  |
| Strip length                         | 9.0mm      |
| Conductor cross sections (mm²)       | 0.5-2.5mm² |
| Conductor cross sections(AWG)        | 20-14AWG   |

Standards

|                            |                           |
|----------------------------|---------------------------|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |
|----------------------------|---------------------------|

アクセサリ

Accessories

Screwdriver

/

ビジネスデータ

|                        |             |
|------------------------|-------------|
| 注文番号                   | 21020000102 |
| パッキングユニット              | 100         |
| 最小注文数量                 | 5           |
| 1 個あたりの重量（梱包を<br>含めない） | 15.33       |