


## 概要

### 製品情報



## WS2.5P-PE-11030000185

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, AWG: 28 - 12, Width: 5 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

### 製品の特長

- ☑spring-cage connection technology, good anti-vibration performance;
- ☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑Grounding structure, protection circuit;
- ☑Can be matched with marker strips to avoid incorrect insertion of wires.

### 製品認証



## 技術データ

### 製品チャート

### 3Dモデル

□

### Wiring data

|                                   |                        |
|-----------------------------------|------------------------|
| Strip length                      | 8~9mm                  |
| Conductor cross section solid     | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~14                  |

### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

## IEC Electrical parameters

Rated surge voltage

4KV

## Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

## Dimension

NS 35/7,5 Height

35.45mm

End plate width

2.5mm

NS 35/15 Height

42.95mm

length

53mm

width

5mm

Height

32.45mm

## Overview

Connection type

Pull back spring connection

Number of rows

1

number of connections

1

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94

V0

## アクセサリ

## Marker

Top marker

ZB5 / WB5

Side marker

DEK5

Marker support

DTH5-25×5 / DTH5-25×12

|               |        |
|---------------|--------|
| Warning cover | EEA2.5 |
|---------------|--------|

#### Accessories

|                                                    |          |
|----------------------------------------------------|----------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5  |
| Adjacent jumper (2P)                               | /        |
| Alternate jumper (2P)                              | /        |
| Staggered jumper (2P)                              | /        |
| End cover                                          | D-WS2.5P |

#### Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZB5   |
| Marker cards  | DBE-1 |

#### Accessories

|                |                      |
|----------------|----------------------|
| End cover      | D-WS2.5P             |
| Plug-in bridge | 8EDGK-5.0            |
| End clamp      | E-WS                 |
| DIN rail       | NS35/7.5-1000-00A(H) |

#### ビジネスデータ

|           |             |
|-----------|-------------|
| 注文番号      | 11030000185 |
| パッキングユニット | 100         |
| 最小注文数量    | 100         |

1 個あたりの重量（梱包を  
含めない）

9.18