


## 概要

### 製品情報



## WS1.5-QU-PE-11030000070

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 28 - 16, Width: 4 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

### 製品の特長

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Grounding structure, protection circuit;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### 製品認証



## 技術データ

### 製品チャート

### 3Dモデル

□

### Wiring data

|                                   |                        |
|-----------------------------------|------------------------|
| Strip length                      | 8~9mm                  |
| Conductor cross section solid     | 0.2~1.5mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~1.5mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~16                  |

### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

## IEC Electrical parameters

Rated surge voltage

8KV

## Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

## Dimension

NS 35/7,5 Height

34.55mm

End plate width

2.5mm

NS 35/15 Height

42.05mm

length

73mm

width

4mm

Height

31.55mm

## Overview

Connection type

Pull back spring connection

Number of rows

1

number of connections

4

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94

V0

## アクセサリ

## Marker

Top marker

ZB4 / WB4

Side marker

DEK4

Marker support

DTH3.5-25×3.5 / DTH3.5-25×12

|               |        |
|---------------|--------|
| Warning cover | EEA1.5 |
|---------------|--------|

#### Accessories

|                                                    |            |
|----------------------------------------------------|------------|
| Slotted screwdriver size (Blade thickness x Width) | 0.4×2.5    |
| Adjacent jumper (2P)                               | /          |
| Alternate jumper (2P)                              | /          |
| Staggered jumper (2P)                              | /          |
| End cover                                          | D-WS1.5-QU |

#### Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZB4   |
| Marker cards  | DBE-1 |

#### Accessories

|           |                      |
|-----------|----------------------|
| End cover | D-WS1.5-QU           |
| End clamp | E-WS                 |
| DIN rail  | NS35/7.5-1000-00A(H) |

#### ビジネスデータ

|                        |             |
|------------------------|-------------|
| 注文番号                   | 11030000070 |
| パッキングユニット              | 100         |
| 最小注文数量                 | 100         |
| 1 個あたりの重量（梱包を<br>含めない） | 10.425      |

