

概要

製品情報



PC10-PE-11010000006

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 10 mm², AWG: 20 - 6, Width: 10.2 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

製品の特長

- ☒ Screw connection technology, reliable connection;
- ☒ Grounding structure, protection circuit;
- ☒ Copper alloy material, good corrosion resistance;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Screw type	Slotted screw
Strip length	9~10mm
Conductor cross section solid	0.2~10mm ²
Conductor cross section flexible	0.2~10mm ²
Conductor cross section solid AWG	20~6
screw thread	M4
Tightening torque	1.2N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	47.25mm
NS 35/15 Height	54.75mm
length	42.5mm
width	10.2mm
Height	46mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Fixed bridge	/

Insertion bridge	EB2-10 / EB3-10 / EB10-10
End cover	/
Separating disk	/
Partition plate	/

Marker

Top marker	/
Marker	ZB10
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

Bridge	EBXX-10
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11010000006
パッキングユニット	50
最小注文数量	50

1 個あたりの重量（梱包を
含めない）

29.646