


概要

製品情報



DC16-PE-11020000017

Screw type Din-Rail TB, connector method: Screw/plug-in connector,
Number of connectors: 2, Number of potentials: 1, Cross section: 1.5 mm² -
25 mm², AWG: 14 - 3, Width: 12 mm, Color: green-yellow, Mounting type:
NS 35/7.5, NS 35/15

製品の特長

- ☒ Steel screw connection technology, reliable connection;
- ☒ Grounding structure, protection circuit;
- ☒ The box has a baffle to prevent mis-insertion;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.75-6mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	1-16mm ²
Conductor cross section flexible (ferrule without plastic sleeve)	1-16mm ²
Strip length	12mm
Conductor cross section solid	1.5~25mm ²
Conductor cross section flexible	1.5~25mm ²

Conductor cross section solid AWG	14~3
screw thread	M5
Tightening torque	2.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	50.9mm
End plate width	1.5mm
NS 35/15 Height	58.4mm
length	50.25mm
width	12mm
Height	49.4mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker	/
Side marker	ZT12
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×6.5
Bridge	/
End cover	D-DC16
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

End cover	D-DC16
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号

11020000017

パッキングユニット	20
最小注文数量	20
1 個あたりの重量（梱包を 含めない）	34.084