


概要

製品情報



DC2.5-PE-11020000028

Screw type Din-Rail TB, connector method: Screw/plug-in connector,
Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² -
4 mm², AWG: 28 - 12, Width: 5.1 mm, Color: green-yellow, Mounting
type: NS 35/7.5, NS 35/15

製品の特長

- ☒ Steel screw connection technology, reliable connection;
- ☒ Grounding structure, protection circuit;
- ☒ The box has a baffle to prevent mis-insertion;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Screw type	Slotted screw
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-1.5mm ²
Strip length	8~9mm
Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~2.5mm ²
Conductor cross section solid AWG	28~12
screw thread	M2.5

Tightening torque	0.4N.m
-------------------	--------

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	41.5mm
End plate width	1.5mm
NS 35/15 Height	49mm
length	44.5mm
width	5.1mm
Height	40mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Marker

Top marker	/
Side marker	ZB5 / WB5
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Bridge	/
End cover	D-DC2.5
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB5
Marker cards	DBE-1

Accessories

End cover	D-DC2.5
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11020000028
パッキングユニット	100
最小注文数量	100

1 個あたりの重量（梱包を 含めない）	6.61
------------------------	------