


概要

製品情報



DS2.5-PE-11040000031

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 26 - 12, Width: 5.2 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

製品の特長

- ☒ Push-in connection technology, tool-free operation, more convenient and faster;
- ☒ With orange wire button, one word or cross screwdriver can release wire.
- ☒ Optional marker to avoid wire mis-inserting.
- ☒ Equipped with test holes for easy testing of the circuit.

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length	10~12mm
Conductor cross section solid AWG	26~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	48.6mm
width	5.2mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker	ZB5 / ZS5
Side marker	ZSF5
Marker support	DTH5-25x5 / DTH5-25x12

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5
Bridge	/
End cover	D-DS2.5

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

ビジネスデータ

注文番号	11040000031
パッキングユニット	100
最小注文数量	100
1 個あたりの重量（梱包を 含めない）	7