

概要

製品情報



FY-M12A-05M-M12A-05F-S-0100-20030001904

M12A-Y hybrid distributor(PCB), Input terminal: Male, Output terminal1: Female, Output terminal2: M8 Female

製品の特長

- ☒ Single wire input, Multi wire output
- ☒ Cost saving and convenient installation
- ☒ Protection level: IP67/68
- ☒ Widely used in industrial automation, rail transit and other industries

製品認証

RoHS REACH

技術データ

製品チャート

3Dモデル

□

Environmental conditions

Ambient temperature	-25℃...85℃
IP class	IP67

General parameters

Rated current	4A
	60V
Number of potentials	4
	5
Insulation resistance	≥ 100 MΩ

Error-proof coding	A-Code
Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100

Material

Flammability rating ,in line with UL97	HB
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PU
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
	Copper alloy, nickel plated
Sealing material	Silicon

アクセサリ

ビジネスデータ

注文番号	20030001904
パッキングユニット	/
最小注文数量	100
1 個あたりの重量（梱包を 含めない）	/