

## 概要

## 製品情報

**FY-M12D-04F-M12D-04F-Q-0100-20030002025**

M12D-Y distributor(PCB),Input terminal:Female,Output terminal1:Female,Output terminal2:Male

## 製品の特長

- ☑Single wire input, Multi wire output
- ☑Cost saving and convenient installation
- ☑Protection level:IP67/68
- ☑Widely used in industrial automation, rail transit and other industries

## 製品認証

**RoHS REACH**

## 技術データ

## 製品チャート

## 3Dモデル

□

## Environmental conditions

Ambient temperature

-25℃...85℃

IP class

IP67

## General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

|                             |       |
|-----------------------------|-------|
| Overvoltage level           | II    |
| Pollution level             | 3     |
| Insertion and pullout cycle | ≥ 100 |

Material

|                                        |                           |
|----------------------------------------|---------------------------|
| Flammability rating ,in line with UL97 | HB                        |
| Contact material                       | CuZn                      |
| Material contact surface               | Au                        |
| Contact carrier material               | PU                        |
| Fixture body material                  | TPU                       |
| Coil material                          | Zinc alloy, nickel plated |
| Sealing material                       | Silicon                   |

アクセサリ

ビジネスデータ

|                        |             |
|------------------------|-------------|
| 注文番号                   | 20030002025 |
| パッキングユニット              | /           |
| 最小注文数量                 | 100         |
| 1 個あたりの重量（梱包を<br>含めない） | /           |