

概要

製品情報



PB-M8A-03P-FF-SL7001-20020000013

Field mounted, Unshielded, Female, Straight, M8, Coding A, Screw connector, Cable External cable diameter 4.0~6.0 mm

製品の特長

- ☑ Sealing optimization, protection level up to IP67
- ☑ Meet the harsh environment
- ☑ Miniature connector, Space saving
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

製品認証



RoHS

REACH



技術データ

製品チャート

3Dモデル

□

Environmental conditions

Ambient temperature	-40℃...85℃
IP class	IP67

General parameters

Rated current	3A
	60V
Number of potentials	3
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code

Overvoltage level	II
Pollution level	3
Connection method	Screw connection
Insertion and pullout cycle	≥ 100
Torque	0.3 Nm ... 0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Copper alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-104
--------------------------	-----------------

Dimension

Assembled cable outer diameter	4.0-6.0mm
Assembled conductor cross section	0.25~0.34 mm²
	24~22 AWG

アクセサリ

ビジネスデータ

注文番号	20020000013
パッキングユニット	/
最小注文数量	100

1 個あたりの重量（梱包を
含めない）

/