


概要

製品情報

**SR-M12D-04P-FF-SF7003-20030000377**

Sensor/Actuator Female socket,M12,Coding D,Unshielded,Rear panel installation/M12*1.0 Thread mounted,90° horizontal pins

製品の特長

- ☑ Sealing optimization, protection level up to IP67
- ☑ Meet the harsh environment
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

製品認証

**RoHS****REACH**

技術データ

製品チャート

3Dモデル

□

Environmental conditions

Ambient temperature

-40℃...105℃

IP class

IP67

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Rear board installation

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

アクセサリ

Accessories

Sealing cap	CAP-M12-MP-8003
-------------	-----------------

ビジネスデータ

注文番号	20030000377
パッキングユニット	/
最小注文数量	100
1 個あたりの重量（梱包を含めない）	/

