概要

製品情報



DG44-1-12060000142

Double-layer barrier terminal blocks,Rated current:20A.Rated voltage（UL）:300V,Cross section:18~12AWG,pitch:9.52mm,Color:black,Contact surface:Tin

製品の特長

☑ Screw connection for worldwide use
☑ Fence type wiring structure, stable and reliable connection
☑ Used in industrial control field to save equipment installation space

製品認証

CE

技術データ

製品チャート

3Dモデル

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

AWG	18~12AWG

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Item properties	
Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3.5
Pitch	9.52mm
Number of potentials	4
Pluggable or not	no
Number of rows	2

Material data	
Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	UL1059

Environmental data	
Ambient temperature (operation)	-40℃~125℃

アクセサリ

Accessories	

ビジネスデータ

注文番号	12060000142
パッキングユニット	160
最小注文数量	/
1個あたりの重量（梱包を含めない）	59.4