

概要

製品情報



DG98-A-12040000304

Transfer barrier terminal blocks, Rated current: 45A. Rated voltage (UL) : 600V, Cross section: 22~8AWG, pitch: 14.28mm, Color: black, Contact surface: Tin

製品の特長

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Panel mounting for electrical transfer between two devices in a small space

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

AWG	22~10AWG
Torque	1.2N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	30A
Rated current (D)	5A

Rated current (C)	30A
-------------------	-----

Electrical parameters IEC

Rated current	1000V
	41A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Pitch	14.28mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~125℃
---------------------------------	-----------

アクセサリ	
Accessories	
Bridge	K54

ビジネスデータ	
注文番号	12040000304
パッキングユニット	90
最小注文数量	/
1 個あたりの重量（梱包を 含めない）	25