

概要

製品情報



DG2000-B-12010000224

Single-layer PCB barrier terminal blocks, Rated current: 75A. Rated voltage (UL) : 600V, Cross section: 26~4AWG, pitch: 20.00mm, Color: black, Contact surface: Tin

製品の特長

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ High current electrical connections at the power end can be met

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

AWG

26~4AWG

Torque

2.5N.m

Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated voltage (D)

600V

Rated current (B)	70A
Rated current (D)	5A
Rated current (C)	70A

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M6
Pitch	20mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

アクセサリ

Accessories

ビジネスデータ	
注文番号	12010000224
パッキングユニット	18
最小注文数量	/
1 個あたりの重量（梱包を 含めない）	63