


概要

製品情報



DGK12-111-13030000123

Building electronic housing ,length :53.6mm,DIN rail housing ,Upper housing with vent ,Can be used in distribution box comply with DIN 43880 standard , IP class:IP20.

製品の特長

- ☒ Modern design
- ☒ flexible PCB connection
- ☒ high-efficiency DIN rail connector is optional
- ☒ Support Wall-mounted installation and distribution power box installation in accordance with DIN 43880 standards

製品認証

技術データ

製品チャート

3Dモデル

□

Dimensions

width	53.6mm
length	89.7mm
Height	60.7mm
Depth from top edge of DIN rail	54.7mm

PCB data

Number of PCB holders	15 (Upper cover 6+Base 9)
PCB thickness	1.8mm
Installation location	Vertical &horizontal(DIN rail)
PCBType of installation	Latching

Item properties

IP class	IP20
Connection levels	1(Both sides)
with ventilation openings	Yes
Maximum connection	32 (pitch: 2.5 mm); 20 (pitch: 5 mm); 12 (pitch: 7.5 mm)

Material data

color	Upper housing: light gray bottom housing: black
Material	PC
Flammability rating	V2

Environmental data

Ambient temperature (assembly)	-5℃～ +100℃
Ambient temperature (operation)	-40℃～ +110℃
Ambient temperature (storage / transport)	-40℃～ +70℃

アクセサリ

Accessories

--	--

ビジネスデータ

注文番号	13030000123
パッキングユニット	10
最小注文数量	10
1 個あたりの重量（梱包を 含めない）	50