

概要

製品情報



MIL cable-DX210-4S-500-00A(H)-23040000011

MIL cable,connector1:IDC/MIL female connector (1×40 Core,90° output) ,connector2:IDC/MIL female connector (1×40 Core,90° output)

製品の特長

- ☒ The cable is soft and has good bending resistance
- ☒ Prefabricated connector, beautiful appearance
- ☒ Provide single-ended and double-ended cables
- ☒ Save wiring time, and can achieve fast wiring with the company's interface module

製品認証

技術データ

製品チャート

3Dモデル

□

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
-----------------------------------	-------

Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	7.6mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	40
spacing	2.54mm
Exit angle	90°

Connection data 2

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	40
Exit angle	90°
spacing	2.54mm

Overview

Single wire, number of twisted wires	40
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC
Outer sheath,color	black

アクセサリ

ビジネスデータ	
注文番号	23040000011
パッキングユニット	1
最小注文数量	10
1 個あたりの重量（梱包を 含めない）	50