


概要

製品情報



DGV4-10090000018

Through-wall terminal blocks, Rated current: 41A. Rated voltage (III/3) : 400V, Width: 8.1mm, Color: gray, Contact surface : Tin

製品の特長

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

製品認証

技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~6.0mm ²
AWG	30~10AWG
Torque	0.5N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A
Rated current (D)	10A

Electrical parameters IEC

Rated current(III/3)	400V
Rated current	400V
	41A
Rated surge voltage(III/3)	6KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	8.1mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40℃~105℃

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10090000018
パッキングユニット	50
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	10.5