


概要

製品情報



DGH25-10090000007

Through-wall terminal blocks, Rated current: 101A. Rated voltage
(III/3) : 500V, Width: 15.0mm, Color: gray, Contact surface : Tin

製品の特長

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

製品認証

技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	6~35mm ²
Conductor cross section flexible	10~25mm ²
AWG	8~2AWG
Torque	4N.m
Strip length	19mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	115A

Rated current (D)	5A
Rated current (C)	115A

Electrical parameters IEC

Rated current(III/3)	500V
Rated current	500V
	101A
Rated surge voltage(III/3)	6KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M5
Pitch	15.1mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ	
Accessories	
Coding strip	ZB15
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

ビジネスデータ	
注文番号	10090000007
パッキングユニット	12
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	133