


概要

製品情報



DG801-10080000099

Feed through terminal blocks, Rated current: 6.3A. Rated voltage
(III/2) : 250V, pitch: 10.0mm, Color: gray, Contact surface : Ni

製品の特長

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Built-in fuse for over-current protection
- ☒ Panel mounting, suitable for various situations

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	0.5~2.5mm ²
Conductor cross section flexible	0.5~2.5mm ²
AWG	22~14AWG
Torque	0.5N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V

Rated current (B)	6.3A
Rated current (D)	6.3A

Electrical parameters IEC

Rated current	250V
	6.3A
Rated current(III/2)	250V
Rated power frequency voltage(1min)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	10mm
Number of potentials	1
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998/IEC60127
--------------------	--------------------------

Environmental data

Ambient temperature (operation)

-40℃~105℃

アクセサリ

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

ビジネスデータ

注文番号

10080000099

パッキングユニット

425

最小注文数量

30

1 個あたりの重量（梱包を
含めない）

4.71