

概要

製品情報



DG635-6.35-10040000615

PCB terminal blocks, Rated current: 32A, Rated voltage (III/2) 450V, Cross section: 1.5~4.0mm², pitch: 6.35mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

製品の特長

- ☒ Fixed screw connection technology, safe and reliable
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

1.5~4.0mm²

Conductor cross section flexible

1.5~4.0mm²

AWG

26~10AWG

Torque

0.5N.m

Strip length

8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A
Rated current (D)	10A

Electrical parameters IEC

Rated current	450V
	32A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	6.35mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

ビジネスデータ	
注文番号	10040000615
パッキングユニット	900
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	5.09