

概要

製品情報



DG632-5.0-10040000564

PCB terminal blocks, Rated current: 24A, Rated voltage (III/2) 250V, Cross section: 0.5~2.5mm², pitch: 5.0mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

製品の特長

- ☒ Fixed screw connection technology, safe and reliable
- ☒ Universal installation method to ensure a high degree of flexibility in device design

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.5~2.5mm²

Conductor cross section flexible

0.5~2.5mm²

AWG

28~12AWG

Torque

0.4N.m

Strip length

6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated current	250V
	24A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ	
Accessories	
Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

ビジネスデータ	
注文番号	10040000564
パッキングユニット	200
最小注文数量	30
1 個あたりの重量（梱包を含めない）	2.7083333333333