


概要

製品情報



DG285-10080000083

Feed through terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 450V, pitch: 11.5mm, Color: White, Contact surface : Ni

製品の特長

- ☒ Pluggable screw connection , reliable wiring
- ☒ Can realize horizontal wire-to-wire connection

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	1.0~2.5mm ²
Conductor cross section flexible	1.0~2.5mm ²
AWG	18~12AWG
Torque	0.5N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	16A

Electrical parameters IEC

Rated current	450V
	24A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	11.5mm
Number of potentials	3
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10080000083
パッキングユニット	200
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	18.7