

概要

製品情報



DG252-10080000069

Feed through terminal blocks, Rated current: 17.5A. Rated voltage
(III/2): 450V, pitch: 10.0mm, Color: White, Contact surface : Zn

製品の特長

- ☒ Multiple wiring holes for current distribution
- ☒ Panel mounting, suitable for various situations
- ☒ Can realize horizontal wire-to-wire connection

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	0.5~1.5mm ²
AWG	22~16AWG
Torque	0.8N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

Electrical parameters IEC

Rated current	450V
	17.5A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Pitch	10mm
Number of potentials	12
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10080000069
パッキングユニット	100
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	30