


概要

製品情報



DG250W-3.5-10060001582

PCB spring terminal blocks, Rated current: 3A. Rated voltage
(III/2): 250V, pitch: 3.5mm, Color: gray, Contact surface: Tin

製品の特長

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~0.75mm²

Conductor cross section flexible

0.2~0.75mm²

AWG

22~18AWG

Strip length

8mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (C)

300V

Rated current (B)	4A
Rated current (C)	4A

Electrical parameters IEC

Rated current	250V
	3A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Push-in spring connection
Pitch	3.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40℃~105℃

アクセサリ

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

ビジネスデータ

注文番号

10060001582

パッキングユニット

2790

最小注文数量

30

1 個あたりの重量（梱包を
含めない）

0.87