


概要

製品情報



DG238-10.0-10060000985

PCB spring terminal blocks, Rated current: 24A. Rated voltage
(III/2): 450V, pitch: 10.0mm, Color: White, Contact surface: Tin

製品の特長

- ☒ Multiple wiring holes for current distribution
- ☒ Panel mounting, suitable for various situations
- ☒ Can realize horizontal wire-to-wire connection

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

AWG	22~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	600V
Rated current (B)	20A

Electrical parameters IEC

Rated current	450V
	24A
Rated current(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
--------	---

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10060000985
パッキングユニット	100
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	6.25