

概要

製品情報



DG224-8.0-10060001097

PCB spring terminal blocks, Rated current: 24A. Rated voltage
(III/2): 450V, pitch: 8.0mm, Color: gray, Contact surface: Tin

製品の特長

- ☒ Cage clamp connection technology, fast wiring
- ☒ Can realize horizontal wire-to-wire connection

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	22~12AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	22A
Rated current (D)	10A

Electrical parameters IEC

Rated current	450V
	24A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Connection method	Push-in spring connection
Pitch	8mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~85℃
---------------------------------	----------

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10060001097
パッキングユニット	100
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	4.5