

## 概要

### 製品情報



## DG141V-2.54-10060000426

PCB spring terminal blocks, Rated current: 6A. Rated voltage  
(III/2): 130V, pitch: 2.54mm, Color: green, Contact surface: Tin

### 製品の特長

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

### 製品認証



## 技術データ

### 製品チャート

### 3Dモデル

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.2~1.0mm<sup>2</sup>

Conductor cross section flexible

0.2~1.0mm<sup>2</sup>

AWG

24~20AWG

Strip length

11mm

### Electrical parameters UL

Rated voltage (B)

150V

Rated voltage (C)

150V

|                   |      |
|-------------------|------|
| Rated voltage (D) | 150V |
| Rated current (B) | 2A   |
| Rated current (D) | 2A   |
| Rated current (C) | 2A   |

#### Electrical parameters IEC

|                                     |        |
|-------------------------------------|--------|
| Rated voltage                       | 130V   |
| Rated current                       | 6A     |
| Rated current(III/2)                | 130V   |
| Rated power frequency voltage(1min) | 1.25KV |

#### Item properties

|                      |                               |
|----------------------|-------------------------------|
| Connection direction | 90°                           |
| Type of installation | PCB welding                   |
| Pin arrangement      | Double-row in a straight line |
| Connection method    | Push-in spring connection     |
| Pitch                | 2.54mm                        |
| Number of potentials | 1                             |
| Pluggable or not     | no                            |
| Number of rows       | 1                             |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | Copper alloy              |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |

|                                 |                 |
|---------------------------------|-----------------|
| Flammability rating             | UL94V-0         |
| Mechanical tests                |                 |
| Test Specification              | UL1059/IEC60998 |
| Environmental data              |                 |
| Ambient temperature (operation) | -40℃~105℃       |

|                |   |
|----------------|---|
| アクセサリ          |   |
| Accessories    |   |
| Coding strip   | / |
| Bridge         | / |
| Marking strip  | / |
| Others         | / |
| Tool           |   |
| Operating tool | / |
| Screwdriver    | / |

|                        |             |
|------------------------|-------------|
| ビジネスデータ                |             |
| 注文番号                   | 10060000426 |
| パッキングユニット              | 500         |
| 最小注文数量                 | 30          |
| 1 個あたりの重量（梱包を<br>含めない） | 0.81        |