


概要

製品情報



DG137TM-15.0-10040002028

PCB terminal blocks, Rated current: 115A, Rated voltage (III/2) 1000V, Cross section: 4-35mm², pitch: 15.0mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

製品の特長

- ☒ Fixed screw connection technology, reliable wiring
- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ Double solder pins reduce mechanical stress on the solder joints

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

4.0~35mm²

Conductor cross section flexible

4.0~35mm²

AWG

20~2AWG

Torque

2N.m

Strip length

18mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	115A
Rated current (D)	5A
Rated current (C)	115A

Electrical parameters IEC

Rated voltage	1000V
Rated current	115A
Rated current(III/2)	1000V
Rated power frequency voltage(1min)	3.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M5
Pitch	15mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper

Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	Cross recessed screwdriver

ビジネスデータ

注文番号	10040002028
パッキングユニット	48
最小注文数量	30
1 個あたりの重量（梱包を含めない）	43.24

