

概要

製品情報

**DG10HS-1.2-10080000016**

Feed through terminal blocks, Rated current: 41A. Rated voltage
(III/2): 450V, pitch: 10.0mm, Color: natural, Contact surface: Zn

製品の特長

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Panel mounting, suitable for various situations

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	1.0~6mm ²
Conductor cross section flexible	1.0~6.0mm ²
AWG	18~10AWG
Torque	0.5N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A

Rated current (D)	10A
-------------------	-----

Electrical parameters IEC

Rated current	450V
	41A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	10mm
Number of potentials	12
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10080000016
パッキングユニット	125
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	30.6