


概要

製品情報

**9EDGKH-7.5-10020001589**

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/2) : 1000V, pitch: 7.5mm, Color: black, Contact surface : Tin

製品の特長

- ☒ Cage clamp pluggable connection technology, reliable wiring
- ☒ Self-locking structure with sound prompt, safe to use

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	16A
Rated current (D)	5A

Rated current (C)	16A
-------------------	-----

Electrical parameters IEC

Rated voltage	1000V
Rated current	20A
Rated current(III/2)	1000V
Rated surge voltage(III/2)	8KV

Item properties

Connection direction	0°
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	Gold plate
Insulation Materials	PA66
Insulating material group	II
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/

ビジネスデータ

注文番号	10020001589
パッキングユニット	330
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	9.316