


概要

製品情報



8EDGKRB-5.0-10020001736

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/2) : 320V, pitch: 5.0mm, Color: gray, Contact surface : Tin

製品の特長

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Cage clamp connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	22~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current	20A
Rated current(III/2)	320V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Type of installation	panel
Pin arrangement	Single row in a straight line
Connection method	spring-cage connection
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40℃~105℃

アクセサリ

Tool

Screwdriver

/

Operating tool

DG010

Accessories

Coding strip

/

Bridge

DG018-5.0

Marking strip

/

Others

/

ビジネスデータ

注文番号

10020001736

パッキングユニット

100

最小注文数量

30

1 個あたりの重量（梱包を
含めない）

3.5