


概要

製品情報



5EDGKM-10.16-10010002939

Pluggable terminal blocks, Rated current: 57A. Rated voltage
(III/3) : 600V, pitch: 10.16mm, Color: green, Contact surface : Tin

製品の特長

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying parts can be installed
- ☒ Universal installation method, suitable for various situations

製品認証



技術データ

製品チャート

3Dモデル

□

Connection capacity

Conductor cross section solid	0.5~10mm ²
Conductor cross section flexible	0.5~10mm ²
AWG	20~6AWG
Torque	1.2N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	300V

Rated current (B)	52A
Rated current (D)	10A
Rated current (C)	52A

Electrical parameters IEC

Rated voltage	600V
Rated current(III/3)	600V
Rated current	57A
Rated surge voltage(III/3)	6KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	10.16mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	Silver plated
Contact zone metal surface	Silver plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ	
Tool	
Screwdriver	/
Operating tool	/
Accessories	
Coding strip	5EDG-PWI
Bridge	/
Marking strip	/
Others	/

ビジネスデータ	
注文番号	10010002939
パッキングユニット	120
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	18.865