

概要

製品情報



2EDG-STD-5.0-10010002817

Pluggable terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 250V, pitch: 5.0mm, Color: green, Contact surface : Tin

製品の特長

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Panel mounting, suitable for various situations

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

1.0~2.5mm²

Conductor cross section flexible

1.0~2.5mm²

AWG

28~12AWG

Torque

0.4N.m

Strip length

8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	24A
Rated current(III/2)	250V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ	
Tool	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	/
Accessories	
Coding strip	2EDG-PWI
Bridge	/
Marking strip	/
Others	/

ビジネスデータ	
注文番号	10010002817
パッキングユニット	100
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	4.33