

## 概要

### 製品情報



## 15EDGRM-LD-3.81-10030000593

Pluggable terminal blocks, Rated current: 7A. Rated voltage  
(Ⅱ/2): 250V, pitch: 3.81mm, Color: green, Contact surface: Tin

### 製品の特長

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is parallel to the PCB
- ☒ Adapt to LED indicator, visual mistake proof

### 製品認証



## 技術データ

### 製品チャート

### 3Dモデル

□

### Processing notes

Process

Wave soldering/manual soldering

### Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

8A

### Electrical parameters IEC

Rated voltage

250V

Rated current

7A

Rated current(Ⅱ/2)

250V

Rated surge voltage(Ⅱ/2)

2.5KV

#### Item properties

|                      |                               |
|----------------------|-------------------------------|
| Connection direction | 0°                            |
| Type of installation | PCB welding                   |
| Pin arrangement      | Single row in a straight line |
| Pitch                | 3.81mm                        |
| Number of potentials | 8                             |
| Pluggable or not     | Yes                           |
| Number of rows       | 1                             |

#### Material data

|                            |                           |
|----------------------------|---------------------------|
| Environmental items        | Compliant with REACH/RoHS |
| Contact material           | Copper alloy              |
| Contact zone metal surface | tin-plated                |
| Insulation Materials       | PA66                      |
| Insulating material group  | I                         |
| Flammability rating        | UL94V-0                   |

#### Mechanical tests

|                    |                 |
|--------------------|-----------------|
| Test Specification | IEC60947/UL1059 |
|--------------------|-----------------|

#### Environmental data

|                                 |             |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~105°C |
|---------------------------------|-------------|

#### アクセサリ

#### Tool

|                |   |
|----------------|---|
| Screwdriver    | / |
| Operating tool | / |

Accessories

|               |           |
|---------------|-----------|
| Coding strip  | /         |
| Bridge        | /         |
| Marking strip | /         |
| Others        | 15EDG-PWI |

ビジネスデータ

|                        |             |
|------------------------|-------------|
| 注文番号                   | 10030000593 |
| パッキングユニット              | /           |
| 最小注文数量                 | 30          |
| 1 個あたりの重量（梱包を<br>含めない） | 4.172       |